

Gas and Vapor Detectors and Sensors - Component

COMPANY

DANFOSS L L C

11655 Crossroads Cir
Baltimore, MD 21220 United States

E534311

A2L refrigerant sensors for detection of R-454B refrigerant gas, Models DST G54B-AB-09, DST G54B-AB-10, DST G54B-AB-11, DST G54B-AB-12, DST G54B-AB-13, DST G54B-AB-14, DST G54B-AB-15, DST G54B-AB-16, DST G54B-AB-17, DST G54B-AB-18, DST G54B-AB-19, and DST G54B-AB-20. For use only within UL Solutions certified end-product Refrigerant Detection Systems that are evaluated to the 4th edition of UL 60335-2-40.

A2L refrigerant sensors for detection of R-454B refrigerant gas, Models DST G54B-A0-09, DST G54B-A0-10, DST G54B-A0-11, DST G54B-A0-12, DST G54B-A0-13, DST G54B-A0-14, DST G54B-A0-15, DST G54B-A0-16, DST G54B-A0-17, DST G54B-A0-18, DST G54B-A0-19, and DST G54B-A0-20. For use only within UL Solutions certified end-product Refrigerant Detection Systems that are evaluated to the 4th edition of UL 60335-2-40.

A2L refrigerant sensors for detection of R-454B refrigerant gas, Models DST G54B-A1-09, DST G54B-A1-10, DST G54B-A1-11, DST G54B-A1-12, DST G54B-A1-13, DST G54B-A1-14, DST G54B-A1-15, DST G54B-A1-16, DST G54B-A1-17, DST G54B-A1-18, DST G54B-A1-19, and DST G54B-A1-20. For use only within UL Solutions certified end-product Refrigerant Detection Systems that are evaluated to the 4th edition of UL 60335-2-40.

A2L refrigerant sensors for detection of R-454B refrigerant gas, Models DST G54B-B0-09, DST G54B-B0-10, DST G54B-B0-11, DST G54B-B0-12, DST G54B-B0-13, DST G54B-B0-14, DST G54B-B0-15, DST G54B-B0-16, DST G54B-B0-17, DST G54B-B0-18, DST G54B-B0-19, and DST G54B-B0-20. For use only within UL Solutions certified end-product Refrigerant Detection Systems that are evaluated to the 4th edition of UL 60335-2-40.

A2L refrigerant sensors for detection of R-32 refrigerant gas, Models DST GR32-AB-09, DST GR32-AB-10, DST GR32-AB-11, DST GR32-AB-12, DST GR32-AB-13, DST GR32-AB-14, DST GR32-AB-15, DST GR32-AB-16, DST GR32-AB-17, DST GR32-AB-18, DST GR32-AB-19, and DST GR32-AB-20. For use only within UL Solutions certified end-product Refrigerant Detection Systems that are evaluated to the 4th edition of UL 60335-2-40.

A2L refrigerant sensors for detection of R-32 refrigerant gas, Models DST GR32-A0-09, DST GR32-A0-10, DST GR32-A0-11, DST GR32-A0-12, DST GR32-A0-13, DST GR32-A0-14, DST GR32-A0-15, DST GR32-A0-16, DST GR32-A0-17, DST GR32-A0-18, DST GR32-A0-19, and DST GR32-A0-20. For use only within UL Solutions certified end-product Refrigerant Detection Systems that are evaluated to the 4th edition of UL 60335-2-40.

A2L refrigerant sensors for detection of R-32 refrigerant gas, Models DST GR32-A1-09, DST GR32-A1-10, DST GR32-A1-11, DST GR32-A1-12, DST GR32-A1-13, DST GR32-A1-14, DST GR32-A1-15, DST GR32-A1-16, DST GR32-A1-17, DST GR32-A1-18, DST GR32-A1-19, and DST GR32-A1-20. For use only within UL Solutions certified end-product Refrigerant Detection Systems that are evaluated to the 4th edition of UL 60335-2-40.

A2L refrigerant sensors for detection of R-32 refrigerant gas, Models DST GR32-B0-09, DST GR32-B0-10, DST GR32-B0-11, DST GR32-B0-12, DST GR32-B0-13, DST GR32-B0-14, DST GR32-B0-15, DST GR32-B0-16, DST GR32-B0-17, DST GR32-B0-18, DST GR32-B0-19, and DST GR32-B0-20. For use only within UL Solutions certified end-product Refrigerant Detection Systems that are evaluated to the 4th edition of UL 60335-2-40.

Marking: Company name, device designation and the Recognized Component Mark  on the product or smallest unit container in which the product is packaged.

Last Updated on 2024-03-04

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."