



Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	Danfoss Drives AS
Address	Ulsnæs 1, Gråsten, 6300, Denmark
Place of Production	Harju Elekter UAB Tinklu g. 35R, Panevezys, LT-35115, Lithuania
Place of Production	VEO Oy Runsorintie 5, Vaasa, 65380, Finland
Place of Production	Danfoss Drives, LLC 12 TW Alexander Drive, Bldg 200A, Durham, North Carolina, 27709, United States
Type	Electronic Frequency Convertor
Description	Active Front End and Diode Front End
Trade Name	VACON 3000 HV AC Drives
Application	For use in environmental categories ENV1, ENV2, ENV3 as defined in Lloyd's Register Test Specification No. 1, December 2019
Specified Standard	Lloyds Register Rules and Regulation for the Classification of Ships, July 2022 Lloyds Register Test Specification Number 1 December 2019

Matthew Partyka

Electrical & Control - Lead Specialist to
Lloyd's Register Canada Limited
A member of the Lloyd's Register group

237 Brownlow Avenue, Suite 200, Dartmouth, NS.
B3B2C7, Canada

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



Type Approval Certificate

IEC 61800-5-1
UL 347A
CSA C22.2 no 274

Ratings

See Appendix

Other Conditions

Installation of this equipment for marine applications is to be in accordance with current Lloyd's Register Rules and Regulations.

Converter 100kW and over where intended for use for essential and emergency services, are to be surveyed by the Surveyors during manufacture and testing.

Radiated and conducted emissions meet the requirement for equipment in general power distribution zones.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register Canada Limited of any modification or changes to the equipment in order to obtain a valid Certificate.

The Design Appraisal Document LR23268843TA and its supplementary Type Approval Terms and Conditions form part of this Certificate.

ATTACHMENT TO CERTIFICATE OF TYPE APPROVAL No.

Appendix

TYPE	AFE Drives: VACON3000-ED-4Q-0340-04+xxxx VACON3000-ED-4Q-0425-03+xxxx VACON3000-ED-4Q-0510-04+xxxx VACON3000-ED-4Q-0640-03+xxxx VACON3000-ED-4Q-0650-04+xxxx VACON3000-ED-4Q-0820-03+xxxx VACON3000-ED-4Q-0980-04+xxxx VACON3000-ED-4Q-1230-03+xxxx DFE Drives: VACON3000-ED-12-0340-04+xxxx VACON3000-ED-12-0425-03+xxxx VACON3000-ED-12-0510-04+xxxx VACON3000-ED-12-0640-03+xxxx VACON3000-ED-12-0650-04+xxxx VACON3000-ED-12-0820-03+xxxx VACON3000-ED-12-0980-04+xxxx VACON3000-ED-12-1230-03+xxxx xxxx – options available from Danfoss: INPUT FREQUENCY +LS50 - 50 Hz +LS60 - 60 Hz INPUT FILTER +PI00 - None +PILC - LC filter +PICM - LCL with common mode filter OUTPUT FILTER +POA0- None +PODU - dU/dt filter +POSI -Sine-wave filter
------	---

ATTACHMENT TO CERTIFICATE OF TYPE APPROVAL No.

	OUTPUT COMMON MODE FILTER +POB0 - None +POCM - Output common mode filter BRAKE CHOPPER OPTION +DB00 - None +DBC0 - Included AFE GRID OPTIONS +PNSI - Not applicable +PSSI - Small Source Impedance +PHSI - High Source Impedance FILTER CHOKES +PFCH - Included C- SLOT OPTION BOARD +SC00 - No board +SCB1 - 6 programmable DI/DO +SCB2 - 1RO(NO/NC),1RO(NO),therm +SCB4 - AI,2AO(mA,isol),+24V/EXT +SCB5 - 3RO(NO) +SCB9 - 1RO(NO),5pcs of 41-240VAC +SCBF - 1AO, 1DO, 1RO +SCBH - 3 temp meas channels D-SLOT OPTION BOARD +SD00 - No board +SDB1 - 6 programmable DI/DO +SDB2 - 1RO(NO/NC),1RO(NO),therm +SDB4 - AI,2AO(mA,isol),+24V/EXT +SDB5 - 3RO(NO) +SDB9 - 1RO(NO),5pcs of 41-240VAC +SDBF - 1AO, 1DO, 1RO +SDBH - 3 temp meas channels +SDD3 - RS232 adapt(no isol.) +SDE3 - PROFIBUS DP +SDE5 - PROFIBUS DP with Sub-D9 +SDE6 - CANopen
--	--

ATTACHMENT TO CERTIFICATE OF TYPE APPROVAL No.

	+SDE7 - DeviceNet +SDE9 - 2-port ethernet +SDEA - Advanced 2-port ethernet +SDEC - EtherCAT E-SLOT OPTION BOARD +SE00 - No board +SEB1 - 6 programmable DI/DO +SEB2 - 1RO(NO/NC),1RO(NO),therm +SEB4 - AI,2AO(mA,isol),+24V/EXT +SEB5 - 3RO(NO) +SEB9 - 1RO(NO),5pcs of 41-240VAC +SEBF - 1AO, 1DO, 1RO +SEBH - 3 temp meas channels +SED3 - RS232 adapt(no isol.) +SEE3 - PROFIBUS DP +SEE5 - PROFIBUS DP with Sub-D9 +SEE6 - CANopen +SEE7 - DeviceNet +SEE9 - 2-port ethernet +SEEA - Advanced 2-port ethernet +SEEC - EtherCAT KEYPAD OPTION +HMGR - Graphical Keypad MK01 ISOLATED AUX TRANSFORMER +QAIT – Included +QAIS - Included, extra XFMR STO circuit GROUNDING SWITCH +QGSW – Included +QGSK - Included with kirk key interlock POTENTIAL TRANSFORMER +QP00 - None STO/SS1 +QS00 - None +QSTO - Included
--	---

ATTACHMENT TO CERTIFICATE OF TYPE APPROVAL No.

	SURGE PROTECTION DEVICE +QS01 - None +QSPD - Included MOUNTING RACK +PM00 - None MODULES SEALING +HG00 - None +HGAS - Gasket sealing CONTROL & FAN VOLTAGE +QFV1 115 V +QFV2 230 V DC CAP OPTIONS +PD00 - No additional +PDC1 - One additional DC cap +PDC2 - Two additional DC caps LIQUID COOLING OPTION +PLIN- Industrial water, grounded heat DC GROUNDING RESISTOR +PGDR - DC N-to-GND R-connected +PGDN - DC N-to-GND R-disconnected SHORT CIRCUIT CURRENT RATING +PUFD - 11 kA, for 100 ms +PUF0 - 25 kA, for 100 ms +PUFE - 40 kA, for 100 ms COMMON MODE CAP TO GROUND +PGCG - Standard 25µF cap +PGCA - Alternative 4µF cap VIBRATION DAMPERS +QV00 - None +QVIB - Included COOLANT INPUT SIDE +PLCT - From top +PLCL - Lateral HEAT EXCHANGER OPTION
--	---

**ATTACHMENT TO CERTIFICATE OF TYPE APPROVAL No.**

	+PHEX- Liquid/liquid HEX included +PHET- Titanium Liquid/liquid HEX included +PH00 - Liquid/liquid HEX not included PRECHARGE INPUT VOLTAGE +QP24 - 240V +QP40 - 400V +QP48 - 480V UL/CUL APPROVAL +GAUL - Included +GNUL - None CE APPROVAL +GACE - Included +GNCE - None MARINE APPROVAL +GALR - Lloyd's Register SHIPPING PACKAGE +GSPV - Pallet with plastic wrap +GSSE - Seaworthy Wooden box CUSTOMIZATION +BM26 - VACON 3000 REGION CODE -R00) - International -R02) - North America HMI UNIT FOR MEASURE +LSSI - International SI units +LSUS - US customary units DOCUMENTATION LEVEL +DNOT - No paper manuals DOCS LANGUAGE PREFERENCES +DLUS - English language manuals INTERNAL FB SELECTION +FBIE - ProfinetIO, EthernetIP SYSTEM FIRMWARE +F3000 - Vacon3000 SW pack
--	--

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

**ATTACHMENT TO CERTIFICATE OF TYPE APPROVAL No.**

	FIRMWARE LANGUAGE PACK +FL01- UK, DE, FI, SE, IT, FR lang APPLICATION +AYYYY - VACON 3000 default app PARAMETER SET +L0000 - No appl. parameter set SOFTWARE LICENSE +PGC0 – None +PGC1 - Shore supply converter +PGC2- Grid converter
RATINGS	As per manufacturer specification.