

Data Sheet

Remote control

T70 2 ATEX Transmitter

The T70 2 ATEX certified transmitter is highly customizable with many features and accessories. A standout feature of this transmitter is the capability to control tandem systems, choosing to operate multiple cranes simultaneously with several receivers or independently with only one.

Features

- High sensitivity two-step push button
- Multi-band Radio with Full-Duplex communication
- External removable EEPROM SIM module
- Frequency management against interferences

Benefits

- Highly customizable
- Easy and fast maintenance
- High resistance to impacts
- Improved ergonomics
- Intrinsically safe

Applications

- ATEX certified for hazardous applications
- Used in crane applications

Comprehensive technical literature is online at www.danfoss.com





Technical data

Specification	Value
Stop function	Cat. 3-PLd
Ingress Protection	IP65/NEMA4
Anti-condensation system	N/A
Frequency band	Multi-band (400-930 MHz)
Main mechanisms	Push button (10 total)
Auxiliary mechanisms	Toggle and rotary switches
Removable EEPROM	External
Battery model	BT06K ATEX
Battery life	8h
Operating temperature	-20° to 70° C (-4° to 158° F)
Weight (with battery)	600 g
Harness	Hand/shoulder strap
Display	N/A
Cable connection	N/A
Range limiter	N/A
Associated receivers	R13, R70, MPCAN, R70 ATEX Z1, R13 ATEX Z2

ATEX / IECEx

Ex II 2 GD
 Ex ia IIC T4 Gb
 Ex ia IIIC T135°C Db
 CE0080
 INERIS 08ATEX0006
 IECEx INE 09.0014

CSA / UL

Class I, Division 1, Groups A, B, C & D
 Class II, Division 1, Groups E, F & G
 Zone 21, AEx iaD T135°C T4 IP65