



Counterbalance Valves Technical Information

Hydraulic Vent

VCB12-EN

OPERATION

The VCB12-EN is a cartridge style, 12-size metric counterbalance valve with hydraulic vent. This valve is 3-ported, externally piloted and low leakage. The check section allows free flow from the directional valve (port 2) to the load (port 3). Reverse flow is blocked until pilot pressure is applied at port 1. When the load pressure at port 3 rises above the pressure setting, the integral relief valve is activated and pressure is relieved from port 3 to port 2.



APPLICATIONS


Single counterbalance valves are normally used when the load is unidirectional, such as aerial lifts, cranes, or winches. In load holding applications, they can be used as hose-break valves when installed near or within an actuator. Dual cartridges can be used for controlling loads bi-directionally in motor applications, or for cylinders going over center. Since this valve is piloted at port 1, no cross port drilling is required when dual cartridges are mounted nose to nose in an HIC.

SPECIFICATIONS


Rated pressure	350 bar [5075 psi]*
Rated flow at 22 bar (319 psi)	140 l/min [37 US gal/min]
Leakage	10 drops/min @ at 70% of crack pressure
Weight	0.7 kg [1.58 lb]
Pilot ratio	4.7:1, 5.9:1, 6.9:1
Cavity	NCS12/3

* 350 bar with steel housing
210 bar with aluminum housing

SCHEMATIC



PERFORMANCE






Counterbalance Valves Technical Information

Hydraulic Vent

VCB12-EN


DIMENSIONS

mm [in]




EXAMPLE CIRCUITS

Load Holding - Single Actuator



Counterbalance Double Actuator



ORDERING INFORMATION

VCB12 - EN - 2 - A - 00 - B - XXX

VCB12-EN:
Counterbalance Valve, Pilot Port 1, 12 size (metric), external adjustment, hydraulic vent

Code	Pilot Ratio
A	6.9:1
B	4.7:1
C	5.9:1

Code	Seal Material
B	Buna-N
V	Viton

Crack Pressure Setting [in bar]

XXX: No factory setting / no stamping

For customer specified settings, enter value in bar (Example 70 bar = 70; 125 bar = 125 etc.)

Pressure Range		
Code	Pilot Ratio A,C bar [psi]	Pilot Ratio B bar [psi]
1	25-140 [363-2031]	25-120 [363-1740]
2	70 - 250 [1015-3625]	60-200 [870-2900]
3	105 - 350 [1523-5075]	90-280 [1305-4060]

Housing & Ports	Housing Nomenclature
00: Cartridge Only	No Body
SE4B: AL, 1/2 BSP	NCS12-3-SE4B
SE6B: AL, 3/4 BSP	NCS12-3-SE6B
SES6B: Steel, 3/4 BSP	NCS12-3-SES6B
SE8S: AL, #8 SAE	NCS12-3-SE8S
SE12S: AL, #12 SAE	NCS12-3-SE12S