

ENGINEERING
TOMORROW

Danfoss

Danfoss high-pressure pumps –
cleaner mist for faster
production of **quality lumber**

Zero Oil

ensures easy
maintenance and
no contamination

hpp.danfoss.com

High pressure, combined with **small nozzle apertures**, produces **excellent atomization** of clean water – perfect for wood applications

PAH/PAHT pumps



The compact pumps are available for operation with tap- and technical water. All pumps use the pumped media as lubrication ensuring 100% oil free operation. They offer long service intervals due to few components and no oil change.

Type	Media	Pressure	Flow	Temperature
PAH 2 - 12.5	Tap water	435 - 2,320 psig	0.52 - 4.54 GPM	35 - 122 °F
PAHT 2 - 12.5	Technical water	435 - 2,320 psig	0.45 - 4.36 GPM	35 - 122 °F

NWC power pack



The proven powerpack concept can be used for many applications. It has high uptime and long service intervals due to water lubricated and fully submerged pump. The high pressure provides highly effective water mist.

Power pack	Flow	Pressure	Output	Tank
NWC	6,6 - 845 Gal/h	1,160 - 1,450 psig	Up to 8 valves	6,6 Gal

Solenoid VDHT valves



The valves are corrosion resistant and dirt tolerant making them highly reliable. They are compact, high-temperature resistant and have a low pressure drop. Easy maintenance without dismantling from system.

Valve type	Q nom.	Max pressure	Max temperature	Operating pressure
VDHT 30 E (NO or NC)	7.9 GPM	2,320 psig	194 °F	50,8 psig
Block Solution 2, 3 or 4	7.9 GPM	2,320 psig	194 °F	

Water-mist nozzles



The nozzles have an excellent spray pattern making them suitable for wood applications. They are made of stainless steel AISI 316/430 ensuring high reliability and long service life.

Nozzle type	Flow	Operating/ max pressure	Spray angle	Nozzle thread
Water mist nozzle	0.11 - 0.33 GPM	1,450 / 1,885 psig	60°	M13 x 1 mm

Danfoss A/S, High Pressure Pumps, DK-6430 Nordborg, Denmark, www.hpp.danfoss.com

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.