




Danfoss Waltech® Tube Fitting Series and Assembly Machines



Tube Fitting **Trilogy**



Reliable and leak free performance, supported by:

- The quality of the tube fitting, as well as its behavior in an assembly – such as its reliability in tough conditions, pressure resistance, strength and safety.
- Repeatable accuracy of assembly, even with untrained personnel, and leak free assembly behavior.
- High corrosion resistance that ensures reliability of assembly.



A broad range of market applications and certifications that prove reliability in different conditions.



Access to a complete tube fitting portfolio from one supplier that can meet any tube fitting needs, while also ensuring consistent performance and superior reliability.



Welcome to Waltech tube fitting system For any tube fitting system, your top priority has to be reliability. That's why our Waltech series ensures excellent performance by combining robust, leak-free design with high bending and impulse resistance. Our Walpro, WalringPlus, Walform tube fitting systems offer a complete solution for any needs. With three different ways to create a connection, our systems can meet a wide range of application Waltech's design features enable simple, safe, and repeatable manual assembly—but our bespoke assembly machines also reduce errors and make assembly quicker and easier. Meanwhile, our unique Guardian Seal surface plating enables high corrosion resistance without affecting To help ensure ease-of-use and outstanding results, we also support our Waltech series with an array of end-to-end services—including machine rental, maintenance and operator training.

Walpro METALLIC SEAL CUTTING CUTTING RING

WalringPlus SOFT SEAL RING

Walform RESHAPING **SYSTEM**













TECHNOLOGY

(profile ring), controlled with captive seal, final assembly

Two-edge cutting ring Two-edge cutting ring machine assembly

Cold reshaping of the tube end with

SYSTEM FEATURES

sealing and retaining functions

Force closure, combined Force closure, separate sealing and retaining functions

Form closure, separate sealing and retaining functions

SEALING PRINCIPLE

Metal-on-metal

Elastomeric + Metal-on-metal Elastomeric + Metal-on-metal

PREFABRICATION

Assembly machine

Assembly machine

Reshaping machine

TIGHTENING TRAVEL FOR FINAL IN SERVICE ASSEMBLY

30°-60° after controlled 30°-60° after machine final assembly

Up to the point of resistance

TORQUE REDUCTION

≈ 25% compared to manual assembly

 \approx 25% compared to manual assembly of a cutting ring


> 25% compared to manual assembly of a cutting ring

RISK OF ASSEMBLY RELATED FAILURES

Minimal with controlled

Minimal with machine Minimal assembly

final assembly machine





making excessive or insufficient tightening very unlikely.

WalringPlus



Choose Walring tube fittings if soft sealing and short bending lengths are required.

The Waltech WalringPlus tube fitting features a two-edge cutting ring with additional soft sealing for both possible leak paths. Specifically optimized for thin wall tubing, it's designed to enable easy, repeatable assembly and to prevent the possible causes of leaks for dependable in-application performance.

Walform



Choose Walform tube fittings for the most demanding, high pressure and high vibration applications where safety is crucial.

Walform tube connector ensures leak free performance through double sealing (soft-seal and metal-to-metal) and is specifically engineered to ensure lasting reliability even under loads with high dynamic pressure and vibration.

- Approved for use with Benteler ZISTA SEAL® and ZISTAPLEX® tubes

Additional Walform Tube fittings feature:

- Proprietary Danfoss forming machine for tube end
- Qualified for wide range of steel and stainless steel tube materials

Waltech Tube Fitting Series

Designed to deliver

As an innovator in tube connectors, our Waltech series offers superior design—enabling exceptional performance in a wide range of applications. Our design features go well beyond simple metallic sealing cutting ring systems to deliver the best possible performance and leak-free operations.

WalringPlus design benefits

- some cutting rings with inner soft seals can be difficult and slower to assemble due to friction between the inner O-ring and the tube's outer surface. neans a significantly lower force is eeded to pull the cutting ring over the enabling easier assembly and a reduced risk of damage to the soft seal
- Where many tube fitting systems ire time-consuming and messy ubrication for all components, this is not necessary for Waltech components in carbon steel. This dry assembly process makes tube fitting assembly easier, faster, and cleaner.
- curve in the material, which increases its mechanical resistance compared to other soft seal cutting rings on the market. This eliminates the risk of the
- With the bulk of material in front of the first cutting edge, WalringPlus allows for visible control over assembly to reduce
- By automating the process of cutting ring assembly and tube forming, Danfoss bespoke WALTRECH M-R7 machine reduces the assembly time and effort required for WalringPlus, as

Walform design benefits

- secondary metallic sealing to eliminate any risk of leakage in the only possible
- Positive locking between the stud and tube ensures absolute reliability under extreme dynamic loads.
- Locked-in retaining tube removes any risk of disconnection and enables Walform to be used in safety-critical
- assembly process eradicates the risk of assembly failure.


Ensuring exceptional performance

All our Waltech fittings are designed to meet the toughest application demands for strength, pressure resistance and reliability. OEMs with very stringent requirements choose Waltech, given our extensive safety and hazardous environment approvals. We also offer a two-year warranty for all components.

Reliable raw materials

To support the most demanding tube fitting needs, the Waltech series uses for critical components high-quality raw materials that ensure in-application reliability:

- High tensile steel grades are used that reduce the variance of material properties.
- Purity analysis to EN 50602 and ISO 10247 standards is undertaken with every batch of materials to ensure its properties meet requirements.
- Ultrasonic crack detection is done for barstock material, according to DIN EN 10277 standards, to prevent the occurrence of microcracks in the material





Pressure resistance

All three Waltech systems can withstand the highest pressures.

- Waltech was the first tube fitting system to support operating pressures of up to 800 bar, and all three systems have the same high pressure resistance.
- Waltech systems are available in L Series fittings, rated up to 500 bar, or S Series fittings, rated up to 800 bar.
- Our carbon steel fittings are calibrated for the highest working pressures.

Vibration and bending resistance

Our tube connector series is designed and tested for excellent resistance to vibration and bending stress.

- Walpro: The tube is clamped over its complete length to compensate for vibration and is held in place by a stable bulk of material in front of the first edge.
- WalringPlus: Two cutting edges share the holding force equally, enabling greater resistance against high dynamic loads and are optimized for thin wall tubing.
- Walform: Cold forming of materials increases stress resistance at the most crucial points of the tube. Combined with no sharp ending, this creates outstanding vibration
- Walformplus-SR: Extends Walform's advantages to thin wall tubing, with an additional support ring behind the formed tube which increases vibration and bending stress
- Walformplus-M: Enables metallic sealing without a soft seal, for applications with aggressive media or very high temperatures.

assembly. The metallic sealing cutting ring can be assembled and disassembled as often as necessary.

edaes.

Lower expenditure, thanks to a reduced need to replace nuts and bodies.

Walpro design benefits

Operators 'feel' when assembly is

unmistakable, thanks to steadily rising

tightening torque with a limit stop

Increased resistance to high dynamic

loads through axial ribs, inner area

clamping along the complete tube

Optimized sealing efficiency due to

cutting ring and tube surface. High

sealing stress also results in a lower

a complete connection between the

Superior assembly characteristics due

Safe connections even after repeated

to cutting edge angles and two cutting

share the holding force.

likelihood of leakage.

length, and cutting edges that equally

complete and overtightening i

- The O-ring groove design of WalringPlus enables an improved stress cutting ring cracking during assembly

Patented nose design provides

No turning of the tube during the

Engineered

for easy assembly

Correct assembly is crucial to tube fitting performance. That's why our Waltech systems make assembly simple, fast, and safe.


By offering the same assembly behavior for all systems, our Waltech tube fittings make correct assembly easy for operators. This includes short assembly travel, lower tightening torque, an unmistakable pressure point to prevent over or underassembly, and unlimited reassembly with no performance impact.




Waltech's assembly advantages

- All three Waltech systems can be assembled with the similar short 30-60° turn in all sizes, requiring less manual effort or machine time to assemble.
- Considerably lower tightening torque and an unmistakable torque increase at the end of assembly prevents overtightening and aids precision.
- After cutting ring system assembly, the visible bulk of removed material makes it easy to check everything is
- Assembly can be repeated any number of times with no
- Dry assembly (no lubrication required) for carbon steel

Final in service assembly after prefabrication





High performance assembly machines

To further reduce the assembly time and effort required and help ensure optimum performance, we've also developed our own Waltech machines to automate the process of cutting ring assembly and tube

- Our innovative M-R7 machine is designed for final assembly of our Walpro and WalringPlus systems. It offers optimized performance and installation advantages, resulting in a short tightening movement and reduced force required at the final stage of the
- Our reliable M-WF385Xplus machine is designed for the most demanding applications, enabling tube forming for the Walform system in steel and stainless steel (1.4571). It enables additional sealing, easy machine assembly, and robust performance.

M-R7 features and benefits

- · Final assembly of Walpro and WalringPlus tube fittings from
- Fast cycle times allow efficient and economical production
- Able to process extremely tight bent tubes and short straight tube
- Automatic pressure point detection and way control ensures accurate and reliable assembly
- RFID-technology for tool detection and setting of process values
- Optimized error detection with self-programmed limits based on statistical process control
- Unmissable error messages that require acknowledgment
- Automatic assembly by pushing the tube through the tool
- Export assembly parameters via a USB port for integration into



M-WF385Xplus features and benefits

- Final assembly of Walform tube connectors from
- Fast cycle times allow efficient and economical production
- Reduced set-up time thanks to easy tool changes
- Compact, low-weight design for easy transportation on the
- Robust design reduces downtime and enables a longer machine lifetime
- Forming pressure control reduces energy consumption and extends machine lifetime
- · Quieter performance for reduced noise level in the shop floor
- Color-coded tools to avoid mistakes in the forming process




including tool cabinet, tool holder and

Guardian **Seal plating**

Guardian Seal is our exceptional, zinc-based surface treatment applied by electroplating. It quarantees excellent, durable protection from corrosion and meets DIN EN ISO 9227 standards-while also being easy to assemble, and better for health and the environment.

The 11-15 µm zinc layer is passivized through a specialized process, resulting in an open-pored structure. Organic micro-particles are then impregnated into this structure in an optimized emersion process. Finally, the cross-linked polymerization of the top layer is completed via a unique curing procedure.



Key features

- Lower assembly and disassembly torque and reduced torque
- >360 hours resistance to white corrosion and >1000 hours to red corrosion
- Nickel and chromium-6 free
- Torque value is the same as Chromium-3
- · High quality shiny silver appearance
- Resistant to commonly used hydraulic fluids
- Paintable with commercially available coatings

Key benefits

- Guarantees excellent, durable corrosion protection
- · Safer and easier assembly and disassembly
- No risk of nickel dust during assembly and handling
- No risk of contact allergies
- Wastewater from the plating process requires



Guardian Seal coating in salt spray test according to DIN EN ISO 9227



Our supporting services

Our Waltech series relies on the proven capabilities at our major manufacturing and distribution facility in Lohmar, Germany—where we produce all our Walpro, WalringPlus and Walform tube connector lines.

With in-house expertise spanning design, testing and production, we can deliver much greater lifecycle value to customers. We offer customers a wide range of support services including high-end test capabilities, inspection maintenance, repairs, backfitting, rentals and operator training.

Training for success

- As well as increasing time and cost requirements, insufficient knowledge or a lack of training can cause errors in assembly, leakages, and even safety issues.
- We offer customers expert training for both our tube fitting systems and assembly machines.
- Training can be held at either our Lohmar facility or at customer

Troubleshooting any issues

- Our service team regularly checks both rented or purchased tools and machines at customer sites.
- · Our engineering team can visit customers to understand their applications, measure performance, and optimize routing and connections to resolve issues.
- We have a large rental pool of machines available to support customer projects or offer replacements in case maintenance is
- Our machine warranty can be extended up to three years and, if a rental machine breaks down, a substitute can be issued subject to the terms of the rental contract.
- We have various options available for the maintenance and backfitting of older assembly machines.

Testing to the extremes

- Our Waltech development and testing programs go to extremes to ensure exceptional performance. We have all the expertise and test equipment needed to validate new products and tubing materials in-house.
- We can design components for specific customer applications and test them in a simulated environment to ensure they offer the best possible solution.
- The Waltech development and testing programs were designed to ensure top-notch performance, as well as help our customers meet specific application needs. They include:
 - · A combined pressure/impulse and reversed bending test
 - A tensile test to failure, with confirmation of the fitting's stripping resistance
 - A fire resistance test to DIN EN ISO 19921 with exposure to
 - The Walpro test program helium test for leakage resistance
 - The Walformplus test program shock and gas pressure tests for military and marine applications



Six reasons to choose Waltech Excellent performance: no leaks and high bending, impulse and corrosion resistance A complete solution for any tube fitting needs Manual assembly that's straightforward, safe and repeatable Machine assembly that's quicker, easier and can reduce In-house supporting services spanning application testing, maintenance, training and more Danfoss's global footprint, excellent application

Go to www.danfoss.com for further product information.

Danfoss Power Solutions (US) Company

2800 East 13th Street Ames, IA 50010, USA Phone: +1 515 239 6000

references and customer success stories

Danfoss Power Solutions II GmbH

Hauptstrasse 150 53797 Lohmar, Germany Phone: +49 2246 1009101

Danfoss Power Solutions ApS

Nordborgvej 81 DK-6430 Nordborg, Denmark Phone: +45 7488 2222

Danfoss Power Solutions Trading (Shanghai) Co. Ltd.

Building #22, No. 1000 Jin Hai Rd Jin Qiao, Pudong New District Shanghai, China 201206 Phone: +86 21 3418 5200

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed.

All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

AD403661823132en-000202 © Copyright Danfoss | 2022