

FT1380 Crimp Machine Backstop

The FT1380 Backstop provides added versatility to one of Danfoss's most widely used crimp machines, the FT1380. Featuring both "spring-loaded" and "positive-stop" options, this backstop simplifies crimping for a wide range of fitting styles including thru-the-cover, PTFE and others.



Features:

- Magnetic mount
- "Spring-Loaded" backstop
- "Positive-Stop" option
- 2.5 inches of travel

Benefits:

- Installs in seconds
- Makes high volume hose assembly easier
- Increases machine capacity to include PTFE
- Accommodates a variety of fitting sizes

"Spring-Loaded" to "Positive-Stop" Adjusting Instructions

Step One

Back out the thumbscrew completely and remove the small round spacer.

Step Two

Re-Install the thumbscrew and tighten securely.

Step Three

Using the 5/32" hex wrench, remove the cap screw that attaches the stop plate to the threaded rod

Step Four

Place the round spacer over the spring-loaded shaft.

Step Five

Re-install the stop plate to the threaded rod and tighten securely.

Attention: Only use the "positive-stop" feature for hoses requiring a positive backstop. Use the "spring-loaded" feature for all other style hoses. This will reduce the possibility of improper hose assembly and damage to backstop components.

Ordering Instructions:

Part Number	Description
FT1380-4	Backstop and 5/32" hex wrench

About Danfoss Power Solutions FC

To learn more please visit: <http://www.danfoss.com/en/about-danfoss/our-businesses/power-solutions>

Danfoss Power Solutions

14615 Lone Oak Road
Eden Prairie, MN 55344, USA
Phone: 952-937-9800

Danfoss can accept no responsibility for possible errors in catalogs, brochures, and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are the property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.