

Installation Guide

SpeedUp Heat Panels in Dry Installations

1 Installation of SpeedUp Heat Panels in Dry Installations



Fig. 1: Install SpeedUp perimeter insulation and support batten on dry, even and load bearing substrate.



Fig. 2: Following the layout, begin the installation in one corner with a SpeedUp header panel.



Fig. 3: Place the SpeedUp heat panels (CZ: pipe distance 250 mm, EZ: pipe distance 125 mm). Fill gaps and unheated areas with blank panels.



Fig. 4: Snap the pre-scored heat panels as required.



Fig. 5: Light constructions (e.g. laminate/engineered timber or strongboard constructions laid directly on the heat panels): rooms > 12 m² glue all perimeter and header panels, rooms < 12 m² glue all panels (recommended).



Fig. 6: Where required cut individual pipe channels using the SpeedUp hot wire cutter.



Fig. 7: Support battens in thresholds should be screwed down.



Fig. 8: Holding the pipe in a large curve to avoid tension, press the composite pipe into the channels. Avoid lifting pipe once installed in the header panels.



Fig. 9: Press fittings should only be positioned between two aluminum sheets and never in curved sections of pipe.



Fig. 10: Cover pipe work in front of manifold with SpeedUp load bearing steel to protect against damage.

Danfoss A/S
Heating Solutions
Haarupvaenget 11
8600 Silkeborg
Denmark
Phone: +45 7488 8000
Fax: +45 7488 8100
Email: ComfortControlsInternet@danfoss.com
www.heating.danfoss.com

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.