



Danfoss Power Solutions
2800 East 13th Street • Ames, IA 50010, USA • Phone: +1 515 239 6000

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Industrial Hose in Food & Beverage


reliable solutions that meet your needs

food & beverage

liquid food transfer

MILK & VEGETABLE OIL

Lemur™ EHF002



- -40°C to +80°C (-40°F to +176°F)
- 10 bar (145 psi)
- FDA compliant
- Steel helical wire
- Oil-resistant NBR construction

BEER & WINE

Light Duty S & D EHB502



- -40°C to +120°C (-40°F to +248°F)
- 7 bar (100 psi)
- Meets FDA & European requirements
- Steel helical wire
- EPDM construction

HIGH PERCENTAGE ALCOHOL


Alcohol S & D EHF021



- -40°C to +80°C (-40°F to +176°F)
- 10 bar (145 psi)
- Meets FDA & European requirements
- Steel helical wire
- UHMW-PE tube & corrugated EPDM rubber cover

NON-DAIRY

Lion® H0350



- -40°C to +82°C (-40°F to +180°F)
- 17.2 bar (250 psi)
- FDA compliant
- Steel helical wire
- Vinyl nitrile construction

POTABLE WATER

Clearforce® R H285



- -10°C to +66°C (-15°F to +150°F)
- Up to 17.2 bar (250 psi)
- FDA compliant
- NSF-51 certified
- PVC construction with fiber reinforcement

MINERAL WATER & FRUIT JUICES

Bosporus EHT200



- -5°C to +60°C (-23°F to +140°F)
- Up to 21 bar (305 psi)
- Smooth & non-toxic innertube
- Crush resistant, flexible & transparent
- PVC construction
- FDA compliant

washdown*

CREAMERY & PACKING


Loris™ H1066



- -40° to +82°C (-40°F to +180°F)
- 13.8 bar (200 psi)
- Pin-pricked vinyl nitrile cover

FACILITY & EQUIPMENT


Joey™ H9610



- -40°C to +82°C (-40°F to +180°F)
- 70 bar (1,000 psi)
- Vinyl nitrile construction

HIGH PRESSURE

Manta™ EC116




- -40°C to +150°C (-40°F to +302°F) intermittent
- 300 bar (4,350 psi)
- Oil, abrasion & weather resistant cover
- Meets BS EN1829-2 safety jet requirements
- MSHA approved

*not for conveying food

dry bulk food transfer

SUCTION & DISCHARGE


Badger™ H0384



- -40°C to +82°C (-40°F to +180°F)
- Up to 10.5 bar (150 psi)
- FDA compliant
- Steel helical wire
- Vinyl nitrile construction

DISCHARGE ONLY

Bison™ H0413




- -29°C to +71°C (-20°F to +160°F)
- 3.5 bar (50 psi)
- Anti-static copper wire
- SBR rubber blend construction

food processing facilities

STEAM TRANSFER & CLEANING

Steam Slayer® EH084



- -40°C to +208°C (-40°F to +407°F) continuous, +450°F for intermittent superheated
- 17 bar (250 psi)
- Chlorobutyl innertube & pin-pricked EPDM cover
- Static ozone and continuity resistant
- Steam resistance failure exceeding 1,000 hours

proven process powerful performance