



Data sheet

# **Solenoid valves for drinking water** Types EV220BW and EV228BW



#### **Features and versions**

- Clip-on coil
- Flow range for water in Kv:  $4 40 \text{ m}^3 / \text{ h}$
- Differential pressure: 0.3 10 bar
- Media temperature from 0 90 °C
- Ambient temperature: Up to 80 °C
- Coil enclosure: IP65
- Thread connections: From G 1/2 G 2
- DN 15 50
- Water hammer damped
- Built-in filter

Solenoid valve range with drinking water approvals

- For water supply
- Houses and large apartments
   Kitchen and bathrooms
- Commercial buildings
- Industrial buildings
- Zoning
- Laundry
- Diswashing
- Main inlet valves
- · Machines and food processing

- Body material in ECO brass (Lead free < 0,1 %) or Stainless steel
- New generation EPDM sealings recommended for drinking water
- Valves are certified by RISE, notified body 1002. Valid in Denmark and Sweden. In accordance with Boverket Building Regulations (BBR 21, 2014-06-17). Certificate number SCO155-18
- Inspection by DTI
- EV220BW 15-25 ECO brass NC/NO
- EV220BW 15-50 SS NC/NO
- EV228BW 15-25 ECO brass UN (Latching)
- EV228BW 15-50 SS UN (Latching)



#### EV220BW 15-25 ECO brass valve body, NC



- In accordance with:
  - Low Voltage Directive 2014/35/EU - EN60730-1
    - EN60730-2-8
  - Pressure Equipment Directive 2014/68/EU
- RoHS Directive 2011/65/EU
- Wetted materials in accordance with BBR, DVGW, 4MS (4 member states Germany, Holland, France and UK), KTW and W270
- Certified by RISE
- Inspection by DTI
  356 DTI

ISO228/1 Seal		Orifice size	K <sub>v</sub> -value	Media temperature	Differential pressure	Code no.
connection	material	[mm]	[m³/ h]	[°C]	[Bar]	
G 1⁄2	EPDM	15	4	0 – 90	0.3 – 10	132U1500
G 34	EPDM	20	8	0 – 90	0.3 – 10	132U2000
G 1	EPDM	25	11	0 - 90	0.3 – 10	132U2500

<sup>1</sup>) It is recommended to use a filter in front of the valve.

<sup>2</sup>) In water applications, exercise the valves at least once every 24 hours, meaning change the state of the valve.

The valve exercise will minimize the risk of the valve sticking due to calcium carbonate, zinc or iron oxide build-up.



# **Technical data**

Main Type	EV220BW 15 BE	EV220BW 20 BE	EV220BW 25 BE
Time to open [ms] 1)	40	40	300
Time to close [ms] 1)	350	1000	1000
	550	1000	1000

<sup>1</sup>) The times are indicative and apply to water. The exact times will depend on the pressure conditions.

Installation	Optional, but vertical solenoid system is recommended				
Max. working pressure (MWP)	10 bar				
Max. test pressure	25 bar				
	BB DC	Up to 50 °C			
Ambient temperature	BB AC	Up to 80 °C			
	EEC BE240CS	Up to 55 °C			
Viscosity	Max. 50 cSt				
	Valve body / cover	ECO brass	CW724R		
	Armature	Stainless steel	W.no. 1.4105 / AISI 430 FR		
	Armature tube	Stainless steel	W.no. 1.4306 / AISI 304 L		
	Armature stop	Stainless steel	W.no. 1.4105 / AISI 430 FR		
Materials	Springs	Stainless steel	W.no. 1.4310 / AISI 301		
	Equalizing orifice	ECO brass	CW724R		
	O-rings	EPDM			
	Valve plate	EPDM			
	Diaphragm	EPDM			



#### EV220BW 15-50 SS valve body NC



- In accordance with:
  - Low Voltage Directive 2014/35/EU - EN60730-1
    - EN60730-2-8
  - Pressure Equipment Directive 2014/68/EU
- RoHS Directive 2011/65/EU
- Wetted materials in accordance with BBR, DVGW, 4MS (4 member states Germany, Holland, France and UK), KTW and W270
- Certified by RISE
- Inspection by DTI
  <sup>356</sup>
  DTI

ISO228/1	Seal	Orifice size	K <sub>v</sub> - value	Media temperature	Differential pressure	Code no.
connection	material	[mm]	[m³/ h]	[°C]	[Bar]	
G 1⁄2	EPDM	15	4	0 - 90	0,3 – 10	132U1580
G 3⁄4	EPDM	20	8	0 – 90	0,3 – 10	132U2080
G 1	EPDM	25	11	0 - 90	0,3 - 10	132U2580
G1 ¼	EPDM	32	18	0 - 90	0,3 - 10	132U3280
G1 1⁄2	EPDM	40	24	0 – 90	0,3 – 10	132U4080
G 2	EPDM	50	40	0 - 90	0,3 - 10	132U5080

<sup>1</sup>) It is recommended to use a filter in front of the valve.

<sup>2</sup>) In water applications, exercise the valves at least once every 24 hours, meaning change the state of the valve.

The valve exercise will minimize the risk of the valve sticking due to calcium carbonate, zinc or iron oxide build-up.



#### **Technical data**

Main Type	EV220BW	EV220BW	EV220BW	EV220BW	EV220BW	EV220BW	
Time to open [ms] 1)	40	40	300	1000	1500	5000	
Time to close [ms] 1)	350	1000	1000	2500	4000	10000	
The times are indicative and apply to water. The exact times will depend on the pressure conditions							

The times are indicative and apply to water. The exact times will depend on the pressure conditions

Installation	Optional, but vertical solenoid system is recommended					
Max. working pressure (MWP)	10 bar					
Max. test pressure	25 bar					
	BB DC	Up to 50 °C				
Ambient temperature	BB AC	Up to 80° C				
	EEC BE240CS	Up to 55° C				
Viscosity	Max. 50 cSt					
	Valve body / cover	Stainless Steel	W. no. 1.4404 / AISI316L			
	Armature	Stainless steel	W.no. 1.4105 / AISI 430 FR			
	Armature tube	Stainless steel	W.no. 1.4306 / AISI 304 L			
	Armature stop	Stainless steel	W.no. 1.4105 / AISI 430 FR			
Materials	Springs	Stainless steel	W.no. 1.4310 / AISI 301			
	Equalizing orifice	Stainless steel	W. no. 1.4435 / AISI 316L			
	O-rings	EPDM				
	Valve plate	EPDM				
	Diaphragm	EPDM				



#### Function, NC



Pos. no.	Description
1	Coil
2	Armature spring
3	Valve plate
4	Pilot orifice
5	Diaphragm
6	Main orifice
7	Equalizing orifice

## Coil voltage disconnected (closed):

When the voltage is disconnected, the valve plate (3) is pressed down against the pilot orifice (4) by the armature spring (2). The pressure across the diaphragm (5) is built up via the equalizing orifice (7). The diaphragm closes the main orifice (6) as soon as the pressure across the diaphragm is equivalent to the inlet pressure. The valve will be closed for as long as the voltage to the coil is disconnected.

#### Coil voltage connected (open):

When voltage is applied to the coil (1), the pilot orifice (4) is opened. As the pilot orifice is larger than the equalizing orifice (7), the pressure across the diaphragm (5) drops and therefore it is lifted clear of the main orifice (6). The valve is now open for unimpeded flow and will be open for as long as the minimum differential pressure across the valve is maintained, and for as long as there is voltage to the coil.



#### EV220BW 15-25 ECO brass valve body NO



- In accordance with:
  - Low Voltage Directive 2014/35/EU - EN60730-1
    - EN60730-2-8
  - Pressure Equipment Directive 2014/68/EU
- RoHS Directive 2011/65/EU
- Wetted materials in accordance with BBR, DVGW, 4MS (4 member states Germany, Holland, France and UK), KTW and W270
- Certified by RISE
- Inspection by DTI
  356 DTI

ISO228/1	Seal	Orifice size	K <sub>v</sub> -value	Media temperature	Differential pressure	Code no.
connection	material	[mm]	[m³/ h]	[°C]	[Bar]	
G 1⁄2	EPDM	15	4	0 – 90	0.3 – 10	132U1501
G 34	EPDM	20	8	0 – 90	0.3 – 10	132U2001
G 1	EPDM	25	11	0 - 90	0.3 – 10	132U2501

<sup>1</sup>) It is recommended to use a filter in front of the valve.

<sup>2</sup>) In water applications, exercise the valves at least once every 24 hours, meaning change the state of the valve.

The valve exercise will minimize the risk of the valve sticking due to calcium carbonate, zinc or iron oxide build-up.



## **Technical data**

Main Type	EV220BW 15 BE	EV220BW 20 BE	EV220BW 25 BE
Time to open [ms] 1)	40	40	300
Time to close [ms] 1)	350	1000	1000

<sup>1</sup>) The times are indicative and apply to water. The exact times will depend on the pressure conditions.

Installation	Optional, but vertical solenoid system is recommended					
Max. working pressure (MWP)	10 bar					
Max. test pressure	25 bar	25 bar				
	BB DC	Up to 50 °C				
Ambient temperature	BB AC	Up to 80° C				
	EEC BE240CS	Up to 55° C				
Viscosity	Max. 50 cSt					
	Valve body / cover	ECO brass	CW724R			
	Armature	Stainless steel	W.no. 1.4105 / AISI 430 FR			
	Armature tube	Stainless steel	W.no. 1.4306 / AISI 304 L			
	Armature stop	Stainless steel	W.no. 1.4105 / AISI 430 FR			
Materials	Springs	Stainless steel	W.no. 1.4310 / AISI 301			
	Equalizing orifice	ECO brass	CW724R			
	O-rings	EPDM				
	Valve plate	EPDM				
	Diaphragm	EPDM				



#### EV220BW 15-50 SS valve body NO



- In accordance with:
  - Low Voltage Directive 2014/35/EU - EN60730-1
    - EN60730-2-8
  - Pressure Equipment Directive 2014/68/EU
- RoHS Directive 2011/65/EU
- Wetted materials in accordance with BBR, DVGW, 4MS (4 member states Germany, Holland, France and UK), KTW and W270
- Certified by RISE
- Inspection by DTI
  <sup>356</sup>
  DTI

ISO228/1	Seal	Orifice size	K <sub>v</sub> - value	Media temperature	Differential pressure	Code no.
connection	material	[mm]	[m³/ h]	[°C]	[Bar]	
G 1/2	EPDM	15	4	0 - 90	0,3 – 10	132U1581
G 34	EPDM	20	8	0 - 90	0,3 – 10	132U2081
G 1	EPDM	25	11	0 - 90	0,3 – 10	132U2581
G1 ¼	EPDM	32	18	0 – 90	0,3 – 10	132U3281
G1 1/2	EPDM	40	24	0 - 90	0,3 – 10	132U4081
G 2	EPDM	50	40	0 - 90	0,3 – 10	132U5081

<sup>1</sup>) It is recommended to use a filter in front of the valve.

<sup>2</sup>) In water applications, exercise the valves at least once every 24 hours, meaning change the state of the valve.

The valve exercise will minimize the risk of the valve sticking due to calcium carbonate, zinc or iron oxide build-up.



# **Technical data**

Main Type	EV220BW	EV220BW	EV220BW	EV220BW	EV220BW	EV220BW
Time to open [ms] 1)	40	40	300	1000	1500	5000
Time to close [ms] 1)	350	1000	1000	2500	4000	10000

) The times are indicative and apply to water. The exact times will depend on the pressure conditions.

Installation	Optional, but vertical solenoid system is recommended					
Max. working pressure (MWP)	10 bar					
Max. test pressure	25 bar	25 bar				
	BB DC	Up to 50 °C				
Ambient temperature	BB AC	Up to 80° C				
	EEC BE240CS	Up to 55° C				
Viscosity	Max. 50 cSt					
	Valve body / cover	Stainless steel	W. no. 1.4404 / AISI 316L			
	Armature	Stainless steel	W.no. 1.4105 / AISI 430 FR			
	Armature tube	Stainless steel	W.no. 1.4306 / AISI 304 L			
	Armature stop	Stainless steel	W.no. 1.4105 / AISI 430 FR			
Materials	Springs	Stainless steel	W.no. 1.4310 / AISI 301			
	Equalizing orifice	Stainless steel	W. no. 1.4435 AISI 316L			
	O-rings	EPDM				
	Valve plate	EPDM				
	Diaphragm	EPDM				



#### **Function**, NO



Pos. no.	Description	
1	Coil	
2	Armature spring	
3	Valve plate	
4	Pilot orifice	
5	Diaphragm	
6	Main orifice	
7	Equalizing orifice	

#### Coil voltage disconnected (closed):

When the voltage to the coil (2) is disconnected, the pilot orifice (4) is open. As the pilot orifice is larger than the equalizing orifice (7), the pressure across the diaphragm (5) drops and therefore it is lifted clear of the main orifice (6). The valve will be open for as long as the minimum differential pressure across the valve is maintained, and for as long as the voltage to the coil is disconnected.

#### Coil voltage connected (open):

When voltage is applied to the coil, the valve plate (3) is pressed down against the pilot orifice (4). The pressure across the diaphragm (5) is built up via the equalizing orifice (7). The diaphragm closes the main orifice (6) as soon as the pressure across the iaphragm is equivalent to the inlet pressure. The valve will be closed for as long as there is voltage to the coil.



EV228BW 15-25 ECO brass valve body UN, latching



- In accordance with:
  - Low Voltage Directive 2014/35/EU - EN60730-1
    - EN60730-2-8
  - Pressure Equipment Directive 2014/68/EU
- RoHS Directive 2011/65/EU
- Wetted materials in accordance with BBR, DVGW, 4MS (4 member states Germany, Holland, France and UK), KTW and W270
- Certified by RISE
- Inspection by DTI
  <sup>356</sup>
  DTI

ISO228/1	Seal	Orifice size	K <sub>v</sub> -value	Media temperature	Differential pressure	Code no.
connection	ion material [mm]		[m³/ h] [°C]		[Bar]	
G 1/2	EPDM	15	4	0 - 60	0.3 – 10	132U2400
G 3/4	EPDM	20	8	0 – 60	0.3 – 10	132U2402
G 1	EPDM	25	11	0 - 60	0.3 – 10	132U2404

<sup>1</sup>) It is recommended to use a filter in front of the valve.

<sup>2</sup>) In water applications, exercise the valves at least once every 24 hours, meaning change the state of the valve.

The valve exercise will minimize the risk of the valve sticking due to calcium carbonate, zinc or iron oxide build-up.



# **Technical data**

Main Type	EV228BW	EV228B 20B	EV228B 25B
Time to open [ms] 1)	40	40	300
Time to close [ms] 1)	350	1000	1000

<sup>1</sup>) The times are indicative and apply to water. The exact times will depend on the pressure conditions. Closing times can be changed by replacement of the equalizing orifice.

Installation	Optional, but verti	cal solenoid system	n is recommended		
Max. working pressure (MWP)	10 bar				
Ambient temperature	Up to 50 ℃				
Viscosity	Max. 50 cSt				
	Valve body / cover	ECO brass	CW724R		
	Armature	Stainless steel	W.no. 1.4105 / AISI 430 FR		
	Armature tube	Stainless steel	W.no. 1.4306 / AISI 304 L		
	Armature stop	Stainless steel	W.no. 1.4105 / AISI 430 FR		
Materials	Springs	Stainless steel	W.no. 1.4310 / AISI 301		
	Equalizing orifice	ECO brass	CW724R		
	O-rings	EPDM			
	Valve plate	EPDM			
	Diaphragm	EPDM			
Switch power (on/off) 018F7396 (12V DC)					



#### EV228BW 15-50 SS valve body UN, latching



- In accordance with:
  - Low Voltage Directive 2014/35/EU - EN60730-1
    - EN60730-2-8
  - Pressure Equipment Directive 2014/68/EU
- RoHS Directive 2011/65/EU
- Wetted materials in accordance with BBR, DVGW, 4MS (4 member states Germany, Holland, France and UK), KTW and W270
- Certified by RISE
- Inspection by DTI
  356 DTI

ISO228/1	Seal	Orifice size	K <sub>v</sub> -value	Media temperature	Differential pressure	Code no.
connection	material	[mm] [m³/ h]		[°C]	[Bar]	
G 1⁄2	EPDM	15 – 50	4	0 - 60	0.3 – 10	132U2401
G 34	EPDM	20 – 50	8	0 - 60	0.3 – 10	132U2403
G 1	EPDM	25 – 50	11	0 - 60	0.3 – 10	132U2405
G1 ¼	EPDM	32 – 50	18	0 - 60	0.3 – 10	132U2407
G1 ½	EPDM	40 – 50	24	0 - 60	0.3 – 10	132U2409
G 2	EPDM	50 – 50	40	0 - 60	0.3 – 10	132U2411

<sup>1</sup>) It is recommended to use a filter in front of the valve.

<sup>2</sup>) In water applications, exercise the valves at least once every 24 hours, meaning change the state of the valve.

The valve exercise will minimize the risk of the valve sticking due to calcium carbonate, zinc or iron oxide build-up.



#### **Technical data**

Main Type	EV220BW	EV220BW	EV220BW	EV220BW	EV220BW	EV220BW
Time to open [ms] 1)	40	40	300	1000	1500	5000
Time to close [ms] 1)	350	1000	1000	2500	4000	10000
The times are indicative and apply to water. The evert times will depend on the pressure conditions						

The times are indicative and apply to water. The exact times will depend on the pressure conditions.

Installation	Optional, but vertical solenoid system is recommended				
Max. working pressure (MWP)	10 bar				
Max. test pressure	25 bar	25 bar			
Ambient temperature	BB DC Up to 50° C				
Viscosity	Max. 50 cSt				
	Valve body / cover	Stainless steel	w. no. 1.4404 / AISI 316L		
	Armature Stainless steel W.		W.no. 1.4105 / AISI 430 FR		
	Armature tube Stainless steel		W.no. 1.4306 / AISI 304 L		
	Armature stop	Stainless steel	W.no. 1.4105 / AISI 430 FR		
Materials	Springs	Stainless steel	W.no. 1.4310 / AISI 301		
	Equalizing orifice	Stainless steel	W. no. 1.4435 / AISI 316L		
	O-rings	EPDM			
	Valve plate	EPDM			
	Diaphragm	EPDM			

Danfoss

## **Function UN, latching**





When — (minus) is supplied to the left terminal pin and + (plus) to the right (see fig. a), the valve plate is pressed down against the pilot orifice (4) by the armature spring (2). The pressure across the diaphragm (5) is built up via the equalizing orifice (7). The diaphragm closes the main orifice (6) as soon as the pressure across the diaphragm is equivalent to the inlet pressure. The valve will stay closed, until the poles are switched (see fig. b).

Pos. no.	Description	
1	Coil	
2	Armature spring	
3	Valve plate	
4	Pilot orifice	
5	Diaphragm	
6	Main orifice	
7	Equalizing orifice	
8	Permanent magnet	



## Switching poles

When + (plus) is supplied to the left terminal pin and - (minus) to the right (see fig. b), the pilot orifice (4) is opened. As the pilot orifice is larger than the equalizing orifice (7), the pressure across the diaphragm (5) drops and therefore it is lifted clear of the main orifice (6). The valve is now open for flow and will stay open as long as the minimum differential pressure across the valve is maintained, until the poles are switched back (see fig. a).



# **Dimensions and weight**



Turne	L	В	B <sub>1</sub> [mm] / coil type				н	H <sub>1</sub>	Weight without coil
туре	[mm]	[mm]	BA	BB / BE	BG / BO	BP	[mm]	[mm]	[kg]
EV220/228BW 15	80.0	52.0	32	46	68	45	99	15.0	0.7
EV220/228BW 20	90.0	58.0	32	46	68	45	103	18.0	0.9
EV220/228BW 25	109.0	70.0	32	46	68	45	113	22.0	1.3
EV220/228BW 32	120.0	82.0	32	46	68	45	120	27.0	2.0
EV220/228BW 40	130.0	95.0	32	46	68	45	129	32.0	3.0
EV220/228BW 50	162.0	113.0	32	46	68	45	135	37.0	4.8

# Mounting angle





#### Capacity diagrams:

Example, water: Capacity for EV220BW 15B at differential pressure of 3 bar. Approx. 7 m<sup>3</sup>/h





## BB / BY, High performance coils



- Enclosure:
  - IP00 version with DIN 43650 A spade connectors
  - IP20 version with protective cap
  - IP65 version with mounted cable plug
- In accordance with:
  - RoHS Directive 2011/65/EU
  - Low Voltage Directive 2014/35/EU - EN60730-1
  - EN60730-2-8

Туре	Tambient	Supply voltage	Voltage	Frequency	Control	Power co	Code no.	
	[°C]	[V]	variation	[Hz]		[W]	[VA]	
BB024AS	-40 - 80	24	-15%, +10%	50	NO, NC	11	19	018F7358
BB230AS	-40 - 80	220 - 230	-15%, +10%	50	NO, NC	11	19	018F7351
BB012DS	-40 - 50	12	±10%	DC	NC, NO, UN (Latching)	13	-	018F7396
BB024DS	-40 - 50	24	±10%	DC	NC, NO, UN (Latching)	16	-	018F7397

#### **Technical data**

Design	In accordance with VDE 0580
Insulation of coil windings	Class H according to IEC 85
Connection	Spade connector in accordance with DIN 43650 form A
Enclosure, IEC 529	IP00 with spade connector, IP20 with protective cap, IP65 with cable plug
Duty rating	Continuous
Plug type	Cable plug (042N0156)

#### **Dimensions and weight**

|--|--|

L without cable plug	L with protective cap	L with cable plug	Weight
[mm]	[mm]	[mm]	[kg]
62	77	85	0.24



Accessories: Cable plug



Type, Form A

GDM 2011 (grey) cable plug according to DIN 43650-A PG11

Code no. 042N0156



# EEC Electronic coil controller



EEC electronic coil controller for solenoid valves, type EV220B.

The EEC gives the coil a short over-boost, and controls the armature speed:

- Low power consumption (holding power: 4 W)
- Reduced noise during operation
- Increased MOPD compared to standard coils
- Increased lifetime of the solenoid valve
- Enclosure:
   IP67 version
- In accordance with:
- Low Voltage Directive 2014/35/EU - EN60730-1

Туре	Tambient	Supply voltage	Voltage	Voltage	Frequency	Control	Power consumption	Code no.
	[°C]	[V]	variation	[Hz]		[W]		
BE240CS	-25 - 55	208 - 240	±10%	60	NC, NO	4	01056703	
		208 - 240	±10%	50	NC, NO	4	01860/83	

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.