

Data Sheet

Danfoss Link™ Room Sensor

Application



Danfoss Link™ Room Sensor is an electronic sensor for measuring room temperature.

The Room Sensor is a part of the *Danfoss Link™* system, which is used for wireless linking and controlling of heating systems in residential and light commercial buildings.

The *Danfoss Link™ Room Sensor* has a built-in temperature sensor, which measures the ambient temperature. It allows you to control the heating, based on room temperature in the room where installed. With the *Danfoss Link™ Room Sensor* you can also adjust the requested temperature.

Ordering

Product	Languages	Code no.
Danfoss Link™ Room Sensor	UK, FI, LT, LV, EE, CZ, PL	014G0580
Danfoss Link™ Room Sensor	UK, DE, FR, IT, SE, ES, DK	014G0581

Technical Specifications

Danfoss Link™ Room Sensor	
Battery	2 x 1.5 V AA alkaline
Battery life	Up to 4-5 years
Backlight	White LED
Battery Level	Indication in display
Ambient temperature	0 to +40 °C
Transmission frequency	2-way wireless 868.42 MHz
Transmission range in normal buildings	Up to 30 m
Transmission power Max. 1mW	Max. 1 mW
IP Class	21
ErP Class	 (2%)
Dimensions	125 mm x 107 mm x 25 mm

Danfoss A/S

Residential Heating

Haarupvaenget 11

8600 Silkeborg

Denmark

Phone: +45 7488 8000

Fax: +45 7488 8100

Email: heating.solutions@danfoss.comwww.heating.danfoss.com

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed.
All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.