





LEGEND

DRAWING LIST

START

END



Start of LX Mat/Cable

End of LX Mat/Cable

Direction of LX Mat

Rotation of LX Mat

Loose Cable

Thermostat

LX-1

LX-2

LX-3

LX-4

LX-5

LX-6

LX-7

LX-8

LX-9

LX-10

Legend/Drawing List

LX Specification

LX General Notes

LX Typical Application

LX Typical Application

LX Typical Wiring Diagram

LX Thermostat to Contactor Panel

LX Mat Modification

LX Typical Layouts

LX Reflect Typical Installation and Layout

No: Date: Description:

Issued:

Project:

LX General Submittal

Drawing Title:

Legend/Drawing List



6711 Mississauga Rd, Suite 410
 Toronto, ON, L5N 2W3
 Tel: 1-866-676-80626711 Fax : 1 (905) 285-2055
www.NA.Heating.Danfoss.com

The Contractor shall verify all job site dimensions all drawing, details & specifications.
 The Contractor shall report any discrepancies, in writing to Danfoss prior to commencing with any work.

Date:

March 2018

Quote No:

Drawn By:

Scale:

Drawing No:

LX-1

LX Mats

LX Cables

LX Mat Specifications

LX Cables Specifications

- 1. General
Supply and install a complete system comprised of heating cables, accessories, and controls.
- 2. Material
 - 2.1. Shall be Danfoss LX twin conductor heating cable.
 - 2.2. Mat with strong dual self-adhesive backing (flexible thermoplastic polymer coated fiberglass).
 - 2.3. The mat is rated to produce 12W/SF at 120V or 240V.
 - 2.4. Shall include 10' cold lead, single point connection.
 - 2.5. Conductor: Copper or copper alloy, with tin-nickel coating.
 - 2.6. Insulation: DuPont FEP insulation with an average thickness not less than 0.35mm.
 - 2.7. Shield: Tin-Coated drain wire combined with 0.050mm aluminum foil coated with 0.012mm PBT, 100% coverage.
 - 2.8. Jacket: PVDF with an average thickness not less than 0.25mm.
 - 2.9. Shall operate on line voltage of (select:120V, 208-240V).
 - 2.10. Shall be approved to applicable UL and CSA standards.
- 3. System Controls
 - 3.1. The system temperature shall be controlled by a Danfoss thermostat with a floor or air sensor, or a combination of both.
 - 3.2. The thermostat shall incorporate an integral 5mA Class A Ground Fault Circuit Interrupter (GFCI), a temperature set-back option to reduce energy consumption, and a digital readout.
 - 3.3. Shall be approved to applicable UL and CSA standards.
- 4. Execution
 - 4.1. Installation
 - a. System must be installed per manufacture's recommendation using the method described in the installation guide.
 - b. Place the heating mats and sensors in the surface material as per the installation guide.
 - c. Inspect the mats and controls upon receiving the shipment. Note any damage and ensure materials received match the order and shipping documents.
 - 4.2. Tests
 - a. Refer to the manufacturer's literature for requirements for testing and documenting cable resistance and insulation-to-ground readings.
 - b. Take tests as outlined in the Installation Manual.
 - c. If problems are discovered, consult the manufacturer.
 - d. If unable to correct problems notify the engineer before proceeding with the installation.
 - e. Keep a record of all readings for inspection by the engineer or for submittal to the manufacturer to ensure a valid warranty.
- 5. Warranty
 - 5.1. Manufacturer shall offer a 20-year, non-prorated warranty.

- 1. General
Supply and install a complete system comprised of heating cables, accessories, and controls.
- 2. Material
 - 2.1. Shall be Danfoss LX twin conductor heating cable.
 - 2.2. Shall Include 10' factory spliced and sealed cold lead, single point connection.
 - 2.3. Conductor: Copper or copper alloy, with tin-nickel coating.
 - 2.4. The Cable is rated to produce 3 W/ft at 120 or 240V.
 - 2.5. Insulation: DuPont FEP insulation with an average thickness not less than 0.35mm.
 - 2.6. Shield: Tin-Coated drain wire combined with 0.050mm aluminum foil coated with 0.012mm PBT, 100% coverage.
 - 2.7. Jacket: PVC with an average thickness not less than 0.76mm.
 - 2.8. Shall operate on line voltage of (select:120V, 208-240V).
 - 2.9. Shall be approved to applicable UL and CSA standards.
- 3. System Controls
 - 3.1. The system temperature shall be controlled by a Danfoss thermostat with a floor or air sensor, or a combination of both.
 - 3.2. The thermostat shall incorporate an integral 5mA Class A Ground Fault Circuit Interrupter (GFCI), a temperature set-back option to reduce energy consumption, and a digital readout.
 - 3.3. Shall be approved to applicable UL and CSA standards.
- 4. Execution
 - 4.1. Installation
 - a. System must be installed per manufacture's recommendation using the method described in the installation guide.
 - b. Place the heating cable and sensors in the surface material as per the installation guide.
 - c. Inspect the cable and controls upon receiving the shipment. Note any damage and ensure materials received match the order and shipping documents.
 - 4.2. Tests
 - a. Refer to the manufacturer's literature for requirements for testing and documenting cable resistance and insulation-to-ground readings.
 - b. Take tests as outlined in the Installation Manual.
 - c. If problems are discovered, consult the manufacturer.
 - d. If unable to correct problems notify the engineer before proceeding with the installation.
 - e. Keep a record of all readings for inspection by the engineer or for submittal to the manufacturer to ensure a valid warranty.
- 5. Warranty
 - 5.1. Manufacturer shall offer a 20-year, non-prorated warranty.

No: Date: Description:

Issued:

Project:

LX General Submittal

Drawing Title:

Specification



6711 Mississauga Rd, Suite 410
Toronto, ON, L5N 2W3
Tel: 1-866-676-80626711 Fax : 1 (905) 285-2055
www.NA.Heating.Danfoss.com

The Contractor shall verify all job site dimensions all drawing, details & specifications.

The Contractor shall report any discrepancies, in writing to Danfoss prior to commencing with any work.

Date:

March 2018

Quote No:


Drawn By:

Scale:

Drawing No:


LX-2

Directly on plywood:



Detail:1 Danfoss LX Typical Installation and Application
LX-4

Directly on concrete:



Detail:2 Danfoss LX Typical Installation and Application
LX-4

No:	Date:	Description:
-----	-------	--------------

Issued:

Project:

LX General Submittal

Drawing Title:

LX Typical Installation



6711 Mississauga Rd, Suite 410
Toronto, ON, L5N 2W3
Tel: 1-866-676-8062/711 Fax: 1 (905) 285-2055
www.NA.Heating.Danfoss.com

The Contractor shall verify all job site dimensions all drawing, details & specifications.
The Contractor shall report any discrepancies, in writing to Danfoss prior to commencing with any work.

Date:

March
2018


Quote No:

Drawn By:

Scale:

Drawing No:

LX-4



No:	Date:	Description:
-----	-------	--------------

Issued:

Project:
LX General Submittal

Drawing Title:
LX Typical Installation



6711 Mississauga Rd, Suite 410
 Toronto, ON, L5N 2W3
 Tel: 1-866-676-8062/6711 Fax: 1 (905) 285-2055
www.NA.Heating.Danfoss.com


The Contractor shall verify all job site dimensions all drawing, details & specifications.
 The Contractor shall report any discrepancies, in writing to Danfoss prior to commencing with any work.

Date:	Quote No:
March 2018	

Drawn By:	Scale:

Drawing No:
LX-5


Typical Electrical wiring
Diagram for Danfoss Thermostat
Max. Load 15 Amps



Max. Load 15 Amps

Detail:1
LX-6 Wiring Diagram for Danfoss Thermostat
Max. Load 15 Amps

Typical Electrical wiring
Diagram for Danfoss Thermostat
Load greater than 15 Amps





Load greater than 15 Amps
(GFCI protection not provided in this wiring diagram)


Detail:2
LX-6 Wiring Diagram for Danfoss Thermostat
Load Greater Than 15 Amps

088L5135

088L5130
088L5136
088L5140



088L5135



SENSOR

Detail:3
LX-6 Wiring Diagram for Danfoss Thermostat
Load Greater Than 15 Amps

No: Date: Description:

Issued:

Project:

LX General Submittal

Drawing Title:

LX Typical Wiring
Diagram



6711 Mississauga Rd, Suite 410
Toronto, ON, L5N 2W3
Tel: 1-866-676-8062/6711 Fax: 1 (905) 285-2055
www.NA.Heating.Danfoss.com

The Contractor shall verify all job site dimensions all drawing, details & specifications.
The Contractor shall report any discrepancies, in writing to Danfoss prior to commencing with any work.

Date:

March
2018

Quote No:


Drawn By:

Scale:

Drawing No:

LX-6


Typical Electrical wiring
Diagram for Danfoss Thermostat
Load greater than 15 Amps



Note: Contractor to provide GFEP

Detail:2
LX-7
Thermostat to Contactor Panel Wiring

Typical Electrical wiring
Diagram for Danfoss Thermostat
Load greater than 15 Amps



Note: Contractor to provide GFEP

Note: Contractor to provide GFEP

Detail:2
LX-7
Thermostat to Contactor Panel Wiring

No: Date: Description:

Issued:

Project:

LX General Submittal

Drawing Title:

Thermostat to Contactor
Panel Wiring



6711 Mississauga Rd, Suite 410
Toronto, ON, L5N 2W3
Tel: 1-866-676-8062/6711 Fax: 1 (905) 285-2055
www.NA.Heating.Danfoss.com

The Contractor shall verify all job site
dimensions all drawing, details &
specifications.

The Contractor shall report any
discrepancies, in writing to Danfoss
prior to commencing with any work.

Date:

March
2018

Quote No:


Drawn By:

Scale:


Drawing No:

LX-7


① 30° Rotation




② 90° Rotation




③ 180° Rotation



④ Avoiding Obstacle



⑤ Fan Rotation



NOTE:

1. To Rotate the Mat at any angle, cut the grey mesh without cutting the red cable and turn it in any direction you want.
2. For some typical shapes or approaching obstacles remove some of the red heating cables from the grey mesh and use hot melt glue or thin strip of tape to secure the loose cable to the floor.
3. Do not cut the **RED** cable.

Detail:1 LX Mat Modification
LX-8

No: Date: Description:

Issued:

Project:

LX General Submittal

Drawing Title:

LX Mat Modification



6711 Mississauga Rd, Suite 410
Toronto, ON, L5N 2W3
Tel: 1-866-676-80626711 Fax : 1 (905) 285-2055
www.NA.Heating.Danfoss.com

The Contractor shall verify all job site dimensions all drawing, details & specifications.
The Contractor shall report any discrepancies, in writing to Danfoss prior to commencing with any work.

Date:

March
2018

Quote No:


Drawn By:

Scale:

Drawing No:


LX-8

No. Mats
 1. 088L3158 - 25ft
 Coverage - 50sf
 Note:
 1. 1ft Mat = 8ft Cable




Detail:1 Bathroom 1 Mat Layout
 LX-9

LX Cables
 1. 088L3145 - 200ft
 Coverage - 50sf
 @ 3" spacing




Detail:2 Bathroom 1 Cable Layout
 LX-9

No. Mats
 1. 088L3179 - 35ft
 Coverage - 70sf
 Note:
 1. 1ft Mat = 8ft Cable



Detail:3 Bathroom 2 Mat Layout
 LX-9

LX Cables
 1. 088L3141 - 60 ft
 Coverage - 15sf
 @ 3" spacing
 2. 088L3146 - 240ft
 Coverage - 60sf
 @ 3" spacing



Detail:4 Bathroom 2 Cable Layout
 LX-9

No: Date: Description:

Issued:

Project:

LX General Submittal

Drawing Title:

LX Typical Layout



6711 Mississauga Rd, Suite 410
 Toronto, ON, L5N 2W3
 Tel: 1-866-676-8062/711 Fax : 1 (905) 285-2055
www.NA.Heating.Danfoss.com

The Contractor shall verify all job site dimensions all drawing, details & specifications.

The Contractor shall report any discrepancies, in writing to Danfoss prior to commencing with any work.

Date:

March 2018


Quote No:

Drawn By:

Scale:


Drawing No:

LX-9



Detail:1 LX Typical Reflect Installation
LX-10

LX Cables (Reflect)
1. 088L3144 - 160 ft
Coverage 55SF
@ 4" Spacing



Detail:2 LX Typical Reflect Layout
LX-10

No:	Date:	Description:
-----	-------	--------------

Issued:

Project:

LX General Submittal

Drawing Title:

LX Reflect Typical Installation and Layout



6711 Mississauga Rd, Suite 410
Toronto, ON, L5N 2W3
Tel: 1-866-676-8062/711 Fax: 1 (905) 285-2055
www.NA.Heating.Danfoss.com

The Contractor shall verify all job site dimensions all drawing, details & specifications.

The Contractor shall report any discrepancies, in writing to Danfoss prior to commencing with any work.

Date:

March 2018

Quote No:

Drawn By:

Scale:

Drawing No:

LX-10