

Intelligent power conversion to accelerate the energy transition

Highlights

- > Unrivalled power density
- > Robust in harsh environments
- > Modular, scalable and serviceable
- > Designed for easy integration
- > Superior control performance
- > Digital twin simulation models reduce risk and get you to market faster
- > Cybersecure by design

Competitive

clean energy enabler



iC7-Hybrid enables smooth integration of energy sources or storages into a variety of systems. This range of intelligent power converters is designed to enable you to meet carbon goals while remaining profitable. iC7-Hybrid is available as liquid-cooled system modules, and its unique filter integration concept comes equipped with built-in wiring and coolant distribution for added convenience.

Powerful support for hybrid and electric applications in

- Marine and Offshore
- Shore power supply
- Power-to-X

Feature	Benefit
Purpose-built product dedicated to power conversion	Fit-for-purpose in your industry increases competitiveness and reduces engineering effort
Quality in focus – world most reliable power converter	High uptime and low operating expenses
Supported by DrivePro® services for global service capability	Fast service and long term planning capability
Engineering support from expert staff and a range of engineering tools	Go to market faster
Future-proof iC7 platform includes power conversion and AC drives applications	Lower lifecycle costs when both power converters and AC drives run in the same system
Integrated functional safety with STO and SS1-t SIL3, PLe as standard, or functional safety via fieldbus	Obtain certification more easily
Logic feature in MyDrive® Insight extends features and provides increased flexibility	Apply conditional controls, implement fault detection and diagnostics, create sequencing, modes, states, and interlocking logic


iC7-Hybrid liquid-cooled system modules – the ultimate in power density

iC7-Hybrid is available in 2 variants

- System modules: Ideal for installations with low height clearance
- System modules with integration unit: integrated filters in a compact housing. Optimized power density for easy cabinet installation and serviceability

Type approvals

Based on decades of experience across a wide range of Marine and Offshore applications, iC7-Hybrid power converters fulfill type approvals of major classification societies, such as ABS, BV, CCS, DNV, LR, KR, NK, and RINA.



Voltage range	3 x 525-690 V AC 640-1100 V DC 3 x 380-500 V AC (B5) 465-800 V DC (B5)
Current range	Grid Converter 236-5750 A DC/DC converter 300-3600 A Inverter module for Generator application 170-6400 A

Key specifications

Environmental conditions	
Protection rating drive modules	– IP00/UL Open Type
Ambient operating temperature	– -15°C (no frost) to +60°C (at IN)
Temperature of cooling agent	– -10 to +38 or +45 °C at (IN)(nominal), up to 60 °C with derating
Vibration (IEC60068-2-6)	– Displacement amplitude 1 mm (peak) at 2-13.2 Hz – Maximum acceleration amplitude 0.7 G at 13.2-100 Hz with maximum amplification of 5
Shock (IEC60068-2-27)	– Max 15G, 11 ms (in package)
Environmental operating conditions (IEC 60721-3-3)	– Climatic conditions: Class 3K22 – Chemically active substances: IEC 60721-3-3 Edition 3.0/ISO 3223 Second Edition, class C4 – Biological conditions: Class 3B1 – Mechanically active substances: Class 3S6
Compliance	– IEC-62477-1 – Cyber Security Product Certification IEC 62443-4-2 (UR26 and UR 27)
EMC	
EMC Immunity	– IEC/EN 61000-6-2
EMC emissions	– CISPR 11 (EN 55011) Class A (Grid Converter) – IEC/EN61800-3 (2018), category C3, when installed according to the instructions (for GC + INU)

Grid Converter application software key features

Control references	Fit for purpose application features	
Grid following	– DC voltage control (AFE) – DC power and DC current – Active and reactive power – Limit controllers	– Online transition between control modes during run state – Independent converter paralleling in same common AC and DC bus – Short circuit current injection with high overloadability – Support for 2 x 3-phase or DC voltage measurement option – Fall back to open loop in case feedback is lost – Blackout prevention (fall back to grid forming when limit is hit) – Black-start capability – Transformer interactive control & voltage drop compensation – Synchronization to external grid – Filter & transformer pre-magnetization – Main circuit breaker and pre-charge control – I/O, fieldbus, PC and control panel control place changeover during run state – Dedicated fieldbus control and status words & fieldbus customizer – Resilient mode enables operation at reduced power in the event that one of the parallel system modules is out of service
Grid forming	– Island mode – Droop control (microgrid) – Droop control with base load – Active and reactive power (PQ) – Limit controllers	
Fieldbus protocols	– Modbus TCP – PROFINET RT – EtherNet I/P	

DC/DC Converter application software key features

Control references	Fit for purpose application features	
	– DC bus voltage and current control – DC source voltage, power and current control – DC bus voltage as well as source voltage and current limit controllers – Buck or boost operation	– Smooth transition between control modes during run state – Droop controllers for voltage references and limit controllers – I/O, fieldbus, PC and control panel control place changeover during run state – Dedicated fieldbus control and status words – Fieldbus customizer – Black start from 350 V DC and higher – Resilient mode enables operation at reduced power in the event that one of the parallel system modules is out of service
Fieldbus protocols	– Modbus TCP – PROFINET RT – EtherNet I/P	

Generator application software key features

Control references & highlights	Key application features
– Torque, power and speed references – DC-voltage reference and limit controllers – Externally excited synchronous machine supported with DC voltage control (AFE) – True sensorless Flux Vector Control provides superior performance also at low speed even without encoder for PM and IM machine types – Closed loop control with bumpless transfer to open loop in case feedback is lost – Identify motor parameters with an automated sequence even at standstill (AMA)	– Multi-purpose use cases: Motor/generator control and AFE for shore connection with same hardware – Control shaft generator efficiently with pre-defined PTI/PTO operation modes – PTI/PTO transition assistant – Generator overload & stall protection – I/O, fieldbus, PC and control panel control place changeover during run state – Dedicated fieldbus control and status words & fieldbus customizer – Motor breaker control – Mains breaker & pre-charge control for shore connection applications – Load drooping with drooping removal – Black start from as low as 350 V DC – Comprehensive supervisions, protections, exceptions, limits & limit controllers – Resilient mode enables operation at reduced power in the event that one of the parallel system modules is out of service
Fieldbus protocols	– Modbus TCP – PROFINET RT – EtherNet I/P

iC7-Hybrid supports these functional extensions:

- I/O and relay option
- Temperature measurement option
- Voltage measurement option


MyDrive® Virtual simulation models reduce time to market

Remove constraints of the physical environment.

FMU models of Grid Converter, DC/DC Converter and Generator application are available for system simulation.

 **MyDrive® Virtual**

fmi Functional
Mock-Up
Interface



Open up a new dimension with iC7 series iC7-Automation | iC7-Marine | iC7-Hybrid

Imagine versatile and highly secure power conversion and motor control. Intensely powerful and compact converters and drives built to optimize a vast range of systems while giving you the flexibility to distribute intelligence the way you want.

Paving the way for a new dimension, where open, connected and intelligent systems are the new reality.

Any information, including, but not limited to information on selection of product, its application or use, product design, weight, dimensions, capacity or any other technical data in product manuals, catalogues descriptions, advertisements, etc. and whether made available in writing, orally, electronically, online or via download, shall be considered informative, and is only binding if and to the extent, explicit reference is made in a quotation or order confirmation. Danfoss cannot accept any responsibility for possible errors in catalogues, brochures, videos and other material. Danfoss reserves the right to alter its products without notice. This also applies to products ordered but not delivered provided that such alterations can be made without changes to form, fit or function of the product. All trademarks in this material are property of Danfoss A/S or Danfoss group companies. Danfoss and the Danfoss logo are trademarks of Danfoss A/S. All rights reserved.

Some functionalities listed in this fact sheet are for future implementation

Danfoss Drives A/S
Ulsnaes 1
6300 Graasten
Denmark
CVR reg. no. 19883876

© Danfoss 2025