

Monitor a wide variety of refrigerants with our innovative Gas Detectors

The Danfoss Gas Sensor is a state-of-the-art fixed gas detector which can detect a wide range of different gases. The sensors can be used on a stand-alone basis and integrated into your Refrigeration Control System or Building Management Systems.

Easily

programmed to
monitor 24/7

Ability to set up
multiple zones and
alarms levels.



Gas Detectors

Danfoss Gas Detectors are a range of products designed to meet all industrial and commercial refrigeration and air conditioning application requirements. Typical refrigerant gas applications include Halocarbons - HFCs, HCFCs, CFCs, Carbon Dioxide, and Hydrocarbons. DGS is available in IP41 and IP66 versions.



HGM-400 Halogen Gas Monitor Gas Monitor

HGM-400 is specified to support compliance to federal, state and local safety codes governing emissions. The Danfoss Multi-zone monitor provides continuous monitoring of gas levels in up to 16 separate test zones. The instrument is **easily programmed** to monitor

a variety of gases and independent leaks (small), spill (medium), and evacuation (large) levels may be designated for each zone. The instrument also retains a log of previous readings that can be easily accessed for analysis.

PGM-IR Portable Gas Monitor Portable Gas Monitors

The PGM-IR is designed to **detect, measure, and display** the concentration of refrigerant gas in the area being monitored.

To ensure accurate gas measurements, the monitor self-zeros every four minutes using an external supply of fresh air provided by activated carbon filtering.



During normal operation the Refrigerant Monitor displays both the current gas level and the peak gas level detected on its front LCD panel.

The monitor retains a log of previous readings that can be easily accessed at a later time for analysis.



DGS-SC

Gas Sensor

Gas Sensor

DGS helps to comply to environmental F-Gas Regulations and Health & Safety requirements, on new or existing systems in supermarkets, process refrigeration plants, refrigerated storage/warehousing, special applications areas/zones.

Functions:

- Utilizing either Semi-Conductor (SC) or Infrared (IR) technologies (only available for CO₂ versions).
- DGS gives **quick and immediate response** in detecting a wide range of different gases typically applied in Refrigeration & Air Conditioning systems.



- DGS sensors can be used **stand-alone** or with **integrated systems**. Danfoss ADAP-Kool® refrigeration control and monitoring system and/or Building management systems provide continuous real time automatic monitoring of the sensors.

Danfoss Gas Detectors offer absolute confidence that both safety and compliance requirements are met or exceeded.

Promote

safety and efficiency

by notifying the occupants exactly when to evacuate, based on leak level settings.

One family for your various needs...



Only available for HGM-400

- Optional models: LCD display, IP65 enclosure, EExd (Explosion Protected)
- Two digital outputs low level and high level alarm
- Manual or automatic alarm reset optional
- Detects, measures, and displays the level of refrigerant gas in the area being monitored
- Automatically logs up to 200 gas readings that can be printed/plotted for analysis
- Eliminates false alarms with use of non-dispersive IR source and sample draw system
- Extensive self diagnostics, providing both visual and audible indications when a fault occurs
- Battery powered, providing 8-12 hours of operation

All models

- Gas Detector is specifically developed for refrigeration applications
- Interchangeable precalibrated sensors
- Can operate as stand-alone product
- Linear analog outputs, current (mA) / (V) proportional to the gas concentration
- Adjustable setting for alarm levels and output contacts with optional NO or NC switches
- Alarm levels can be set locally
- Gas Detectors can be monitored by integrating them into an existing or New ADAP-KOOL Controls Solution.
- Available with a range of different sensor technologies to monitor refrigeration gases: electro-chemical, semi-conductor, catalytic and infra-red
- Measures all gases up to 10.000 ppm with a sensitivity of 1 ppm
- Visual and audible gas alarm indicators that are turned "ON" when the detected gas level exceeds a user defined trip-point

Avoiding

Safety Risks, which also

- Reduces equipment replacement cost
- Maintains equipment efficiency
- Promotes Safety
- Protects the Environment

Typical Applications

- Commercial refrigeration
- Cold Storage Facilities
- Supermarket/Hypermarket
- Distribution Centers
- Air Conditioning
- Chillers

Please contact your local Danfoss office for further information

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without consequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.