

Fluid Control, Pressure and Temperature Monitoring and Control

Core Industrial Products

for Distributors and Wholesalers

Easy

selection of future
proof products.





Selection Made Easy

With only a few clicks, Danfoss product selectors can help you to find the product you need.



Troubleshooting

Find information about how to use, maintain and troubleshoot our products



Core Industrial Products

See our catalogue with standard core industrial products for wholesalers and distributors.



Product Catalogue

See our complete product portfolio in the product catalogue.



Danfoss Learning

Danfoss Learning is your online access point to knowledge.



Documentation

Find data sheets and available products here.

contents

Fluid controls

Solenoid valves. Thermostatic valves. Externally operated valves

Pages 8-71

Pressure transmitters

Pages 72-110

Temperature sensors

Pages 111-129

Switches

Pressure switches. Temperature switches

Pages 130-173

Content	page
EV310A direct-operated 3/2-way compact solenoid valves	16
EV210A direct-operated 2/2-way compact solenoid valves	18
EV220A servo-operated 2/2-way solenoid valves	20
EV310B direct-operated 3/2-way solenoid valves	24
EV210B direct-operated 2/2-way solenoid valves	27
EV220B 6-22 servo-operated 2/2-way solenoid valves	32
EV220B 15-50 servo-operated 2/2-way solenoid valves	37
EV220B 65-100 servo-operated 2/2-way solenoid valves	44
EV250B assisted lift 2/2-way solenoid valves	48
EV224B servo-operated 2/2-way solenoid valves for high pressure air	52
EV225B servo-operated 2/2-way solenoid valves for steam	55
EV260B servo-operated 2-way proportional solenoid valves	59
AVTA thermostatic valves for industrial cooling applications	63
AV210 externally operated valves	69
MBS 3000 compact pressure transmitter	78
MBS 3050 compact pressure transmitters with pulse snubber	80
MBS 3200 compact pressure transmitters	82
MBS 3250 compact pressure transmitters with pulse-snubber	84
MBS 3100 compact pressure transmitter	86
MBS 3150 compact pressure transmitter with pulse-snubber	89
MBS 1900, OEM pressure transmitter for compressed air and water pump applications	91
MBS 1200/1250 OEM pressure transmitters for use in severe hydraulic applications	93
MBS 1300/1350 OEM electronic pressure switch with dual output for severe hydraulic applications	95
MBS 5100 pressure transmitter	97

MBS 5150 pressure transmitters with pulse-snubber	100
MBS 4510 flush diaphragm pressure transmitter	103
MBS 9200 Low pressure transmitter	105
MBS 9300 Low pressure transmitter	107
EMP 2 pressure transmitters	109
MBT 3250 temperature sensor	115
MBT 3270 temperature sensors	117
MBT 3560 temperature sensors with built-in transmitter	118
MBT 153 cable-type temperature sensors	120
MBT 5250 temperature sensor	122
MBT 5252 temperature sensors	124
MBT 5113 Temperature sensor	126
MBT 5116 Temperature sensors	128
RT pressure switches	137
BCP pressure controller / pressure limiter	142
KPS heavy-duty pressure switches	144
CAS heavy-duty pressure switches	146
KPI pressure switches for light industry	149
KP pressure switches for light industry	151
CS pressure switches for air and water	155
MBC 5100 block-type compact pressure switches	157
MBV 5000 pressure test valve	159
RT temperature switches	162
KPS temperature switches	165
KP temperature switches	168
MBC 8100 block-type compact temperature switches for marine applications	172

Danfoss Industrial Automation core products

Fluid controls

Solenoid valves: Direct, servo, assisted lift and proportional operated valves for water, air, oil and steam application. Differential pressure from 0 to 40 bar and connections from G 1/8 to G 2" flange. Thermostatic valves for cooling applications, and solar systems. Regulation ranges from 0 to 90 °C and connections from G 3/8 to G 1" flange.

Externally operated valves for demanding industrial applications. Differential pressure from 0 to 16 bar and connections from G 3/8 to G 2".

Direct operated valve
for closed and drain
systems



Assisted lift operated
valve for closed and
drain systems



Servo operated valve
for open systems



Valve for steam
applications



Thermostatic valve



Externally operated
valve for demanding
applications



Pressure transmitters

Pressure transmitters for industrial and marine applications. Design in cartridge, block and box with measuring range up to 600 bar. Output signal: 4 – 20 mA, 0 – 10 V, ratiometric etc. with an accuracy from 0,1% FS. Versions with marine and ATEX approvals.

Pressure transmitter in
cartridge design
for industrial applications



Pressure transmitter with flush
diaphragm for demanding
industrial applications



Pressure transmitter in
block design for industrial
and marine applications




Pressure transmitter in
box design for marine
applications



Temperature sensors

Temperature transmitters for industrial and marine applications with measuring range from -50 to 800 °C. Sensor type Pt100, Pt1000, PTC, NTC, integrated transmitter etc in different designs for example DIN 43650, DIN B, cable etc. Versions with marine and ATEX approvals.

Temperature transmitter in a cable version



Flexible temperature transmitter with different sensing elements and electrical connections



Temperature transmitter equipped with a DIN 43650 for industrial applications



Temperature transmitter equipped with a DIN B (B-head) for industrial and marine applications



Switches

Pressure and temperature switches (on-off) for industrial and marine applications from -60 °to 300 °C or -1 to 400 bar. Degree of enclosure: IP30 – IP67 in different designs, versions with marine, TÜV and ATEX approvals.

Pressure switch for industrial applications (enclosure degree from IP30 to IP55)



Pressure switch for boiler control



Temperature switch for industrial applications (enclosure degree from IP54 to IP66)



Pressure switch for industrial and marine applications in block design



Temperature switch for marine applications (enclosure degree IP67)



The main industries for these products are

Marine



Mobile hydraulics



Air compressors



Wind turbines



Industrial hydraulics



Heating equipment



Industrial water



Fluid control

With Danfoss valves you gain high quality, balanced with cost efficiency, making them the first choice in a many industrial applications.

Our valves are virtually maintenance free and designed to provide reliable service, year after year.

Three ways of efficiently controlling fluids:

Solenoid valves are an easy way to control and regulate fluids and gasses. Our programme consists of direct-operated, servo-operated and assisted lift versions. Solenoid valves are the right choice when you have media with limited dirt content and small to high flow volume.

Our solenoid valve programme consists of two ranges:

- The compact A range
 - offering small physical dimensions for control of flow where space is limited.
- The high performance B range
 - a sturdy and universal broad programme for control of flow in industrial applications and within heating and sanitary systems.

Externally operated valves are designed for specialised and demanding applications. These robust valves are the right choice for media with high dirt content, high viscosity, high ambient and media temperatures and large flow volumes. They are also suitable for humid environments, explosion hazard environments and for applications with low or unknown pressure conditions.

Thermostatic self-acting valves are a simple and reliable way to control the temperature of cooling equipment. They do not require electricity and they are insensitive to dirt and media pressure, making them a highly robust choice.



Example: Heating systems



An EV250B solenoid valve, a great all-round valve, is the preferred choice for many manufacturers in applications with low differential pressures, such as heating systems. Its design not only allows for a wide pressure range, it also reduces noise and increases the lifetime of the system through water hammer dampening.

Other applications

- Water booster pumps
- Membrane filtration units
- Fire-fighting pumping stations and equipment
- Biomass boilers
- Irrigation system
- Ultra and high purity water
- Catering water
- Desalination of saline water
- Water leak protection
- Car wash
- Dentist equipment
- Wind turbines
- Steam boilers
- Steam generators
- Laundry system
- Burners
- Cleaning units
- Dishwashing
- Degassing system
- Sterilizers and autoclaves
- Lubricated screw compressors
- Oil free compressors
- Drainage
- Pool control
- Solar
- Showers
- Saunas
- Sprinklers
- Petrol dispensers
- Heavy duty application


Fluid controls

in this catalogue



Type		EV310A 3/2-way	EV210A 2/2-way	EV220A 2/2-way	EV310B 3/2-way	EV210B 2/2-way	EV220B 6-22 2/2-way
Media	Water						
	Air and neutral gasses						
	Oil						
	Steam						
Characteristics	Dirty media				✓	✓	✓
	Long lifetime				✓	✓	✓
	Soft closing (Low waterhammer)			✓			✓
	System suitability						
		Closed and drain	Closed, drain and open	Open	Closed and drain	Closed, drain and open	Closed and drain
	Connection	G 1/8 – G 1/4, flange 32 mm	G 1/8 – G 1/4, flange 32 mm	G 1/4 – G 2	G 1/8 – G 3/8, flange 32 mm	G 1/8 – G 1	G 1/4 – G 1
	Function	NC or NO	NC or NO	NC or NO	NC or NO	NC or NO	NC or NO
	Orifice size mm	1.2 – 2	1.2 – 3.5	6 – 50	1.5 – 3.5	1.5 – 25	6 – 22
	Pressure range, bar	0 – 20	0 – 30	0.2 – 16	0 – 20	0 – 30	0.1 – 30
	Medium temperature max.	100 °C	120 °C	100 °C	100 °C	140 °C	100 °C
	Kv value m³/h	0.04 – 0.08	0.04 – 0.26	1 – 32	0.08 – 0.4	0.08 – 8	0.7 – 6
Material	Special features	Manual override option			Manual override option	Isolating diaphragm	
	Approvals*	WRAS		WRAS	GL	GL, WRAS and DNV	WRAS and DNV
	Valve body	Brass or stainless steel	Brass or stainless steel	Brass	Brass or stainless steel	Brass or stainless steel	Brass or DZR brass
	Internal	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
	Seal material	FKM	EPDM or FKM	EPDM, NBR or FKM	FKM	EPDM or FKM	EPDM or FKM

* Only EPDM versions in Normally Closed (NC) valves are WRAS approved. GL = Germanischer Lloyd. WRAS = Water Regulations Advisory Scheme. VA = Water supply and drainage of ETA Denmark.

								
EV220B 15-50 2/2-way	EV220B 65-100 2/2-way	EV250B 2/2-way	EV224B 2/2-way	EV225B 2/2-way	EV260B 2-way proportional	AVTA 2-way proportional	BVTs 2-way proportional	AV210
								
								
								
								
✓	✓	✓	✓		✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓		✓			
							Back-burning and overheat protection	
Closed and drain	Open	Closed and drain	Open	Open	Open	Closed		Closed, drain and open
G 1/2 – G 2	Flange connections: 2.5, 3 and 4"	G 3/8 – G 1	G 1/2 – G 1	G 1/4 – G 1	G 1/4 – G 3/4	G 3/8 – G 1	G 3/4	G 3/8 – G 2
NC or NO	NC	NC or NO	NC or NO	NC	NC	Thermostatic	Thermostatic	NC or NO
15 – 50	65 – 100	10 – 22	15 – 25	6 – 25	6 – 20	10 – 25	18	15 – 50
0.3 – 16	0.25 – 10	0 – 10	0.3 – 40	0.2 – 10	0.5 – 10	0 – 10	0 – 10	0 – 16
140 °C	90 °C	140 °C	60 °C	185 °C	80 °C	130 °C	110 °C	180 °C
4 – 40	50 – 130	2.5 – 7	4 – 11	0.9 – 6	0.8 – 5	1.4 – 5.5	2.6	4.5 – 74
			High pressure	IP65			Test function	Options: Manual override position indicator
GL, WRAS and DNV		WRAS	GL				TÜV	
Brass, DZR Brass or stainless steel	Cast iron	DZR Brass	Brass	DZR Brass	Brass	Brass or stainless steel	DZR brass	Gun metal or stainless steel
Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Brass or stainless steel	Stainless steel	Stainless steel
EPDM, FKM or NBR	EPDM or NBR	EPDM or FKM	NBR	PTFE and AFLAS	FKM and PTFE	EPDM or NBR	EPDM or NBR	PTFE

DNV = Det Norske Veritas. SVGW = Schweizerischer Verein des Gas- und Wasserfaches.

Media list for Danfoss In

Medium	Temperature/ Concentration			
			Brass	DZR-brass Bronze RG5
Ammonia			-	-
Brine (Potassium formate; without oxygen, closed systems)	-20 °C		✓	✓✓
Butane	20 °C		✓✓	✓✓
Chloric acid HCl			-	-
Citric acid			-	-
CO ₂			✓✓	✓✓
Compressed air			✓✓	✓✓
De-ionized water	80 °C		-	✓✓
Fresh Water	100 °C		✓✓	✓✓
Glycol	80 °C	100 %	✓	✓✓
Methane	20 °C		✓✓	✓✓
NaOH	50 °C	40 %	-	✓
Natural Gas (dry)	40 °C		✓✓	✓✓
Nitrogen (Air)			✓✓	✓✓
Oil; Animal			✓✓	✓✓
Oil; Mineral			✓✓	✓✓
Oil; Vegetable			✓✓	✓✓
Oxygen			✓	✓✓
Ozone			✓	✓✓
Propane	20 °C		✓✓	✓✓
Salt water (sea water)	20 °C	2 %	-	✓
Steam	185 °C		-	✓✓
Sulphuric acid H ₂ SO ₄			-	-
Water electrical conduction < 20 µ-siemens	60 °C		-	✓
Water electrical conduction > 500 µ-siemens	60 °C		✓✓	✓✓
Water electrical conduction between 20 and 500 µ-siemens	60 °C		✓	✓✓

✓✓	=	Suitable
✓	=	Suitable in most cases
-	=	Not recommendable

Industrial Valves

Body material			Seal material			
Stainless Steel AISI 316 / EN 1.44xx	Stainless Steel AISI 430 / EN 1.41xx armature/spring steel quality	Cast Iron	EPDM	NBR	FKM	PTFE
✓✓	✓✓	-	✓✓	✓	-	✓✓
✓✓	✓✓	✓	✓✓	✓	-	✓✓
✓✓	✓✓	✓✓	-	✓✓	✓✓	✓✓
-	-	-	-	-	✓	✓✓
✓	-	-	✓✓	✓✓	✓✓	✓✓
✓✓	✓✓	✓✓	✓✓	✓✓	✓✓	✓✓
✓✓	✓✓	✓	-	✓✓	✓✓	✓✓
✓✓	✓✓	-	✓✓	✓✓	✓	✓✓
✓✓	✓✓	✓	✓✓	✓	✓	✓✓
✓✓	✓✓	✓	✓✓	✓	-	✓✓
✓✓	✓✓	✓✓	-	✓✓	✓✓	✓✓
✓✓	✓✓	-	✓✓	-	-	✓✓
✓✓	✓✓	✓✓	-	✓	✓✓	✓✓
✓✓	✓✓	✓✓	✓✓	✓✓	✓✓	✓✓
✓✓	✓✓	✓✓	-	✓	✓✓	✓✓
✓✓	✓✓	✓✓	-	✓	✓✓	✓✓
✓✓	✓✓	✓	✓✓	✓	✓✓	✓✓
✓✓	✓✓	✓	✓✓	-	✓	✓✓
✓✓	✓✓	✓	✓✓	-	-	✓
✓✓	✓✓	✓✓	-	✓✓	✓✓	✓✓
✓	-	-	✓✓	✓✓	✓	✓✓
✓✓	✓✓	-	-	-	-	✓✓
-	-	-	✓	-	✓	✓✓
✓✓	✓	-	✓✓	✓✓	✓	✓✓
✓✓	✓✓	✓	✓✓	✓✓	✓✓	✓✓
✓✓	✓✓	-	✓✓	✓✓	✓	✓✓


Use the icons to find the right valve

Use the icons to help select the right solenoid valve for your application. Displayed on the top right corner of the following pages, the icons symbolize values and applications for each solenoid valve type.

Application: Select the right valve based on the differential pressure of the system.


Closed or drain systems

In a closed-circuit system, there is not significant pressure difference between the inlet and outlet. For example, central heating systems are closed-circuit systems – as are tank systems where the drain is located at a low level in the tank.



Open systems

In an open-circuit system, the inlet side of the valve will have a relatively high pressure compared to the outlet side. Tap water and sprinkler systems are examples of applications with open systems.



Value: the following icons indicate values for the different solenoid valves – select according to your needs.

Insensitive to dirt




A dirt-resistant valve is fitted with a coaxial, self-cleaning filter which protects the valve pilot. Valves controlled by a B-series coil have a square armature which allows dirt particles to pass through easily.

Long lifetime and high performance

A specially shaped and strengthened diaphragm reduces stress on the rubber, and prolongs valve lifetime. Coil lifetime is also extended, depending on the shape and IPclass.

Effective water hammer damping / soft closing

The valve design protects system damage from water hammer through soft closing. To minimize water hammer, some valves have an optimized diaphragm assembly and equalizing orifice. By changing the equalizing orifice on the EV220B 15-50, you can also increase the closing time.




Results are based on comparisons between Danfoss valves only.

Complete valve or valve and coil separately

A complete solenoid valve consists of: Valve + coil + plug.

The valves can be delivered as separate parts – valve housing, coil and plug or as complete valves.



Selection Made Easy

Need help selecting the right component for your application? With only a few clicks, Danfoss product selectors can help you find the right product for, standard applications.

Developed to help wholesalers, retailers, installers and endusers pinpoint their solenoid valve needs, the web-based tool makes product selection quick and easy.

All it takes is an internet connection to access the solenoid valve selector tool from your desk or laptop, tablet or smartphone.

To discover just how easy the product selectors are to use, please visit:

<http://valveselector.danfoss.com>

To visit by mobile, scan the QR code:

Welcome

The Danfoss Switch Selector will help you as installer or end-user to specify the correct industrial pressure switch for your application.

> Contact
> Click for more information

Pressure Switches

Application ①
Please select

Enclosure

Reset function

Connection size

Setting range

> Reset > Search

Visit our mobile site

Scan the QR code to visit the Danfoss Switch Selector on your mobile device.

No scanner? - Search "Barcode Reader" in App-store or Android Market.

Pressure Switches

Code no: 032U7115
Indirect servo-operated solenoid valve, type EV220B
Connection size: G 1/2
Function: Voltage off > Valve closed (NC)
> More details

Code no: 01RF7360
Coil type BB, dip-on, IP55 with cable plug
Coil voltage: AC ~ 110 V ~ 50/60 Hz
> More details

Code no: 042M0150
> More details

Medium: Water (max 90°C)
System: Sprinkler

> Print this page > Where to buy
> Send result as email
> Send result as text message
> New search

INDUSTRIAL AUTOMATION > Privacy Policy > Country

EV310A direct-operated 3/2-way compact solenoid valves




-				+
-				+

EV310A covers a wide range of small competitive, direct-operated 3/2-way solenoid valves for use within industrial applications, for example pilot valve applications.

- 3/2-way
 - Direct-operated
 - DN 1.2 - DN2
- G 1/8" to G 1/4"
 - Ambient temperature: 50 °C
 - Brass or stainless steel valve body
 - NC (normally closed) and NO (normally open) versions
 - Wetted parts: brass, stainless steel, copper and FKM rubber

Dimensions, weight and mounting angle:



Thread ISO 228/1	L [mm]	B [mm] Coil type		H [mm]	A [mm]	Weight without coil [kg]
		AB	AM			
G 1/8	26	22	33	54	13	0.090
G 1/4	35	22	33	59	17.5	0.115

EV310A direct-operated valve, brass, NC



Type	Connection	Kv [m³/h]	Media Oil / Air	Seal material	Differential pressure [bar]		Code number
					AM coil Oil	AM coil Air	
EV310A 1.5	G 1/8	0.07	✓	FKM	0 – 5	0 – 12	032H8087
EV310A 2.0	G 1/8	0.08	✓	FKM	0 – 4	0 – 8	032H8089
EV310A 1.2	G 1/4	0.04	✓	FKM	0 – 9	0 – 20	032H8095
EV310A 1.5	G 1/4	0.07	✓	FKM	0 – 5	0 – 12	032H8097
EV310A 2.0	G 1/4	0.08	✓	FKM	0 – 4	0 – 8	032H8099

EV310A direct-operated valve, brass, NO



Type	Connection	Kv [m³/h]	Media Oil / Air	Seal material	Differential pressure [bar] AM coil	Code number
EV310A 1.2	G 1/8	0.04	✓	FKM	0 – 13/0 – 9	032H8125

Coils for EV310A



Voltage		Frequency [Hz]	Power consumption [W]		AP coil DIN 43650-A	AM coil DIN 43650-A
[V] AC	[V] DC		AP coil	AM coil		
24		50		7.5		042N0842
24		60	5	5.5	042N4193	042N0842
110		50		7.5		042N0845
110		60		5.5		042N0845
110 – 120		60	5		042N4192	
230		50		9.5	042N4191	042N0840
230		60		6.5		042N0840
208 – 240		60	5.5		042N4191	
240		50		7.5		042N0841
240		60		5.5		042N0841
12		–		8.5		042N0848
24		–		9.0		042N0843

Cable plugs, IP65 enclosure



To use with all AP, AM coils	042N0156	042N0156
To use with AP, AM coils - 24 V AC and DC	042N0263	042N0263
To use with AP, AM coils - 230 V AC	042N0265	042N0265


Accessories for EV310A

Electronic timers for coils for pulse start, for IP65 only



Type	Description	Control [50/60 Hz]	Power cons. Max [W]	Ambient temp. [°C]	Code number
ET 20 M	External adjustable timing from 1 to 45 minutes with 1 to 15 seconds drain open. With manual override (test button) Electrical connection DIN 43650 A / EN 175 301-803-A	24 – 240	20.0	–10 – 50	042N0185

EV210A direct-operated 2/2-way compact solenoid valves



-			
-			
-			


EV210A covers a wide range of small, direct-operated 2/2-way solenoid valves for use in industrial machinery.

The compact design together with the broad range of coils means that EV210A covers a broad variety of industrial applications.

- 2/2-way
- Compact dimensions
- Direct-operated

- DN 1.2 - DN 3.5
- G 1/8 to G 1/4
- Ambient temperature: 50 °C
- Brass or stainless steel valve body
- NC (normally closed)
- Wetted parts: brass, stainless steel, copper, EPDM or FKM rubber

Dimensions, weight and mounting angle:



Thread ISO 228/1	L [mm]	B [mm] Coil type		H [mm]	A [mm]	Weight with AB coil [kg]
		AB	AM			
G 1/8	26	22	33	54	13	0.09
G 1/4	35	22	33	59	17.5	0.115

EV210A direct operated valve, brass or stainless steel (SS), NC



Type	Connection	Kv [m³/h]	Media		Seal material	Body material		Differential pressure [bar]		Code number
			Water 120 °C	Oil / Air		Brass	SS	AB coil [a.c.] / [d.c.]	AM coil [a.c.] / [d.c.]	
EV210A 1.2	G 1/8	0.04	✓		EPDM	✓		0 - 30 / 0 - 17.5	0 - 30 / 0 - 24	032H8000
EV210A 1.2	G 1/8	0.04		✓	FKM	✓		0 - 28 / 0 - 16	0 - 30 / 0 - 24	032H8001
EV210A 1.5	G 1/8	0.08	✓		EPDM	✓		0 - 18 / 0 - 9.5	0 - 28 / 0 - 22.5	032H8002
EV210A 1.5	G 1/8	0.08		✓	FKM	✓		0 - 15 / 0 - 8	0 - 26 / 0 - 19	032H8003
EV210A 1.5	G 1/8	0.08		✓	FKM		✓	0 - 15 / 0 - 8	0 - 26 / 0 - 19	032H8027
EV210A 2	G 1/8	0.11	✓		EPDM	✓		0 - 11 / 0 - 5.5	0 - 23 / 0 - 18.5	032H8004

EV210A direct operated valve, brass or stainless steel (SS), NC



Type	Connection	Kv [m³/h]	Media		Seal material	Body material		Differential pressure [bar]		Code number
			Water 120 °C	Oil / Air		Brass	SS	AB coil [a.c.] / [d.c.]	AM coil [a.c.] / [d.c.]	
EV210A 2	G 1/8	0.11		✓	FKM	✓		0-9/0-5	0-22/0-17	032H8005
EV210A 2	G 1/8	0.11		✓	FKM		✓	0-9/0-5	0-22/0-17	032H8029
EV210A 2.5	G 1/8	0.17	✓		EPDM	✓		0-6/0-3	0-17/0-13	032H8006
EV210A 2.5	G 1/8	0.17		✓	FKM	✓		0-5/0-2.5	0-16/0-12	032H8007
EV210A 2.5	G 1/8	0.17		✓	FKM		✓	0-5/0-2.5	0-16/0-12	032H8031
EV210A 3	G 1/8	0.22	✓		EPDM	✓		0-4/0-1.5	0-13/0-9	032H8008
EV210A 3	G 1/8	0.22		✓	FKM	✓		0-3/0-1.5	0-12/0-8	032H8009
EV210A 3	G 1/8	0.22		✓	FKM		✓	0-3/0-1.5	0-12/0-8	032H8033
EV210A 2.5	G 1/4	0.17	✓		EPDM	✓		0-6/0-3	0-17/0-13	032H8014
EV210A 2.5	G 1/4	0.17		✓	FKM	✓		0-5/0-2.5	0-16/0-12	032H8015
EV210A 2.5	G 1/4	0.17		✓	FKM		✓	0-5/0-2.5	0-16/0-12	032H8039
EV210A 3	G 1/4	0.22	✓		EPDM	✓		0-4/0-1.5	0-13/0-9	032H8016
EV210A 3	G 1/4	0.22		✓	FKM	✓		0-3/0-1.5	0-12/0-8	032H8017
EV210A 3	G 1/4	0.22		✓	FKM		✓	0-3/0-1.5	0-12/0-8	032H8041
EV210A 3.5	G 1/4	0.26	✓		EPDM	✓		0-2.8/0-1.2	0-11/0-6	032H8018
EV210A 3.5	G 1/4	0.26		✓	FKM	✓		0-2/0-0.8	0-10/0-5.5	032H8019
EV210A 3.5	G 1/4	0.26		✓	FKM		✓	0-2/0-0.8	0-10/0-5.5	032H8043

Coils for EV210A



Voltage		Frequency [Hz]	Power consumption [W]		AP coil	AM coil
[V] AC	[V] DC		AP coil	AM coil	DIN 43650-A	DIN 43650-A
24		50		7.5		042N0842
24		60	5	5.5	042N4193	042N0842
110		50		7.5		042N0845
110		60		5.5		042N0845
110 – 120		60	5		042N4192	
230		50		9.5	042N4191	042N0840
230		60		6.5		042N0840
208 – 240		60	5.5		042N4191	
240		50		7.5		042N0841
240		60		5.5		042N0841
12		–		8.5		042N0848
24		–		9.0		042N0843

Cable plugs, IP65 enclosure



To use with all AP, AM coils

042N0156

042N0156



To use with AP, AM coils - 24 V AC and DC

042N0263

042N0263

To use with AP, AM coils - 230 V AC

042N0265

042N0265


Accessories for EV210A

Electronic timers for coils for pulse start, IP65 only

Type	Description	Control [50/60 Hz]	Power cons. Max [W]	Ambient temp. [°C]	Code number
ET 20 M	External adjustable timing from 1 to 45 minutes with 1 to 15 seconds drain open. With manual override (test button) Electrical connection DIN 43650 A / EN 175 301-803-A	24 - 240	20.0	-10 – 50	042N0185



EV220A servo-operated 2/2-way solenoid valves




-			+
-			+
-			+

EV220A is a compact servo-operated 2/2-way solenoid valve program, especially designed for use in machines and equipment with limited space.

- 2/2-way
- Servo-operated
- DN 6 – DN50
- G 1/4" to G 2"

- Ambient temperature: 50 °C
- Brass valve body
- NC (normally closed) and NO (normally open) versions
- ISO 228/1 or NPT thread connection
- Nominal pressure from PN 16
- Wetted parts: brass, stainless steel, copper, EPDM or NBR rubber

Dimensions, weight and mounting angle:



Type / orifice size	L [mm]	B [mm]	B ₁ [mm] coil type		H [mm]		H ₁ [mm]	Weight with AM coil [kg]
			AM		NC	NO		
EV220A 6	51	50	33		76	80	13	0.56
EV220A 10	51	50	33		76	80	13	0.54
EV220A 12	58	58	33		77	81	13	0.62
EV220A 14	58	58	33		77	81	13	0.6
EV220A 18	90	58	33		78	82	18	0.82
EV220A 22	90	58	33		83	87	22	1.1
EV220A 32	120	82	33		95	-	27	2.1
EV220A 40	130	95	33		105	-	32	3.3
EV220A 50	162	113	33		111	-	37	4.4

EV220A servo-operated 2/2-way solenoid valves, brass, NC



Type	Connection	Kv [m³/h]	Media			Seal material	Differential pressure [bar]	Code number
			Water 120 °C	Water 90 °C	Oil / Air			
EV220A 6	G ¼	1	✓			EPDM	0.2 – 16	042U4001
EV220A 6	G ¼	1		✓	✓	NBR	0.2 – 16	042U4003
EV220A 10	G ¾	1.6	✓			EPDM	0.2 – 16	042U4011
EV220A 10	G ¾	1.6		✓	✓	NBR	0.2 – 16	042U4013
EV220A 10	G ½	1.6	✓			EPDM	0.2 – 16	042U4012
EV220A 10	G ½	1.6		✓	✓	NBR	0.2 – 16	042U4014
EV220A 12	G ½	2.5		✓	✓	NBR	0.3 – 16	042U4023
EV220A 14	G ½	4	✓			EPDM	0.3 – 16	042U4022
EV220A14	G ½	4		✓	✓	NBR	0.3 – 16	042U4024
EV220A 18	G ¾	7	✓			EPDM	0.3 – 16	042U4031
EV220A 18	G ¾	7		✓	✓	NBR	0.3 – 16	042U4032
EV220A 22	G 1	7	✓			EPDM	0.3 – 16	042U4041
EV220A 22	G 1	7		✓	✓	NBR	0.3 – 16	042U4042
EV220A 32	G 1 ¼	15	✓			EPDM	0.3 – 16	042U4085
EV220A 32	G 1 ¼	15		✓	✓	NBR	0.3 – 16	042U4084
EV220A 40	G 1 ½	18	✓			EPDM	0.3 – 16	042U4087
EV220A 40	G 1 ½	18		✓	✓	NBR	0.3 – 16	042U4086
EV220A 50	G 2	32	✓			EPDM	0.3 – 16	042U4089
EV220A 50	G 2	32		✓	✓	NBR	0.3 – 16	042U4088

EV220A servo-operated 2/2-way solenoid valves, brass, NO



Type	Connection	Kv [m³/h]	Media			Seal material	Differential pressure [bar]	Code number
			Water 120 °C	Water 90 °C	Oil / Air			
EV220A 6	G ¼	1		✓	✓	NBR	0.2 – 16	042U4053
EV220A 10	G ¾	1.6		✓	✓	NBR	0.2 – 16	042U4063
EV220A 14	G ½	4		✓	✓	NBR	0.3 – 16	042U4074
EV220A 18	G ¾	7		✓	✓	NBR	0.3 – 16	042U4082
EV220A 22	G 1	7		✓	✓	NBR	0.3 – 16	042U4092

Coils for EV220A



Voltage		Frequency [Hz]	Effect [W] AM coil	AM coil
[a.c.]	[d.c.]			DIN 43650-A
24		50/60	7.5/5.5	042N0842
110		50/60	7.5/5.5	042N0845
230		50/60	9.5/6.5	042N0840
240		50/60	7.5/5.5	042N0841
	12	-	8.5	042N0848
	24	-	9.0	042N0843

Cable plugs, IP65 enclosure



To use with AM coils

042N0156



To use with AM coils - 24 V a.c. and d.c.

042N0263

To use with AM coils - 230 V a.c.

042N0265

Spare parts and accessories for EV220A



Spare part kits, NC

Application	Seal material	Code number
EV220A 6 - 10	EPDM	042U1000
EV220A 6 - 10	NBR	042U1001
EV220A 12-14	EPDM	042U1003
EV220A 12 - 14	NBR	042U1004
EV220A 18 - 22	EPDM	042U1006
EV220A 18 - 22	NBR	042U1007
EV220A 32	EPDM	042U1037
EV220A 32	NBR	042U1038
EV220A 40	EPDM	042U1039
EV220A 40	NBR	042U1040
EV220A 50	EPDM	042U1041
EV220A 50	NBR	042U1042


Electronic timers for coils for pulse start, only AM coil



Type	Description	Control [V 50/60 Hz]	Power cons. Max [W]	Ambient temp. [°C]	Code number
ET 20 M	External adjustable timing from 1 – 45 minutes with 1 – 15 seconds drain open. With manual override (test button) Electrical connection DIN 43650 A / EN 175 301-803-A	24 – 240	20.0	-10 – 50	042N0185

Capacity diagram for EV220A

Example for water:
Capacity for EV220A at differential
pressure of 3 bar: Approx. 7 m³/h



EV310B direct-operated 3/2-way solenoid valves



-			+
-			+

EV310B covers a wide range of direct-operated 3/2-way solenoid valves for universal use.


EV310B is a real robust valve program with high performance and can be used in all kind of tough working conditions.

Clip-on coils can not be used on EV310B.

- 3/2-way
- Direct-operated
- DN 1.5 – DN 3.5
- Ambient temperature: 40 °C
- Brass valve body
- Thread (G 1/8" to G 3/8") or flange (32x32 mm) connections
- NC (normally closed) and NO (normally open) versions
- Manual override versions
- Nominal pressure from PN 16
- Wetted parts: brass, stainless steel, copper and FKM rubber

Dimensions, weight and mounting angle:

Weight without coil: 0.220 kg



All dimensions in millimetres

EV310B without coil, brass, NC



Type	Connection	Kv [m³/h]	Media Oil / Air	Seal material	Differential pressure [bar]	Code number
EV310B 2	G 1/8	0.15	✓	FKM	0 – 16	032U4901
EV310B 2	G 1/4	0.15	✓	FKM	0 – 16	032U4904

Media: EPDM: Water (120 °C), FKM: Oil and Air, NBR: Water (90 °C), Oil and Air

EV310B without coil, brass, NC, manual override unit



Type	Connection	Kv [m³/h]	Media Oil / Air	Seal material	Differential pressure [bar]	Code number
EV310B 2	G 1/8	0.15	✓	FKM	0 – 16	032U4916
EV310B 2	G 1/4	0.15	✓	FKM	0 – 16	032U4919

Media: EPDM: Water (120 °C), FKM: Oil and Air, NBR: Water (90 °C), Oil and Air

Coils for EV310B



Voltage		Frequency [Hz]	Effect [W] BA coil	BA coil IP00
[a.c.]	[d.c.]			
24		50	8.5	042N7508
48		50	9.5	042N7510
115		50	9.0	042N7512
220 – 230		50	12	042N7501
240		50	10	042N7502
380 – 400		50	12	042N7504
	12	-	14	042N7550
	24	-	14	042N7551

Cable plug, IP65 enclosure



To use with all BA coils	042N0156
To use with BA coils - 24 V a.c.+d.c.	042N0263
To use with BA coils - 230 V	042N0265

Accessories for EV310B

Electronic timers for coils for pulse start



Type	Description	Control [V 50/60 Hz]	Power cons. Max [W]	Ambient temp. [°C]	Code number
ET 20 M	External adjustable timing from 1 – 45 minutes with 1 – 15 seconds drain open. With manual override (test button) Electrical connection DIN 43650 A / EN 175 301-803-A	24 – 240	20.0	-10 – 50	042N0185

The EV210B solenoid valve for tough working conditions

The EV210B is designed to control the flow of water, oil or air in a wide range of applications.

1 Increased performance without increasing coil power

The EV210B's non-fixed valve plate doubles performance without increasing the coil power or reducing the valve's lifetime. When the coil is energised, the armature moves and accumulates energy, and when it hits the valve plate, the impact lifts the plate to increase performance.

2 Modular design for customised solutions

EV210B with direct actuator is extremely durable at high temperature and pressure. The valve has a modular design which is perfect for customised solutions.

3 Long life

Designed to last, the EV210B has a high wall thickness, a unique square-shaped armature and a specially designed spring. And because the spring movements are very close, wear is significantly reduced.

4 Insensitive to dirt


Due to the armature's unique design, there is a low risk of particles sticking to the armature. If particles become lodged between the armature and the armature tube or top, they will be displaced by the fluid when the armature moves.

5 Optimum Kv-values for many connections


The optimum shape and diameter of the valve plate, as well as the valve plate lift ensure that the EV210B has high Kv-values (capacity).

Secure opening and closing

To prevent particles lodging in the armature, an isolating diaphragm is available for valves up to 4.5 mm.



EV210B direct-operated 2/2-way solenoid valves




-			
-			
-			

EV210B covers a wide range of direct-operated 2/2-way solenoid valves for universal use. EV210B is a real robust valve program with high performance and can be used in all kind of tough working conditions.

- 2/2-way
- High Performance series
- Direct-operated
- DN 1.5 – DN 25

- Brass or stainless steel valve body
- NC (normally closed) and NO (normally open) versions
- ISO 228/1 G 1/8" to G 1"
- UL listed version with NPT for North America (EVI)
- Wetted parts: brass, stainless steel, copper, EPDM, FKM or NBR rubber

Dimensions, weight and mounting angle:



Type / orifice size	L [mm]	B [mm]	B ₁ [mm] Coil type		H ₁ [mm]	H [mm]	Weight with BB coil [kg]
			BA	BB			
EV210B 1.5/2	35.0	34	32	46	12.0	70.0	0.39
EV210B 3/4.5	38.0	34	32	46	11.0	70.0	0.44
EV210B 6	45.5	34	32	46	15.5	72.5	0.46
EV210B 8/10	49.0	34	32	46	15.5	72.5	0.53
EV210B 15	58.0	53.0	32	46	12.5	92.5	0.69
EV210B 20	90.0	58.0	32	46	18.0	92.0	1.34
EV210B 25	90.0	58.0	32	46	23.0	96.0	1.34

EV210B direct operated valve with coil and plug IP65, brass, NC



Type	Connection	Kv [m³/h]	Media Oil / Air	Seal material	Differential pressure [bar]	Coil BB [V a.c. 50 Hz] [V d.c.]	Code number
EV210B 1.5	G 1/8	0.08	✓	FKM	0 – 30	24	032U145802
EV210B 1.5	G 1/8	0.08	✓	FKM	0 – 30	24	032U145816
EV210B 1.5	G 1/8	0.08	✓	FKM	0 – 30	230	032U145831
EV210B 3	G 1/4	0.30	✓	FKM	0 – 13	24	032U147002
EV210B 3	G 1/4	0.30	✓	FKM	0 – 20	24	032U147016
EV210B 3	G 1/4	0.30	✓	FKM	0 – 20	230	032U147031
EV210B 4.5	G 3/8	0.55	✓	FKM	0 – 4.5	24	032U148002
EV210B 4.5	G 3/8	0.55	✓	FKM	0 – 10	24	032U148016
EV210B 4.5	G 3/8	0.55	✓	FKM	0 – 10	230	032U148031

EV210B direct operated valve, brass, NC



Type	Connection	Kv [m³/h]	Media			Seal material	Differential pressure [bar]		Code number
			Water 120 °C	Water 90 °C	Oil / Air		BA coil [a. c.] / [d. c.]	BB/BE coil [a. c.] / [d. c.]	
EV210B 1.5	G 1/8	0.08	✓			EPDM	0 – 30 / 0 – 30	0 – 30 / 0 – 30	032U5701
EV210B 1.5	G 1/8	0.08			✓	FKM	0 – 30 / 0 – 30	0 – 30 / 0 – 30	032U5702
EV210B 1.5	G 1/8	0.08		✓	✓	NBR	0 – 30 / 0 – 30	0 – 30 / 0 – 30	032U1200
EV210B 1.5	G 1/4	0.08			✓	FKM	0 – 30 / 0 – 30	0 – 30 / 0 – 30	032U3629
EV210B 1.5	G 1/4	0.08		✓	✓	NBR	0 – 30 / 0 – 30	0 – 30 / 0 – 30	032U1205
EV210B 2	G 1/8	0.15			✓	FKM	0 – 30 / 0 – 20	0 – 30 / 0 – 30	032U5704
EV210B 2	G 1/4	0.15	✓			EPDM	0 – 30 / 0 – 20	0 – 30 / 0 – 30	032U5707
EV210B 2	G 1/4	0.15			✓	FKM	0 – 30 / 0 – 20	0 – 30 / 0 – 30	032U5708
EV210B 3	G 1/8	0.30			✓	FKM	0 – 15 / 0 – 9	0 – 20 / 0 – 13	032U5706
EV210B 3	G 1/8	0.30	✓			EPDM	0 – 15 / 0 – 9	0 – 20 / 0 – 13	032U5705
EV210B 3	G 1/4	0.30		✓	✓	NBR	0 – 15 / 0 – 9	0 – 20 / 0 – 13	032U1220
EV210B 3	G 1/4	0.30	✓			EPDM	0 – 15 / 0 – 9	0 – 20 / 0 – 13	032U5709
EV210B 3	G 1/4	0.30			✓	FKM	0 – 15 / 0 – 9	0 – 20 / 0 – 13	032U5710
EV210B 3	G 3/8	0.30	✓			EPDM	0 – 15 / 0 – 9	0 – 20 / 0 – 13	032U3642
EV210B 3	G 3/8	0.30		✓	✓	NBR	0 – 15 / 0 – 9	0 – 20 / 0 – 13	032U1225
EV210B 3	G 3/8	0.30			✓	FKM	0 – 15 / 0 – 9	0 – 20 / 0 – 13	032U3643
EV210B 4.5	G 1/4	0.55			✓	FKM	0 – 8 / 0 – 3.5	0 – 10 / 0 – 4.5	032U3601
EV210B 4.5	G 3/8	0.55	✓			EPDM	0 – 8 / 0 – 3.5	0 – 10 / 0 – 4.5	032U3605
EV210B 4.5	G 3/8	0.55			✓	FKM	0 – 8 / 0 – 3.5	0 – 10 / 0 – 4.5	032U3606
EV210B 6	G 3/8	0.70		✓	✓	NBR	0 – 2.5 / 0 – 1	0 – 4 / 0 – 2	032U1231
EV210B 6	G 3/8	0.70	✓			EPDM	0 – 2.5 / 0 – 1	0 – 4 / 0 – 2	032U3607
EV210B 6	G 3/8	0.70			✓	FKM	0 – 2.5 / 0 – 1	0 – 4 / 0 – 2	032U3608
EV210B 8	G 1/2	1.00	✓			EPDM	0 – 1.5 / 0 – 0.5	0 – 2 / 0 – 1.2	032U3615
EV210B 8	G 1/2	1.00			✓	FKM	0 – 1.5 / 0 – 0.5	0 – 2 / 0 – 1.2	032U3616
EV210B 10	G 1/2	1.50	✓			EPDM	0 – 0.8 / 0 – 0.3	0 – 1.2 / 0 – 0.6	032U3617
EV210B 10	G 1/2	1.50			✓	FKM	0 – 0.8 / 0 – 0.3	0 – 1.2 / 0 – 0.6	032U3618

EV210B direct operated valve, DZR brass, NC



Type	Connection	Kv [m ³ /h]	Media		Seal material	Differential pressure [bar]		Code number
			Water 120 °C	Oil / Air		BA/BE coil [a. c.] / [d. c.]	BB coil [a. c.] / [d. c.]	
EV210B 15	G ½	2.85	✓		EPDM	0 – 0.25 / -	0 – 0.3 / 0 – 0.15	032U3619
EV210B 15	G ½	2.85		✓	FKM	0 – 0.25 / -	0 – 0.3 / 0 – 0.15	032U3620
EV210B 20	G ¾	4.50	✓		EPDM	-	0 – 0.28 / 0 – 0.12	032U3621
EV210B 20	G ¾	4.50		✓	FKM	-	0 – 0.28 / 0 – 0.12	032U3622
EV210B 25	G 1	8.00	✓		EPDM	-	0 – 0.25 / 0 – 0.09	032U3623
EV210B 25	G 1	8.00		✓	FKM	-	0 – 0.25 / 0 – 0.09	032U3624

EV210B direct operated valve, brass, NO



Type	Connection	Kv [m³/h]	Media		Seal material	Differential pressure [bar]	Code number
			Water 120 °C	Oil / Air		BA/BE/BB coil [a. c.] / [d. c.]	
EV210B 1.5	G 1/8	0.08	✓		EPDM	0 – 30	032U3630
EV210B 1.5	G 1/8	0.08		✓	FKM	0 – 30	032U3631
EV210B 2.0	G 1/8	0.15	✓		EPDM	0 – 12	032U3632
EV210B 2.0	G 1/8	0.15		✓	FKM	0 – 12	032U3633
EV210B 2.0	G 1/4	0.15	✓		EPDM	0 – 12	032U3636
EV210B 2.0	G 1/4	0.15		✓	FKM	0 – 12	032U3637
EV210B 3.0	G 1/4	0.30	✓		EPDM	0 – 5	032U3638
EV210B 3.0	G 1/4	0.30		✓	FKM	0 – 5	032U3639
EV210B 4.5	G 1/4	0.55	✓		EPDM	0 – 2	032U3640
EV210B 4.5	G 1/4	0.55		✓	FKM	0 – 2	032U3641

Coils for EV210B

Voltage		Frequency	Power consumption [W]				BA coil IP00	BB coil IP00 clip-on	BY coil IP65 clip-on	BE coil IP67 clip-on
[V] AC	[V] DC	[Hz]	BA	BB	BY	BE				
24		50	8.5	11	14	12	042N7508	018F7358	018F7655	018F6707
24		60			12				018F7655	
48		50	9.5			11	042N7510			018F6709
110		50		15	14			018F7360	018F7663	
110		60		13				018F7360		
110 - 120		60			14				018F7663	
115		50	9.0	11		11	042N7512	018F7361		018F6711
220 - 230		50	12	11		12	042N7501	018F7351		018F6701
230		50			16				018F7658	
208 - 240		60			14				018F7658	
240		50	10	11		11	042N7502	018F7352		018F6702
380 - 400		50	12	14		14	042N7504	018F7353		018F6703
440		60		15		15		018F7353		018F6703
	12		14	13		15	042N7550	018F7396		018F6756
	24		14	16		13	042N7551	018F7397		018F6757

Cable plug, IP65 enclosure

To use with all BA, BB and BY coils



042N0156



042N0156



042N0156

No plug
needed IP67
terminal box
fitted as
standard

To use with BA, BB and BY coils - 24 V AC+DC



042N0263



042N0263



042N0263

To use with BA, BB and BY coils - 230 V AC

042N0265

042N0265

042N0265

Spare parts and accessories for EV210B

Isolating diaphragm kit, NC

Application	Seal material	Code number
EV210B 1.5 - 4.5	EPDM	042U1009
EV210B 1.5 - 4.5	FKM	042U1010



Permanent magnet

Application	Code number
Fits all EV220B valves	018F0091



Electronic timers for coils for pulse start

Type	Description	Control [50/60 Hz]	Power cons. Max [W]	Ambient temp. [°C]	Code number
ET 20 M	External adjustable timing from 1 to 45 minutes with 1 to 15 seconds drain open. With manual override (test button) Electrical connection DIN 43650 A / EN 175 301-803-A	24 - 240	20.0	-10 - 50	042N0185



The EV220B 6-22 for medium to large flow

The EV220B 6-22 is a high performance, robust valve programme.

1 Low water hammer

The softest closing valve on the market, the EV220B 6-22 has an optimised diaphragm shape, added reinforcement for internal damping, and a special damping cone to ensure viscous damping in the critical late closing stage.

2 Insensitive to dirt

The square armature design enables the armature to move freely and reduces the risk of dirt particles lodging in the armature. If particles do lodge between the armature and the armature tube walls, they are quickly displaced by the fluid when the valve is activated.

3 Broad range of body and sealing materials

The EV220B 6-22 is available in two body materials. The brass version is ideal for applications with a limited risk of corrosion. Tougher applications should use versions with dezincification resistant brass (DZR brass) bodies and stainless steel inserts.

The EV220B 6-22 is also available with two seal materials. Both the EPDM and FKM seals can cope with all common media and a wide temperature range, while the EPDM versions have water approvals.

4 Long lifetime


The moulded rubber diaphragm has a special profile that greatly reduces the effects of stress and maximises valve lifetime.

5 Wide coil range


The valves use the standard B-range of coils from IP00 to IP67, including the clip-on system and specialty coils, making it easy to select a coil with the right features. And the special ATEX coil programme is ideal for hazardous environments.

6 High capacity across the entire pressure range

The optimised diaphragm shape gives a very high lift height, providing excellent capacity and tightness at any pressure.



EV220B 6-22 servo-operated 2/2-way solenoid valves




-			
-			
-			

EV220B 6-22 is a direct servo-operated 2/2-way solenoid valve program with connections from 1/4" – 1". This program is especially for OEM applications demanding a robust solution and moderate flow rates.

- 2/2-way
- Servo-operated
- DN 6 – DN 22
- Brass or DZR (de-zincification resistant) brass valve body
- NC (normally closed) and NO (normally open) versions
- ISO 228/1 or NPT thread connection (EVSI and EVSI-U)
- Nominal pressure from PN 25
- Wetted parts: brass, stainless steel, copper, EPDM, FKM or NBR rubber

Dimensions, weight and mounting angle:



Type / orifice size	L [mm]	B [mm]	B ₁ [mm] Coil type		H ₁ [mm]	H [mm]	Weight with BB coil [kg]
			BA	BB/BE			
EV220B 6	45.5	43,5	32	46	13.0	74.0	0.46
EV220B 10	51.5	48.0	32	46	13.0	77.0	0.53
EV220B 12	58.0	54.0	32	46	13.0	77.0	0.59
EV220B 18	90.0	62.0	32	46	18.0	83.0	0.89
EV220B 22	90.0	62.0	32	46	18.0	98.0	0.89

EV220B 6-22 servo-operated valves with coil and plug, IP65, brass, NC



Type	Connection	Kv [m³/h]	Media		Seal material	Differential pressure [bar]	Coil BB		Code number
			Water 90 °C	Oil / Air			[V a.c. 50Hz]	[V d.c.]	
EV220B 10	G 3/8	1.5	✓	✓	NBR	0.1 – 10		24	032U151802
EV220B 10	G 3/8	1.5	✓	✓	NBR	0.1 – 20	24		032U151816
EV220B 10	G 3/8	1.5	✓	✓	NBR	0.1 – 20	230		032U151831
EV220B 12	G 1/2	2.5	✓	✓	NBR	0.3 – 6*		24	032U153802
EV220B 12	G 1/2	2.5	✓	✓	NBR	0.3 – 10	24		032U153816
EV220B 12	G 1/2	2.5	✓	✓	NBR	0.3 – 10	230		032U153831
EV220B 18	G 3/4	6	✓	✓	NBR	0.3 – 6*		24	032U528602
EV220B 18	G 3/4	6	✓	✓	NBR	0.3 – 10	24		032U528616
EV220B 18	G 3/4	6	✓	✓	NBR	0.3 – 10	230		032U528631
EV220B 22	G 1	6	✓	✓	NBR	0.3 – 6*		24	032U528702
EV220B 22	G 1	6	✓	✓	NBR	0.3 – 10	24		032U528716
EV220B 22	G 1	6	✓	✓	NBR	0.3 – 10	230		032U528731

*6 bar max opening differential pressure is measured at 6% under voltage (22.6 volt d.c. hot coil), 50 °C ambient, 90 °C media temperature and nominal pressure PN 6

EV220B 6-22 servo-operated valves, brass, NC



Type	Connection	Kv [m³/h]	Media		Seal material	Differential pressure [bar]	Code number
			Water 100 °C	Oil / Air			
EV220B 6	G 1/4	0.7	✓		EPDM	0.1 – 20	032U1236
EV220B 6	G 1/4	0.7		✓	FKM	0.1 – 20	032U1237
EV220B 6	G 3/8	0.7	✓		EPDM	0.1 – 20	032U1241
EV220B 6	G 3/8	0.7		✓	FKM	0.1 – 20	032U1242
EV220B 10	G 3/8	1.5	✓		EPDM	0.1 – 20	032U1246
EV220B 10	G 3/8	1.5		✓	FKM	0.1 – 20	032U1247
EV220B 10	G 1/2	1.5	✓		EPDM	0.1 – 20	032U1251
EV220B 10	G 1/2	1.5		✓	FKM	0.1 – 20	032U1252
EV220B 12	G 1/2	2.5	✓		EPDM	0.3 – 10	032U1256
EV220B 12	G 1/2	2.5		✓	FKM	0.3 – 10	032U1255
EV220B 18	G 3/4	6	✓		EPDM	0.3 – 10	032U1261
EV220B 18	G 3/4	6		✓	FKM	0.3 – 10	032U1260
EV220B 22	G 1	6	✓		EPDM	0.3 – 10	032U1263
EV220B 22	G 1	6		✓	FKM	0.3 – 10	032U1266

EV220B 6-22 servo-operated valves, brass, NO



Type	Connection	Kv [m³/h]	Media		Seal material	Differential pressure [bar]	Code number
			Water 100 °C	Oil / Air			
EV220B 6	G 3/8	0.7	✓		EPDM	0.1 – 10	032U1238
EV220B 6	G 3/8	0.7		✓	FKM	0.1 – 10	032U1239
EV220B 10	G 1/2	1		✓	FKM	0.1 – 10	032U1249

Coils for EV220B 6 - EV220B 22:



Voltage		Frequency [Hz]	Power consumption [W]				BA coil IP00	BB coil IP00 clip-on	BY coil IP65 clip-on	BE coil IP67 clip-on
[V] AC	[V] DC		BA	BB	BY	BE				
24		50	8.5	11	14	12	042N7508	018F7358	018F7655	018F6707
24		60			12				018F7655	
48		50	9.0			11	042N7510			018F6709
110		50		15	14			018F7360	018F7663	
110		60		13				018F7360		
110 - 120		60			14				018F7663	
115		50	9.0	11		11	042N7512	018F7361		018F6711
220 - 230		50	12	11		12	042N7501	018F7351		018F6701
230		50			16				018F7658	
208 - 240		60			14				018F7658	
240		50	10	11		11	042N7502	018F7352		018F6702
380 - 400		50	12	14		14	042N7504	018F7353		018F6703
440		60		15		15		018F7353		018F6703
	12		14	13		15	042N7550	018F7396		018F6756
	24		14	16		13	042N7551	018F7397		018F6757

Cable plug, IP65 enclosure

To use with all BA, BB and BY coils



042N0156

042N0156

042N0156

No plug
needed IP67
terminal box
fitted as
standard

To use with BA, BB and BY coils - 24 V AC+DC



042N0263

042N0263

042N0263

To use with BA, BB and BY coils - 230 V AC

042N0265

042N0265

042N0265

Spare parts and accessories for EV220B 6-22

Spare part kits, NC

Application	Seal material	Code number
EV220B 6	EPDM	032U1062
EV220B 6	FKM	032U1063
EV220B 10	EPDM	032U1065
EV220B 10	FKM	032U1066



Spare part kits, NC

Application	Seal material	Code number
EV220B 12	EPDM	032U1068
EV220B 12	FKM	032U1067
EV220B 18	EPDM	032U1070
EV220B 18	FKM	032U1069



Spare part kits, NO

Application	Seal material	Code number
EV220B 6	EPDM	032U0165
EV220B 6	FKM	032U0166
EV220B 10	FKM	032U0167



Permanent magnet

Description

Fits all EV220B valves



Code number

018F0091


Electronic timers for coils for pulse start, only IP65

Type	Description	Control [50/60 Hz]	Power cons. Max [W]	Ambient temp. [°C]	Code number
ET 20 M	External adjustable timing from 1 to 45 minutes with 1 to 15 seconds drain open. With manual override (test button) Electrical connection DIN 43650 A / EN 175 301-803-A	24 - 240	20.0	-10 - 50	042N0185




Capacity diagram for EV220B 6 - EV220B 22:

Example, water: EV220B 10 NC,
at 4 bar diff. pressure: Approx: 3 m³/h



The EV220B 15-50 for large capacities and damping water hammer

A universal indirect servo-operated 2/2 way solenoid valve range, the EV220B 15-50 is ideal for a wide variety of applications.



1 Effective against water hammer

To minimise water hammer, the valve's moulded diaphragm reinforces internal damping, and a special damping cone provides viscous damping in the very late closing stage. The closing speed can be adjusted by changing the equalising orifice.

2 Insensitive to dirt

A self-cleaning coaxial filter in the main valve flow prevents dirt entering the pilot system. However, if the equalising orifice does become blocked, the dirt can easily be removed with compressed air.

3 Broad temperature and material range

With a range of materials, there is an EV220B 15-50 valve suited to your application. The EV220B 15-50 is available in brass, as well as dezincification resistant brass (DZR) and stainless steel versions for aggressive steam applications.

The EPDM seals remain soft even at -30 °C, while the FKM and NBR rubber seals can handle temperatures up to 140 °C.

4 Wide coil range up to IP67

The EV220B range uses the standard B-range of coils from IP00 to IP67. Coils subject to water splash and temperatures up to 80 °C should use the more powerful and robust clip-on coils.


5 High capacity across the entire pressure range

The valve body has a smooth internal shape, and the specially designed diaphragm increases the lift height capacity. In indirect servo-operated valves, the kv-value is determined by the diameter of the orifice and the diaphragm lift height.

6 Good external tightness even at high differential pressures

Pressure in the valve increases the distance between the valve cover and body, so the moulded diaphragm has a built-in O-ring to avoid leakage. This provides an excellent seal between the valve cover and body even at high pressures, ensuring excellent external tightness.

EV220B 15-50 servo-operated 2/2-way solenoid valves



-				+
-				+
-				+


EV220B 15-50 is a universal indirect servo-operated 2/2-way solenoid valve program. Valve body in brass, dezincification resistant brass and stainless steel ensures that a broad variety of application can be covered.

Built-in pilot filter as standard, adjustable closing time and enclosures up to IP67 ensures optimal performance even under critical working conditions.

- 2/2-way
- Servo-operated
- DN 15 – DN 50

- Valve body available in brass, DZR brass, gun metal or stainless steel
- NC and NO versions
- ISO 228/1 or NPT thread connection (EVSI and EVSI-U)
- Built in filter for protection of pilot system
- Water hammer damped
- Adjustable closing time available
- Nominal pressure from PN 10
- Wetted parts: brass, stainless steel, copper, tin, EPDM, FKM or NBR rubber

Dimensions, weight and mounting angle:



Type / orifice size	L [mm]	B [mm]	B ₁ [mm] Coil type		H ₁ [mm]	H [mm]	Weight with BB coil [kg]
			BA	BB/BE			
EV220B 15	80	52	32	46	15	99	1.04
EV220B 20	90	58	32	46	18	103	1.24
EV220B 25	109	70	32	46	22	113	1.64
EV220B 32	120	82	32	46	27	120	2.24
EV220B 40	130	95	32	46	32	129	3.46
EV220B 50	162	113	32	46	37	135	4.54

EV220B 15-50 servo-operated valves with coil and plug, brass, IP65, NC



Type	Connection	Differential pressure [bar]	Kv [m³/h]	Media		Seal material	Coil BB		Code number
				Water 90 °C	Oil / Air		[V a.c. 50 Hz]	[V d.c.]	
EV220B 15	G ½	0.3 – 16	4	✓	✓	NBR		24	032U451402
EV220B 15	G ½	0.3 – 16	4	✓	✓	NBR	24		032U451416
EV220B 15	G ½	0.3 – 16	4	✓	✓	NBR	230		032U451431
EV220B 20	G ¾	0.3 – 16	8	✓	✓	NBR		24	032U453002
EV220B 20	G ¾	0.3 – 16	8	✓	✓	NBR	24		032U453016
EV220B 20	G ¾	0.3 – 16	8	✓	✓	NBR	230		032U453031
EV220B 25	G 1	0.3 – 16	11	✓	✓	NBR		24	032U453402
EV220B 25	G 1	0.3 – 16	11	✓	✓	NBR	24		032U453416
EV220B 25	G 1	0.3 – 16	11	✓	✓	NBR	230		032U453431
EV220B 32	G 1 ¼	0.3 – 16	18	✓	✓	NBR		24	032U456802
EV220B 32	G 1 ¼	0.3 – 16	18	✓	✓	NBR	24		032U456816
EV220B 32	G 1 ¼	0.3 – 16	18	✓	✓	NBR	230		032U456831
EV220B 40	G 1 ½	0.3 – 16	24	✓	✓	NBR		24	032U458502
EV220B 40	G 1 ½	0.3 – 16	24	✓	✓	NBR	24		032U458516
EV220B 40	G 1 ½	0.3 – 16	24	✓	✓	NBR	230		032U458531
EV220B 50	G 2	0.3 – 16	40	✓	✓	NBR		24	032U460402
EV220B 50	G 2	0.3 – 16	40	✓	✓	NBR	24		032U460416
EV220B 50	G 2	0.3 – 16	40	✓	✓	NBR	230		032U460431

EV220B 15-50 servo-operated valves, NC

DZR brass, brass or stainless steel (SS)



Type	Connection	Differential pressure [bar]	Kv [m³/h]	Media			Seal material	Body material			Code number
				Water 120 °C	Water 90 °C	Oil / Air		DZR	Brass	SS	
EV220B 15	G ½	0.3 – 16	4	✓			EPDM	✓			032U5815
EV220B 15	G ½	0.3 – 16	4	✓			EPDM		✓		032U7115
EV220B 15	G ½	0.3 – 16	4	✓			EPDM			✓	032U8500
EV220B 15	G ½	0.3 – 10	4			✓	FKM		✓		032U7116
EV220B 15	G ½	0.3 – 10	4			✓	FKM			✓	032U8506
EV220B 15	G ½	0.3 – 16	4		✓	✓	NBR		✓		032U7170
EV220B 20	G ¾	0.3 – 16	8	✓			EPDM	✓			032U5820
EV220B 20	G ¾	0.3 – 16	8	✓			EPDM		✓		032U7120
EV220B 20	G ¾	0.3 – 16	8	✓			EPDM			✓	032U8501
EV220B 20	G ¾	0.3 – 10	8			✓	FKM		✓		032U7121
EV220B 20	G ¾	0.3 – 10	8			✓	FKM			✓	032U8507
EV220B 20	G ¾	0.3 – 16	8		✓	✓	NBR		✓		032U7171
EV220B 25	G 1	0.3 – 16	11	✓			EPDM	✓			032U5825
EV220B 25	G 1	0.3 – 16	11				EPDM	✓			032U5825
EV220B 25	G 1	0.3 – 16	11	✓			EPDM		✓		032U7125
EV220B 25	G 1	0.3 – 16	11	✓			EPDM			✓	032U8502
EV220B 25	G 1	0.3 – 10	11			✓	FKM		✓		032U7126
EV220B 25	G 1	0.3 – 10	11			✓	FKM			✓	032U8508
EV220B 25	G 1	0.3 – 16	11		✓	✓	NBR		✓		032U7172
EV220B 32	G 1 ¼	0.3 – 16	18	✓			EPDM	✓			032U5832

EV220B 15-50 servo-operated valves, NC

DZR brass, brass or stainless steel (SS)



Type	Connection	Differential pressure [bar]	Kv [m³/h]	Water 120 °C	Media		Seal material	Body material			Code number
					Water 90 °C	Oil / Air		DZR	Brass	SS	
EV220B 32	G 1 ¼	0.3 – 16	18	✓			EPDM		✓		032U7132
EV220B 32	G 1 ¼	0.3 – 16	18	✓			EPDM			✓	032U8503
EV220B 32	G 1 ¼	0.3 – 10	18			✓	FKM		✓		032U7133
EV220B 32	G 1 ¼	0.3 – 10	18			✓	FKM			✓	032U8509
EV220B 32	G 1 ¼	0.3 – 16	18		✓	✓	NBR		✓		032U7173
EV220B 40	G 1 ½	0.3 – 16	24	✓			EPDM	✓			032U5840
EV220B 40	G 1 ½	0.3 – 16	24	✓			EPDM		✓		032U7140
EV220B 40	G 1 ½	0.3 – 16	24	✓			EPDM			✓	032U8504
EV220B 40	G 1 ½	0.3 – 10	24			✓	FKM		✓		032U7141
EV220B 40	G 1 ½	0.3 – 10	24			✓	FKM			✓	032U8510
EV220B 40	G 1 ½	0.3 – 16	24		✓	✓	NBR		✓		032U7174
EV220B 50	G 2	0.3 – 16	40	✓			EPDM	✓			032U5850
EV220B 50	G 2	0.3 – 16	40	✓			EPDM		✓		032U7150
EV220B 50	G 2	0.3 – 16	40	✓			EPDM			✓	032U8505
EV220B 50	G 2	0.3 – 10	40			✓	FKM		✓		032U7151
EV220B 50	G 2	0.3 – 10	40			✓	FKM			✓	032U8511
EV220B 50	G 2	0.3 – 16	40		✓	✓	NBR		✓		032U7175

EV220B 15-50 servo-operated valves, brass, NO



Type	Connection	Differential pressure [bar]	Kv [m³/h]	Water 120 °C	Media		Seal material	Code number
					Water 90 °C	Oil / Air		
EV220B 15	G ½	0.3 – 16	4	✓			EPDM	032U7117
EV220B 15	G ½	0.3 – 16	4		✓	✓	NBR	032U7180
EV220B 20	G ¾	0.3 – 16	8	✓			EPDM	032U7122
EV220B 20	G ¾	0.3 – 16	8		✓	✓	NBR	032U7181
EV220B 25	G 1	0.3 – 16	11	✓			EPDM	032U7127
EV220B 25	G 1	0.3 – 16	11		✓	✓	NBR	032U7182
EV220B 32	G 1 ¼	0.3 – 16	18	✓			EPDM	032U7134
EV220B 32	G 1 ¼	0.3 – 16	18		✓	✓	NBR	032U7183
EV220B 40	G 1 ½	0.3 – 16	24	✓			EPDM	032U7142
EV220B 40	G 1 ½	0.3 – 16	24		✓	✓	NBR	032U7184
EV220B 50	G 2	0.3 – 16	40	✓			EPDM	032U7152
EV220B 50	G 2	0.3 – 16	40		✓	✓	NBR	032U7185

Coils for EV220B 15 - EV220B 50



Voltage		Frequency [Hz]	Power consumption [W]				BA coil IP00	BB coil IP00 clip-on	BY coil IP65 clip-on	BE coil IP67 clip-on
[V] AC	[V] DC		BA	BB	BY	BE				
24		50	8.5	11	14	12	042N7508	018F7358	018F7655	018F6707
24		60			12				018F7655	
48		50	9.0			11	042N7510			018F6709
110		50		15	14			018F7360	018F7663	
110		60		13				018F7360		
110 - 120		60			14				018F7663	
115		50	9.0	11		11	042N7512	018F7361		018F6711
220 - 230		50	12	11		12	042N7501	018F7351		018F6701
230		50			16				018F7658	
208 - 240		60			14				018F7658	
240		50	10	11		11	042N7502	018F7352		018F6702
380 - 400		50	12	14		14	042N7504	018F7353		018F6703
440		60		15		15		018F7353		018F6703
	12		14	13		15	042N7550	018F7396		018F6756
	24		14	16		13	042N7551	018F7397		018F6757

Cable plug, IP65 enclosure



To use with all BA, BB and BY coils

042N0156

042N0156

042N0156



To use with BA, BB and BY coils - 24 V AC+DC

042N0263

042N0263

042N0263

To use with BA, BB and BY coils - 230 V AC

042N0265

042N0265

042N0265

No plug
needed IP67
terminal box
fitted as
standard

Spare parts for EV220B 15-50

Spare part kit, NC



Application	Seal material	Code number
EV220B 15	EPDM	032U1071
EV220B 15	FKM	032U1072
EV220B 15	NBR	032U6013
EV220B 20	EPDM	032U1073
EV220B 20	FKM	032U1074
EV220B 20	NBR	032U6014
EV220B 25	EPDM	032U1075
EV220B 25	FKM	032U1076
EV220B 25	NBR	032U6015
EV220B 32	EPDM	032U1077
EV220B 32	FKM	032U1078
EV220B 32	NBR	032U6016
EV220B 40	EPDM	032U1079
EV220B 40	FKM	032U1080
EV220B 40	NBR	032U6017
EV220B 50	EPDM	032U1081
EV220B 50	FKM	032U1082
EV220B 50	NBR	032U6018

Spare part kit, NO



Application	Seal material	Code number
EV220B 15-50	FKM	032U0295
EV220B 15-50	EPDM	032U0296
EV220B 15-50	NBR	032U0299

Manual override kit, tool operated



Application	Description	Code number
EV220B 15-50	Manual override kit. Used for manual override in event of power failure. Note: Valve height is increased by 16 mm	032U0150

Manual override kit, hand operated



Application	Seal material	Description	Code number
EV220B 15-50	EPDM	Manual override kit. Used for manual override in event of power failure. Note: Valve height is increased by 16 mm	032U7390

Spare parts and accessories for EV220B 15-50



Isolating diaphragm kits

Application	Seal material	Description	Code number
EV220B 15-50	EPDM	The isolating diaphragm protects the actuator against dirt and corrosion.	042U1009
EV220B 15-50	FKM		042U1010

Adjustable orifice kit, brass



Application	Seal material	Code number
EV220B 15-50	EPDM	032U0682
EV220B 15-50	NBR	032U0681
EV220B 15-50	FKM	032U0683

Equalizing orifice



Application	Seal material	Dimension [mm]	Description	Code number
EV220B 25-32	FKM	1.2	The valves closing time can be changed by installing an equalizing orifice of a size which deviates from the standard valve.	032U0085
EV220B 15-20	EPDM	0.5		032U0082
EV220B 25-32-40	EPDM	0.8		032U0084
EV220B 50	EPDM	1.2		032U0086
EV220B 40-50	FKM	1.4		032U0087

Permanent magnet



Application	Code number
Fits all EV220B valves	018F0091

Electronic timers for coils for pulse start, only IP65




Type	Description	Control [V 50/60 Hz]	Power cons. Max [W]	Ambient temp. [°C]	Code number
ET 20 M	External adjustable timing from 1 – 45 minutes with 1 – 15 seconds drain open. With manual override (test button) Electrical connection DIN 43650 A / EN 175 301-803-A	24 – 240	20.0	-10 – 50	042N0185

Capacity diagram for EV220B 15 - EV220B 50:


Example, water:

Capacity for EV220B 15 at differential pressure of 3 bar. Approx. 7 m³/h




Example, air:

Capacity for EV220B 15 at inlet pressure (p_1) of 5 bar and outlet pressure (p_2) of 3.5 bar: Approx. 245 Nm³/h



Flow information on other media types: Please contact Danfoss.

EV220B 65-100 servo-operated 2/2-way solenoid valves



-			+
-			+
-			+




EV220B 65-100 is a 2/2-way solenoid valve program for use in robust industrial applications, demanding high flow rates. The valve is designed with cast iron valve bodies and flanged connection.

Water-hammer damped design and built-in pilot filter ensures a reliable operational period.

- 2/2-way
- Servo-operated

- DN 65 – DN 100
- Cast iron valve body
- Flange connection
- Max. medium temperature: 90 °C
- Nominal pressure from PN 10
- Wetted parts: brass, centralen WS 3820 and NBR rubber

Dimensions, weight and mounting angle:



Type / orifice size	L [mm]	L ₁ [mm]	Coil width [mm]		Ø D [mm]	H ₁ [mm]	H ₂ [mm]	Weight with BE coil [kg]
			10 W a.c.	20 W d.c.				
EV220B 65	320	224	46	66	185	85	185	24
EV220B 80	370	265	46	66	200	93	215	34
EV220B 100	430	315	46	66	220	103	240	44

EV220B 65-100 servo-operated valves, NC



Type	Connection Flange / [inch]	Kv [m³/h]	Media Water 120 °C	Water 90 °C	Oil / Air	Seal material	Body material Cast iron	Differential pressure [bar]	Code number
EV220B 65	2 ½	50	✓	✓	✓	NBR	✓	0.25 – 10	016D3330
EV220B 65	2 ½	50	✓			EPDM	✓	0.25 – 10	016D6065
EV220B 80	3	75	✓	✓	✓	NBR	✓	0.25 – 10	016D3331
EV220B 80	3	75	✓			EPDM	✓	0.25 – 10	016D6080
EV220B 100	4	130	✓			EPDM	✓	0.25 – 10	016D6100

Coils for EV220B 65 - EV220B 100



Voltage		Frequency	Power consumption [W]		BB coil	BE coil
[V] AC	[V] DC	[Hz]	BB	BE	IP00 clip-on	IP67 clip-on
24		50	11	12	018F7358	018F6707
48		50		11		018F6709
110		50	15		018F7360	
110		60	13		018F7360	
115		50	11	11	018F7361	018F6711
220 - 230		50	11	12	018F7351	018F6701
240		50	11	11	018F7352	018F6702
380 - 400		50	14	14	018F7353	018F6703
440		60	15	15	018F7353	018F6703
	12	–	13	13	018F7396	018F6756
	24	–	16	16	018F7397	018F6757

Cable plug, IP65 enclosure



042N0156



042N0263

042N0265

No plug needed -
IP67 terminal box
fitted as standard

Accessories for EV220B 65-100 servo-operated valves

Permanent magnet



Application	Code number
Fits all EV220B valves	018F0091

Electronic timers for coils for pulse start , only IP65



Type	Description	Control [50/60 Hz]	Power cons. Max [W]	Ambient temp. [°C]	Code number
ET 20 M	External adjustable timing from 1 to 45 minutes with 1 to 15 seconds drain open. With manual override (test button) Electrical connection DIN 43650 A / EN 175 301-803-A	24 - 240	20.0	-10 – 50	042N0185


Spare parts for EV220B 65 - EV220B 100 servo-operated valves



Flange sets. Each set contains 2 flanges.

Application	Connection	Code number
EV220B 65	2½ in. weld	027N3065
EV220B 80	3 in. weld	027N3080
EV220B 100	4 in. weld	027N3100

Spare part kit



Application	Code number EPDM	Code number NBR
EV220B 65	016D0078	016D0095
EV220B 80	016D0079	016D0096
EV220B 100	016D0080	

Seal kit



Application	Code number EPDM
EV220B 65	016D0075
EV220B 80	016D0076
EV220B 100	016D0077


Manual override kit, hand operated




Application	Seal material	Description	Code number
EV220B 65 – EV220B100	EPDM	Manual override kit. Used for manual override in event of power failure. Note: Valve height is increased by 16 mm	032U7390

Capacity diagram for EV220B 65 – EV220B 100:

Example, water:
Capacity for EV220B 65-100 at differential pressure of 2 bar: Approx. 70 m³/h





The EV250B for low and unspecified pressure conditions

Designed for closed circuits, the EV250B 2/2-way assisted-lift solenoid valve range damps water hammer at low differential pressure and moderate flow rates.

1 Clip-on coil systems

Suitable for clip-on coil systems, the EV250B ensures faultless mounting so that both assembly and dismantling is simple and safe. And when needed, a hermetic seal against moisture penetration gives a tighter seal and a safer and more stable fastening.

2 High lift at zero or low differential pressures

High armature lift secures a high opening degree from zero differential pressure.

3 For aggressive low-pressure steam

Made from dezincification resistant brass (DZR), the EV250B valve body is suitable for aggressive technical water and steam.


4 Good external tightness even at high differential pressures

The thick valve cover and moulded diaphragm with built-in o-ring secures an excellent seal between valve cover and body even at high pressure.

Extra features

The EV250B is available with a range of water approvals, including the British WRAS approval. It is also available with hum-free coils, American NPT threads and UL approval, IP67 protection, EEx coils, and DNV ship approval.

EV250B assisted lift 2/2-way solenoid valves



-			+
-			+
-			+


EV250B with assisted lift can operate from zero and up to 10 bar differential pressure.

This 2/2-way valve program is especially to use in closed circuits with low differential pressure, but demanding moderate flow rates. Valve body in dezincification resistant brass for ensuring a long life even in connection with aggressive steam media.

EV250B is compatible with the broad Danfoss coil program with enclosures from IP00 up to IP67. Medium temperatures up to 140 °C (low pressure steam).

- 2/2-way
- Assisted lift
- DN 10 – DN 22
- DZR brass valve body
- NC (normally closed) or NO (normally open)
- From zero differential pressure
- Especially suitable for closed circuits and for emptying tanks
- Available with WRAS, VA and UL approvals
- ISO or NPT thread connections
- Nominal pressure from PN 10
- Wetted parts: brass, stainless steel, copper, EPDM or FKM rubber

Dimensions, weight and mounting angle:



Type / orifice size	L [mm]	B [mm]	B ₁ [mm] Coil type	H ₁ [mm]	H [mm]	Weight with BB coil [kg]
			BB/BE			
G 3/8	58	52.3	46	12.5	91	0.84
G 1/2	58	52.3	46	12.5	91	0.84
G 3/4	90.5	58	46	18	92	1.04
G 1	90	58	46	22.3	96.3	1.34

EV250B assisted lift valve with coil and plug IP65, DZR brass, NC



Type	Connection	Kv [m³/h]	Media Water 120 °C	Seal material	Differential pressure [bar]	Coil BB		Code number
						[V a.c. 50 Hz]	[V d.c.]	
EV250B 10	G 3/8	2.5	✓	EPDM	0 – 6*		24	032U157102
EV250B 10	G 3/8	2.5	✓	EPDM	0 – 10	24		032U157116
EV250B 10	G 3/8	2.5	✓	EPDM	0 – 10	230		032U157131
EV250B 12	G 1/2	4	✓	EPDM	0 – 6*		24	032U158002
EV250B 12	G 1/2	4	✓	EPDM	0 – 10	24		032U158016
EV250B 12	G 1/2	4	✓	EPDM	0 – 10	230		032U158031
EV250B 18	G 3/4	6	✓	EPDM	0 – 6*		24	032U161402
EV250B 18	G 3/4	6	✓	EPDM	0 – 10	24		032U161416
EV250B 18	G 3/4	6	✓	EPDM	0 – 10	230		032U161431
EV250B 22	G 1	7	✓	EPDM	0 – 6*		24	032U162402
EV250B 22	G 1	7	✓	EPDM	0 – 10	24		032U162416
EV250B 22	G 1	7	✓	EPDM	0 – 10	230		032U162431

* 6 bar max opening differential pressure is measured at 6% under voltage (22.6 volt d.c. hot coil), 50 °C ambient, 90 °C media temperature and nominal pressure PN 6

EV250B assisted lift valve with coil and plug IP65, DZR brass, NO



Type	Connection	Kv [m³/h]	Media Water 120 °C	Seal material	Differential pressure [bar]	Coil BB		Code number
						[V a.c. 50 Hz]	[V d.c.]	
EV250B 18	G 3/4	4.9	✓	EPDM	0 – 10	230		032U537431
EV250B 20	G 1	5.2	✓	EPDM	0 – 10	230		032U537631

EV250B assisted lift valve, DZR brass, NC



Type	Connection	Kv [m³/h]	Media		Seal material	Differential pressure [bar]	Code number
			Water 120 °C	Oil / Air			
EV250B 10	G 3/8	2.5	✓		EPDM	0 – 10	032U5250
EV250B 10	G 3/8	2.5		✓	FKM	0 – 10	032U5251
EV250B 12	G 1/2	4	✓		EPDM	0 – 10	032U5252
EV250B 12	G 1/2	4		✓	FKM	0 – 10	032U5253
EV250B 18	G 3/4	6	✓		EPDM	0 – 10	032U5254
EV250B 18	G 3/4	6		✓	FKM	0 – 10	032U5255
EV250B 22	G 1	7	✓		EPDM	0 – 10	032U5256
EV250B 22	G 1	7		✓	FKM	0 – 10	032U5257

EV250B assisted lift valve, DZR brass, NO



Type	Connection	Kv [m³/h]	Media Water 120 °C	Seal material	Differential pressure [bar]	Code number
EV250B 10	G 3/8	2.5	✓	EPDM	0 – 10	032U5350
EV250B 12	G 1/2	4	✓	EPDM	0 – 10	032U5352
EV250B 18	G 3/4	4.9	✓	EPDM	0 – 10	032U5354
EV250B 22	G 1	5.2	✓	EPDM	0 – 10	032U5356

Coils for EV250B



Voltage		Frequency [Hz]	Power consumption [W]			BB coil	BY coil	BE coil
[V] AC	[V] DC		BB	BY	BE	IP00 clip-on	IP65 clip-on	IP67 clip-on
24		50	11	14	12	018F7358	018F7655	018F6707
24		60		12			018F7655	
48		50			11			018F6709
110		50	15	14		018F7360	018F7663	
110		60	13			018F7360		
110 - 120		60		14			018F7663	
115		50	11		11	018F7361		018F6711
220 - 230		50	11		12	018F7351		018F6701
230		50		16			018F7658	
208 - 240		60		14			018F7658	
240		50	11		11	018F7352		018F6702
380 - 400		50	14		14	018F7353		018F6703
440		60			15	018F7353		018F6703
	12		13		15	018F7396		018F6756
	24		16		13	018F7397		018F6757

Cable plug, IP65 enclosure

To use with all BB and BY coils



042N0156

042N0156



042N0263

042N0263

To use with BB and BY coils - 24 V AC+DC

To use with BB and BY coils - 230 V AC


042N0265

042N0265

No plug
needed IP67
terminal box
fitted as standard

Capacity diagram for solenoid valve EV250B

Example, water: EV250B 12
at differential pressure of 3 bar:
Approx. 7 m³/h



Spare parts and accessories for EV250B



Spare part kits for EV250B EPDM NC

Application	Seal material	Code number
EV250B 10-12	EPDM	032U5315
EV250B 18-22	EPDM	032U5317



Spare part kits for EV250B FKM NC

Application	Seal material	Code number
EV250B 10-12	FKM	032U5271
EV250B 18-22	FKM	032U5273



Sparepart kits for EV250B NO

Application	Seal material	Code number
EV250B 10-12	EPDM	032U5319
EV250B 10-12	FKM	032U5320
EV250B 18-22	EPDM	032U5321
EV250B 18-22	FKM	032U5322



Permanent magnet


Description	Code number
Fits all EV250B valves	018F0091



Electronic timers for coils for pulse start, only IP65

Type	Description	Control [50/60 Hz]	Power cons. Max [W]	Ambient temp. [°C]	Code number
ET 20 M	External adjustable timing from 1 to 45 minutes with 1 to 15 seconds drain open. With manual override (test button) Electrical connection DIN 43650 A / EN 175 301-803-A	24 - 240	20.0	-10 – 50	042N0185

EV224B servo-operated 2/2-way solenoid valves for high pressure air




-				+
-				+

EV224B is a high pressure indirect servo-operated 2/2-way solenoid valve with working pressure up to 40 bar, medium temperature up to 60 °C and available in NC and NO versions. Built-in pilot filter as standard, adjustable closing time, enclosures up to IP67 (depending on coil) ensure a reliable and satisfactory function.

- For high pressure air applications up to 40 bar
- 2/2-way
- Servo-operated

- DN 15 – DN 25
- Ambient temperature: 80 °C
- NC and NO versions
- Brass valve body
- Built in filter for protection of pilot system
- Based on proven EV220B technology
- Nominal pressure from PN 40
- Wetted parts: brass, stainless steel, copper, tin, PTFE (only NO) and NBR rubber

Dimensions, weight and mounting angle:



Type	L [mm]	B [mm]	B ₁ [mm] Coil type BB/BE	H ₁ [mm]	H [mm]	Weight with BB coil [kg]
EV224B 15	80.0	52.0	46	15.0	99.0	1.04
EV224B 20	90.0	58.0	46	18.0	103.0	1.24
EV224B 25	109.0	70.0	46	22.0	113.0	1.64

EV224B servo-operated valves, NC



Type	Connection	Kv [m³/h]	Seal material	Media Air 60 °C	Body material Brass	Differential pressure [bar]	Code number
EV224B 15	G ½	4	NBR	✓	✓	0.3 – 40	032U8360
EV224B 20	G ¾	8	NBR	✓	✓	0.3 – 40	032U8362
EV224B 25	G 1	11	NBR	✓	✓	0.3 – 40	032U8364

EV224B servo-operated valves, NO



Type	Connection	Kv [m³/h]	Seal material	Media Air 60 °C	Body material Brass	Differential pressure [bar]	Code number
EV224B 15	G ½	4	NBR	✓	✓	0.3 – 40	032U8361
EV224B 20	G ¾	8	NBR	✓	✓	0.3 – 40	032U8363
EV224B 25	G 1	11	NBR	✓	✓	0.3 – 40	032U8365

Coils for EV220B 65 - EV220B 100



Voltage		Frequency [Hz]	Power consumption [W]		BB coil IP00 clip-on	BE coil IP67 clip-on
[V] AC	[V] DC		BB	BE		
24		50	11	12	018F7358	018F6707
48		50		11		018F6709
110		50	15		018F7360	
110		60	13		018F7360	
115		50	11	11	018F7361	018F6711
220 - 230		50	11	12	018F7351	018F6701
240		50	11	11	018F7352	018F6702
380 - 400		50	14	14	018F7353	018F6703
440		60	15	15	018F7353	018F6703
	12	–	13	13	018F7396	018F6756
	24	–	16	16	018F7397	018F6757

Cable plug, IP65 enclosure



To use with all BB coils

042N0156



To use with BB coils - 24 V AC+DC

042N0263

To use with BB coils - 230 V AC

042N0265

No plug needed -
IP67 terminal box
fitted as standard

Spare parts and accessories for EV224B

Electronic timers for coils for pulse start, only IP65



Type	Description	Control [50/60 Hz]	Power cons. Max [W]	Ambient temp. [°C]	Code number
ET 20 M	External adjustable timing from 1 to 45 minutes with 1 to 15 seconds drain open. With manual override (test button) Electrical connection DIN 43650 A / EN 175 301-803-A	24 - 240	20.0	-10 - 50	042N0185

Spare part kits, NC



Application	Seal material	Code number
EV224B 15	NBR	032U6156
EV224B 20	NBR	032U6158
EV224B 25	NBR	032U6160

Spare part kits, NO



Application	Seal material	Code number
EV224B 15	NBR	032U6157
EV224B 20	NBR	032U6159
EV224B 25	NBR	032U6161

Spare part kits for synthetic oil, NC/NO



Application	Seal material	Code number
EV224B 15	FKM	032U8118
EV224B 20	FKM	032U8119

EV225B servo-operated 2/2-way solenoid valves for steam



-			+
-			+


EV225B is a servo-operated 2/2-way solenoid valve for use in steam application.

The design is based on a PTFE diaphragm concept, ensuring high reliable function even in connection with contaminated steam.

Valve body in dezincification resistant brass and valve seats made in stainless steel for ensuring a long life even in connection with aggressive steam media.

- 2/2-way
- Specifically designed for steam applications, 160 °C or 185 °C
- Servo-operated
- DN 6 – DN 25
- Ambient temperature: 40 °C
- G 1/4" – G 1"
- DZR brass valve body
- NC (normally closed)
- ISO 228/1 or UL listed version with NPT for North America (EVSIS/UL)

Dimensions, weight and mounting angle:



Type / orifice size	L [mm]	B [mm]	H [mm]	H ₁ [mm]	H ₂ [mm]	Weight with BQ/BB coil [kg]	Weight with BN coil [kg]
EV225B 6	62	46	98	13	85	0.75	1.03
EV225B 10	62	46	98	13	85	0.72	1.00
EV225B 15	81	56	102	15	87	0.86	1.14
EV225B 20	98	72	110	18	92	1.40	1.68
EV225B 25	106	72	117	21	96	1.70	1.98

EV225B servo operated steam valve with BQ coil and plug, DZR brass, NC



Type	Connection	Kv [m³/h]	BQ coil, 10 W a.c.		24 V 50 Hz	110 V 60 Hz	230 V 50 Hz	220 V 60 Hz	Code number
			Temp. max [°C]	Diff. pressure [bar]					
EV225B 10	G ½	2.2	185	0.2 – 10	✓				032U380416
EV225B 15	G ½	3.0	185	0.2 – 10	✓				032U380516
EV225B 20	G ¾	5.0	185	0.2 – 10	✓				032U380616
EV225B 25	G 1	6.0	185	0.2 – 10	✓				032U380716
EV225B 10	G ½	2.2	185	0.2 – 10		✓			032U380420
EV225B 15	G ½	3.0	185	0.2 – 10		✓			032U380520
EV225B 20	G ¾	5.0	185	0.2 – 10		✓			032U380620
EV225B 25	G 1	6.0	185	0.2 – 10		✓			032U380720
EV225B 10	G ½	2.2	185	0.2 – 10			✓		032U380431
EV225B 15	G ½	3.0	185	0.2 – 10			✓		032U380531
EV225B 20	G ¾	5.0	185	0.2 – 10			✓		032U380631
EV225B 25	G 1	6.0	185	0.2 – 10			✓		032U380731
EV225B 10	G ½	2.2	185	0.2 – 10				✓	032U380429
EV225B 15	G ½	3.0	185	0.2 – 10				✓	032U380529
EV225B 20	G ¾	5.0	185	0.2 – 10				✓	032U380629
EV225B 25	G 1	6.0	185	0.2 – 10				✓	032U380729



EV225B servo operated steam valve with BN coil and plug, DZR brass, NC

Type	Connection	Kv [m³/h]	BN coil, 20 W		24 V d.c.	Code number
			Temp. max [°C]	Diff. pressure [bar]		
EV225B 10	G ½	2.2	160	0.2 – 5	✓	032U380402
EV225B 15	G ½	3.0	160	0.2 – 5	✓	032U380502
EV225B 20	G ¾	5.0	160	0.2 – 5	✓	032U380602
EV225B 25	G 1	6.0	160	0.2 – 5	✓	032U380702

EV225B servo-operated steam valve, DZR brass, NC, PTFE seal material



Type	Connection	Kv [m³/h]	BQ coil, 10 W a.c.		BN coil, 20 W d.c.		BB coil, 10 W a.c.		BB coil, 18 W d.c.		Code number
			Temp. max [°C]	Diff. pressure [bar]	Temp. max [°C]	Diff. pressure [bar]	Temp. max [°C]	Diff. pressure [bar]	Temp. max [°C]	Diff. pressure [bar]	
EV225B 6	G ¼	0.9	185	0.2 – 10	160	0.2 – 5	160	0.2 – 5	140	0.2 – 3.6	032U3802
EV225B 10	G ¾	2.2	185	0.2 – 10	160	0.2 – 5	160	0.2 – 5	140	0.2 – 3.6	032U3803
EV225B 10	G ½	2.2	185	0.2 – 10	160	0.2 – 5	160	0.2 – 5	140	0.2 – 3.6	032U3804
EV225B 15	G ½	3.0	185	0.2 – 10	160	0.2 – 5	160	0.2 – 5	140	0.2 – 3.6	032U3805
EV225B 20	G ¾	5.0	185	0.2 – 10	160	0.2 – 5	160	0.2 – 5	140	0.2 – 3.6	032U3806
EV225B 25	G 1	6.0	185	0.2 – 10	160	0.2 – 5	160	0.2 – 5	140	0.2 – 3.6	032U3807

Coils for EV225B



Voltage		Frequency [Hz]	Power consumption [W]		BQ coil, AC 10 bar, 185 °C IP65 clip-on	BN coil, DC 5 bar, 160 °C IP65 clip-on
[V] AC	[V] DC		BQ	BN		
24		50	10		018F4517	
24		60	9.0		018F4517	
110		50	13.5		018F4519	
230		50	10		018F4511	
208 – 240		60	9.5		018F4511	
240		50				
	24	–		20		018F6968

Cable plug, IP65 enclosure



To use with all BQ and BN coils					042N0156	042N0156
---------------------------------	--	--	--	--	-----------------	-----------------


Spare part kits




Application	Seal material	Code number
EV225B 6 - EV225B 10	PTFE	032U3171
EV225B 15	PTFE	032U3172
EV225B 20 - EV225B 25	PTFE	032U3173

Capacity diagram for EV225B

Example, steam:
Capacity for EV225 10 BD; inlet pressure (p_1) of 6 bar absolute; differential pressure at 1 bar:
Approx. 100 kg/h / 80 kW



EV260B servo-operated 2-way proportional solenoid valves



-			+
-			+
-			+


EV260B is a proportional (modulating) servo-operated 2-way solenoid valve program with connections from 1/4" to 3/4". Through stepless regulation of the coil current, the armature can be placed in any position in the armature tube, thus setting the valve to any position between completely closed and completely open.

The valve is fully open when the coil current has reached its maximum value.

- Proportional (modulating)
- For stepless flow regulation
- 2-way
- Servo-operated

- DN 6 - DN 20
- Ambient temperature: 50 °C
- Short reaction time
- Linear characteristic throughout the regulation range
- Closes on power failure (fail-safe function)
- IP67 coil enclosure
- 24 V d.c. supply voltage
- This product is only applicable for liquids
- Nominal pressure from PN 10
- Wetted parts: brass, stainless steel, PTFE, CR, NBR or FKM rubber

Dimensions, weight and mounting angle:



Type / orifice size	L [mm]	L ₁ [mm]	L ₂ [mm]	H ₁ [mm]	H ₂ [mm]	B [mm]	Weight without signal converter [kg]	Weight with signal converter [kg]
EV260B 6	62	112 ¹⁾	30	13	71	68	1.02	1.22
EV260B 10	62	112 ¹⁾	30	13	71	68	1.02	1.22
EV260B 15	81	112 ¹⁾	30	15	74	68	1.17	1.37
EV260B 20	98	112 ¹⁾	30	18	79	68	1.71	1.91


1) With the BM and the BL coil the measurement is 128 mm

EV260B proportional valve, brass, NC



Type	Connection	Kv [m³/h]	Seal material	Medium water [°C]	Differential pressure [bar]	Code number
EV260B 6	G ¼	0.8	PTFE	-10 – 80	0.5 – 10	032U8052
EV260B 6	G ¾	0.8	PTFE	-10 – 80	0.5 – 10	032U8053
EV260B 10	G ¾	1.3	PTFE	-10 – 80	0.5 – 10	032U8054
EV260B 10	G ½	1.3	PTFE	-10 – 80	0.5 – 10	032U8055
EV260B 15	G ½	2.1	PTFE	-10 – 80	0.5 – 10	032U8056
EV260B 20	G ¾	5	PTFE	-10 – 80	0.5 – 10	032U8057

Coils for EV260B




Voltage [d.c.]	BK coil 300-600 mA	BM coil 0-10 V	BL coil 4-20 mA
24	018Z6987	018Z0290	018Z0291
	IP67 terminal box fitted as standard	IP67 terminal box fitted as standard	IP67 terminal box fitted as standard

Spare part kits for EV260B




Application	Seal material	Code number
EV260B 6	PTFE	032U8039
EV260B 10	PTFE	032U8040
EV260B 15	PTFE	032U8041
EV260B 20	PTFE	032U8042


Signal flow characteristics for EV260B



Coil type BK. Without signal converter
The basic version consists of a valve with a coil for pulsating direct current. The supply voltage of 24V d.c. can be established with full-wave rectified alternating current. The valve begins to open at a coil current of approx. 300 mA and is fully open at a coil current of approx. 600 mA. The relation between coil current and flow between the two outer points is directly proportional.




Coil type BM. With signal converter and 0-10 V pilot signal.
The relation between pilot signal and flow is directly proportional throughout the regulation range.




Coil type BL. With signal converter and 4-20 mA pilot signal.
The relation between pilot signal and flow is directly proportional throughout the regulation range.

Capacity diagram for EV260B

For water at fully opened valve
Example: Differential pressure of 3 bar:
EV260B 6 B: Appr. 1.4 m³/h
EV260B 10 B: Appr. 2.2 m³/h
EV260B 15 B: Appr. 3.6 m³/h
EV260B 20 B: Appr. 8.7 m³/h



The 'fit and forget' AVTA thermostatic valve



A self-acting thermostatic valve, the AVTA controls the temperature in cooling water applications. Often referred to as the 'fit and forget' valve due to its proven reliability, the AVTA is easy to install and functions without electrical power.

Self-acting - no electricity required

The AVTA does not require electricity to function because a temperature-dependent pressurised charge or vapour charge provides accurate flow control based on the sensor temperature. And because it needs no power supply, it keeps working as long as the coolant is pressurised.

Exact temperature control

Designed for low hysteresis, the hermetically-sealed thermostatic element consists of a cylindrical sensor connected to a bellows with a capillary tube.

Dirt resistant

The force-balanced design prevents particles from adhering to the large valve opening. But if dirt does become lodged in the valve, the sensor simply detects that more cooling water is needed and the valve opens wider to allow more water to pass and dislodge the particles.

Insensitive to pressure

Pressure equalising diaphragms ensure reliable function across the entire pressure range – from zero to ten bar pressure – by balancing the forces on the bellows and setting sections. And with reinforced EPDM diaphragms, the valve can take up to 25 bar pressure.


AVTA thermostatic valves for industrial cooling applications



AVTA thermostatic valves are widely used for temperature control in many different sorts of equipment and installations where cooling is required.

- Self-acting thermostatic valves for accurate cooling flow control based on sensor temperature
- Capillary sensor with adsorption charge, mass charge or universal charge, depending on application
- Open on rising temperature
- Brass or stainless steel valve body
- For extremely aggressive media, also available in titanium (please contact Danfoss)

Dimensions, weight and mounting angle:



All dimensions in millimetres

Brass Type	H ₁ [mm]	H ₂ [mm]	L [mm]	L ₁ [mm]	a	b [mm]	Weight [kg]
AVTA 10	240	133	72	14	G 3/8	27	1.45
AVTA 15	240	133	72	14	G 1/2	27	1.45
AVTA 20	240	133	90	16	G 3/4	32	1.50
AVTA 25	240	138	95	19	G 1	41	1.65

AVTA thermostatic valve

Adsorption charge. Brass valve body

Type	Connection	Temperature setting range [°C]	Max sensor temperature [°C]	Kv [m³/h]	Sensor dimensions Ø x L [mm]	Capillary tube, length [m]	Code number
AVTA 10	G 3/8	10 – 80	130	1.4	9.5 x 150	2.3	003N1144
AVTA 15	G 1/2	10 – 80	130	1.9	9.5 x 150	2.3	003N0107
AVTA 20	G 3/4	10 – 80	130	3.4	9.5 x 150	2.3	003N0108
AVTA 25	G 1	10 – 80	130	5.5	9.5 x 150	2.3	003N0109




Universal charge. Brass valve body

Type	Connection	Temperature setting range [°C]	Max sensor temperature [°C]	Kv [m³/h]	Sensor dimensions Ø x L [mm]	Capillary tube, length [m]	Code number
AVTA 10	G 3/8	0 – 30	57	1.4	18 x 210	2	003N1132
AVTA 15	G 1/2	0 – 30	57	1.9	18 x 210	2	003N2132
AVTA 20	G 3/4	0 – 30	57	3.4	18 x 210	2	003N3132
AVTA 25	G 1	0 – 30	57	5.5	18 x 210	2	003N4132
AVTA 10	G 3/8	25 – 65	90	1.4	18 x 210	2	003N1162
AVTA 15	G 1/2	25 – 65	90	1.9	18 x 210	2	003N2162
AVTA 20	G 3/4	25 – 65	90	3.4	18 x 210	2	003N3162
AVTA 25	G 1	25 – 65	90	5.5	18 x 210	2	003N4162
AVTA 10	G 3/8	50 – 90	125	1.4	18 x 210	2	003N1182
AVTA 15	G 1/2	50 – 90	125	1.9	18 x 210	2	003N2182
AVTA 20	G 3/4	50 – 90	125	3.4	18 x 210	2	003N3182
AVTA 25	G 1	50 – 90	125	5.5	18 x 210	2	003N4182



Mass charge. Brass valve body

Type	Connection	Temperature setting range [°C]	Max sensor temperature [°C]	Kv [m³/h]	Sensor dimensions Ø x L [mm]	Capillary tube, length [m]	Code number
AVTA 15	G 1/2	0 – 30	57	1.9	9.5 x 180	2	003N0042
AVTA 20	G 3/4	0 – 30	57	3.4	9.5 x 180	2	003N0043
AVTA 15	G 1/2	25 – 65	90	1.9	9.5 x 180	2	003N0045
AVTA 20	G 3/4	25 – 65	90	3.4	9.5 x 180	2	003N0046
AVTA 25	G 1	25 – 65	90	5.5	9.5 x 180	2	003N0047



Adsorption charge. Stainless steel valve body

Type	Connection	Temperature setting range [°C]	Max sensor temperature [°C]	Kv [m³/h]	Sensor dimensions Ø x L [mm]	Capillary tube, length [m]	Code number
AVTA 15	G 1/2	10 – 80	130	1.9	9.5 x 150	2.3	003N2150
AVTA 20	G 3/4	10 – 80	130	3.4	9.5 x 150	2.3	003N3150
AVTA 25	G 1	10 – 80	130	5.5	9.5 x 150	2.3	003N4150



For all types: Media temperature range: -25 – 130 °C.

For higher Kv values (larger capacities) and other requirements please contact Danfoss.



Ask Danfoss or your local wholesaler if larger size than G1 is needed

Charges

Adsorption charge

The charge consists of active carbon and CO_2 which is adsorbed on falling sensor temperature and thereby produce pressure changes in the element.



The sensor can be installed in any position as far as orientation and temperature are concerned.



Universal charge

The charge is a mix of liquid and gas where the liquid surface (sensing point) is always inside the sensor.



The sensor can be installed colder or warmer than the valve, and oriented as shown.



Mass charge

The charge is a mix of liquid and gas.

Due to the volumetric conditions the sensor must be installed warmer than the valve, since the liquid surface (sensing point) must be in the sensor. Orientation as shown.



Spare parts and accessories for AVTA

Service sensor elements



Sensor size Ø x L [mm]	Cap. tube length [m]	Charge			Temperature range [°C]	Code number
		Adsorption	Universal	Mass		
18 x 210	2		✓		0 – 30	003N0075
18 x 210	2		✓		25 – 65	003N0078
18 x 210	2		✓		50 – 90	003N0062
9.5 x 180	2			✓	25 – 65	003N0091
9.5 x 150	2.3	✓			10 – 80	003N0278

Sensor pockets



Sensor size Ø x L [mm]	Connection standard	Connection size [inch]	Sensor pocket insertion [mm]	Pocket material		Code number
				Brass	Stainless steel	
9.5x180 / 9.5x150	ISO 228-1	½	182	✓		017-436766
9.5x180 / 9.5x150	ISO 7-1	½	182		✓	003N0196
18x210	ISO 228-1	¾	220	✓		003N0050
18x210	ISO 7-1	¾	220		✓	003N0192

Capillary tube glands




Sensor size Ø x L [mm]	Connection standard	Connection size [inch]	Material	Charge		Code number
				Adsorption / Mass	Universal	
9.5x180 / 9.5x150	ISO 228-1	G ½	Brass	✓		017-422066
18x210	ISO 228-1	G ¾	Brass		✓	003N0155

Bracket



Type	Material	Code number
Bracket	Zinc plated steel	003N0388


AVTA thermostatic valve - sizing



Heating or cooling with water.

Example: Necessary cooling output 10 kW with $\Delta t = 10^\circ\text{C}$.


Required flow 0.85 m^3/h .



Relation between water quantity and pressure drop across valve.


Example: Flow 0.85 m^3/h with a pressure drop of 1.5 bar.

The K_v value becomes 0.7 m^3/h .




Nomogram showing the valve K_v range.
 K_v values are always given for water flow in m^3/h with a pressure drop Δp of 1 bar.
 The valve should be selected so that the necessary K_v value lies in the middle of the regulation range.
 Example: AVTA 10 and 15 are the most suitable for a K_v value of 0.7.

Valve flow quantity in fully open position, as a function of pressure drop Δp .
 With fully open valve the differential pressure should be around 50% of the total pressure drop across the cooling system.



AV210 externally operated valve for high capacity applications

The AV210 can operate at very high medium temperatures and viscosities, and can withstand dirt particles in the medium.



Wide temperature range

Known as the 'trouble-shooter', the AV210 is made from FKM, PTFE, and gun metal (RG5/bronze) or stainless steel (AISI 316), so it can withstand temperatures as low as -30 °C and as high as 180 °C.

Dirt resistant

Mounted on a spindle, the resilient internal valve seat is made of AISI 316, a high grade corrosion-resistant stainless steel. And the PTFE valve plate gives excellent resistance to dirt particles in the medium.

Insensitive to media pressure and viscosity

Made for air, neutral gases and fresh water applications, the valve is designed to operate with media viscosities up to 400cSt and 10 bar pressure – and it is not affected by low flow rates or pressure loss across the opening.

Tight fit even at high differential pressures

As the valve seat is pressurised at the valve opening, the standard AV210 valve closes against the flow. When closed the spindle is not exposed to the medium, significantly reducing water hammer. The AV210 can also close with the flow if required.

High capacity

For optimum capacity, the special control head design and high closing spring allows the valve plate to lift higher than the usual 25 percent of the valve diameter.

Modular design

Available in five sizes, it is easy to find an AV210 to suit your size and pressure range requirements.

Accessories

For even higher performance and versatility, the AV210 can be fitted with the following accessories:

- Manual override
- Flow limiters
- Valve position indicators


AV210 externally operated valves



AV210 is an externally operated valve for use in demanding industrial applications. The valve can operate at very high medium temperatures and viscosities, and is insensitive to dirt particles in the medium; thus, it is often called a “trouble-shooter” valve. The valve is available in gun metal (RG5/bronze) and stainless steel (AISI316).

- High capacity basic program
- 2/2-way
- Angle-seated piston
- NC version: Both closing against and withflow direction
- NO version: Closing against the flow direction
- Bronze or stainless steel valve body
- Danfoss recommends a EV310A as pilot solenoid valve

Dimensions, weight and mounting angle:



Stainless Steel / Bronze RG5

Type / orifice size	Connec- tion ISO 228/1	Diameter control head [mm]	A [mm]	B [mm]	C [mm]	D [mm]	ØE [mm]	F [mm]	H [mm]	ch.L [mm]	Weight [kg]
15	G 3/8	40	190/144	156/121	169/134	44/35	70/61	85/65	12/12	25/27	1.1
15	G 3/8	50	-/163	-/140	-/153	-/44	-/70	-/65	-/12	-/27	1.1
15	G 1/2	40	-/144	-/121	-/134	-/35	-/61	-/65	-/13	-/27	1
15	G 1/2	50	190/163	156/140	169/153	44/44	70/70	85/65	15/13	25/27	1
20	G 3/4	50	195/173	160/147	176/163	44/44	70/70	95/75	16.3/14.3	31/27.5	1.2
20	G 3/4	63	213/191	178/165	194.4/181	50.5/50.5	84.4/84.4	95/75	16.3/14.3	31/27.5	1.2
25	G 1	63	219/206	182/176	202/196	50.5/50.5	84.4/84.4	105/90	19.5/17.5	38/41	1.6
25	G 1	90	259/246	222/216	242/236	66.2/66.2	116.4/116.4	105/90	19.5/17.5	38/41	1.7
32	G 1 1/4	90	266/255	226/220	249/245	66.2/66.2	116.4/116.4	120/110	19/19	47/50	3
40	G 1 1/2	90	271/270	230/235	258/264	66.2/66.2	116.4/116.4	130/120	18/18	54/58	3.4
40	G 1 1/2	110	307/306	266/271	294/300	77.4/77.4	140.6/140.6	130/120	18/18	54/58	4
50	G 2	110	321/316	276/276	310/311	77.4/77.4	140.6/140.6	150/150	20/20	66/70	5.3

AV210 externally operated valves, PTFE seal material, NC

Closing against flow recommended



Type	Connection	Kv [m³/h]	Body material		Differential pressure [bar]	Control pressure [bar]	Control head diameter Ø [mm]	Code number
			Bronze RG5	Stainless steel				
AV210A 15	G 3/8	4.5	✓		0 – 16	4.2 – 10	40	042N4400
AV210B 15	G 3/8	4.9	✓		0 – 16	4 – 10	50	042N4401
AV210B 15	G 3/8	4.9		✓	0 – 16	4 – 10	50	042N4450
AV210A 15	G 1/2	5.3	✓		0 – 16	4.2 – 10	40	042N4402
AV210B 15	G 1/2	5.7	✓		0 – 16	4 – 10	50	042N4403
AV210B 15	G 1/2	5.7		✓	0 – 16	4 – 10	50	042N4451
AV210B 20	G 3/4	10	✓		0 – 10	4 – 10	50	042N4404
AV210B 20	G 3/4	10		✓	0 – 10	4 – 10	50	042N4452
AV210C 20	G 3/4	10		✓	0 – 16	4 – 10	63	042N4453
AV210C 25	G 1	20	✓		0 – 11	4 – 10	63	042N4406
AV210D 25	G 1	20	✓		0 – 16	4 – 8	90	042N4407
AV210C 25	G 1	20		✓	0 – 11	4 – 10	63	042N4454
AV210D 25	G 1	20		✓	0 – 16	4 – 8	90	042N4455
AV210D 32	G 1 1/4	29	✓		0 – 14	4 – 8	90	042N4408
AV210D 32	G 1 1/4	29		✓	0 – 14	4 – 8	90	042N4456
AV210D 40	G 1 1/2	46	✓		0 – 11	4 – 8	90	042N4409
AV210D 40	G 1 1/2	46		✓	0 – 11	4 – 8	90	042N4457
AV210E 50	G 2	67	✓		0 – 10	4 – 8	110	042N4411
AV210E 50	G 2	67		✓	0 – 10	4 – 8	110	042N4459

AV210 externally operated valves, PTFE seal material, NO

Closing against flow recommended



Type	Connection	Kv [m³/h]	Body material		Differential pressure [bar]	Control pressure [bar]	Control head diameter Ø [mm]	Code number
			Bronze RG5	Stainless steel				
AV210B 15	G 3/8	4.9	✓		0 – 16	5 – 10	50	042N4430
AV210B 15	G 3/8	4.9		✓	0 – 16	5 – 10	50	042N4480
AV210B 15	G 1/2	5.7	✓		0 – 16	5 – 10	50	042N4431
AV210B 15	G 1/2	5.7		✓	0 – 16	5 – 10	50	042N4481
AV210B 20	G 3/4	10	✓		0 – 16	5 – 10	50	042N4432
AV210B 20	G 3/4	10		✓	0 – 16	5 – 10	50	042N4482
AV210C 25	G 1	20	✓		0 – 16	5 – 10	63	042N4433
AV210C 25	G 1	20		✓	0 – 16	5 – 10	63	042N4483
AV210C 32	G 1 1/4	29		✓	0 – 16	6 – 10	63	042N4484
AV210D 40	G 1 1/2	46	✓		0 – 16	5 – 10	90	042N4435
AV210D 40	G 1 1/2	46		✓	0 – 16	5 – 10	90	042N4485
AV210E 50	G 2	67	✓		0 – 16	5 – 10	110	042N4436
AV210E 50	G 2	67		✓	0 – 16	5 – 10	110	042N4486

* in case control pressure is reduced below 5 or 6 bar max. differential pressure will be reduced accordingly.

AV210 externally operated valves - accessories & spare parts


Position indicators. Voltage: Max 5A 250 V a.c. / 1A 250 V d.c.



Enclosure	Control head diameter Ø [mm]	Code number
IP65	50	042N4820
IP65	63	042N4821
IP65	90	042N4822
IP65	110	042N4823

Capacity diagram, water

Example for water:
Capacity for AV 210 40 at
differential pressure of 3 bar:
Approx 80 m³/h





Safety application - tilt control - mobile hydraulic

An MBS 3050 pressure transmitter controls the pressure circuit. Its integrated pulse-snubber ensures reliable operation despite cavitation, liquid hammer or pressure peaks





Pressure transmitters

Industries

Serving a broad, global market within diverse and demanding industries, Industrial Automation is your one-stop partner for industrial control components. Through Danfoss Industrial Automation you gain access to the entire Danfoss pool of technology for a wide range of industries.

HYDRAULICS

In a world depending on infrastructure, mobile hydraulic equipment is key to making modern living possible for an ever growing population. Whether used in construction, agriculture or for material handling, mobile hydraulics equipment offers efficiency, economy, safety and environmental advantages.

MARINE

From the handling of sewage water to the treatment of exhaust gasses: A modern ship contains most of the applications found on shore, albeit in a limited space. Danfoss Industrial Automation is a global leader in supplying pressure transmitters to equipment placed in and around the engine room: 2 and 4 stroke diesel and gas engines, propulsion systems, fuel treatment, oil separators among others.

AIR COMPRESSORS

Spanning from very small units for medical use to very large industrial compressors operating in the kilowatt power band, the air compressor industry covers a huge range of equipment. Equally varied are the fundamental compressor technologies used.

PUMPS

The global need for clean water is enormous and on the rise, calling for a dedicated common effort to control the water cycle. Danfoss is well prepared to contribute to such endeavors. To us, the pump is the key to controlling the water cycle – from intake to effluent. Consequently, we have developed a range of sensors and switches for pumps, tailored for the most common applications in the water industry.

Pressure transmitters

in this catalogue



Type	Standard	MBS 3000	MBS 3200	MBS 3100	MBS1900
------	----------	----------	----------	----------	---------

Pulse-snubber	MBS 3050	MBS 3250	MBS 3150	
---------------	----------	----------	----------	--

Transportation				
----------------	---	---	---	--



Heating and sanitation	 	 		
------------------------	---	---	--	--



Machine and equipment	  	 		 
-----------------------	---	---	---	---



Energy				
--------	---	---	--	--





Sensor technology	Piezo resistive	Piezo resistive	Piezo resistive	Piezo resistive
-------------------	-----------------	-----------------	-----------------	-----------------

Accuracy FS (typ)	± 0.5%	± 0.5%	± 0.5%	± 1%
-------------------	--------	--------	--------	------

Max. measuring range	600 bar 9,000 psi	600 bar 9,000 psi	600 bar 9,000 psi	25 bar 362 psi
----------------------	----------------------	----------------------	----------------------	-------------------

Output signal	4 – 20 mA and absolute voltage	4 – 20 mA and absolute voltage	4 – 20 mA	4 – 20 mA Ratiometric
---------------	--------------------------------------	--------------------------------------	-----------	--------------------------

Medium temperature	-40 – 85 °C -40 – 185 °F 	-40 – 125 °C -40 – 257 °F 	-40 – 85 °C -40 – 185 °F 	0 – 80 °C 32 – 176 °F 
--------------------	--	---	--	---



Enclosure IP	IP65 IP67	IP65 IP67	IP65 IP67	IP65
--------------	--------------	--------------	--------------	------

Wetted parts material	AISI 316L	AISI 316L	AISI 316L	AISI 304/AISI 316
-----------------------	-----------	-----------	-----------	-------------------

Housing material	AISI 316L, PA 6.6	AISI 316L, PA 6.6	AISI 316L, PA 6.6	AISI 316L
------------------	----------------------	----------------------	----------------------	-----------

Zero point and span adjustment				
--------------------------------	--	--	--	--

Marine approvals			•	
------------------	--	--	---	--

ATEX approvals	Zone 2	Zone 2	Zone 2	UL
----------------	--------	--------	--------	----

UL HazLoc	Class 1, Div. 2	Class 1, Div. 2	Class 1, Div. 2	
-----------	--------------------	--------------------	--------------------	--



Railways and marine



Industrial hydraulics, air compressors, water pumps and industrial engines



Electric power and wind turbines




Boiler and boiler room equipment, sterilisers and autoclaves, mobile hydraulic

							
MBS1200	MBS1300	MBS 5100	MBS 4510	MBS 9200	MBS 9300	EMP 2	
MBS1250	MBS1350	MBS 5150					
							
 							
							
							
Thin film	Thin film	Piezo resistive	Piezo resistive	Piezo resistive	Piezo resistive	Piezo resistive	
± 0.5%	± 0.5%	± 0.3%	± 0.5%	± 0.5% – ± 2% (depending on pressure range)	± 0.5% – ± 2% (depending on pressure range)	± 0.3%	
2200 bar 32000 psi	2200 bar 32000 psi	600 bar 9,000 psi	25 bar 360 psi	250 mbar 3.62 psi	250 mbar 3.62 psi	400 bar 6,000 psi	
4 – 20 mA Voltage Ratiometric		4 – 20 mA	4 – 20 mA	4 – 20 mA or Ratiometric	4 – 20 mA	4 – 20 mA	
-40 – 125 °C -40 – 257 °F 	-40 – 125 °C -40 – 257 °F 	-40 – 85 °C -40 – 185 °F 	-10 – 85 °C 14 – 185 °F 	-40 – 85 °C -40 – 185 °F 	-40 – 85 °C -40 – 185 °F 	-40 – 100 °C -40 – 212 °F 	
IP67	IP67	IP65 IP67	IP65 IP67	IP65	IP65	IP67	
17-4PH	17-4PH	AISI 316L	AISI 316L	AISI 316L	AISI 316L	AISI316L	
AISI 304 or plastic	AISI 304 or plastic	AISI 316L, PA 6.6	AISI 316L, PA 6.6	AISI 316L, PA 6.6	AISI 316L, PA 6.6	Al	
		•	•			•	
		•			•	•	
		Zone 2	Zone 2	Zone 2	Zone 2	Zone 2	
		Class 1, Div. 2	Class 1, Div. 2				

Sensor packages designed for customer needs


The extent of automation in both mobile and stationary applications has over the past decade increased dramatically and the demand for sensors and controls has increased accordingly. Danfoss has followed this development closely, and as a result we now have a programme of products perfectly aligned to our customer’s needs.

Box transmitter



Often used in applications requiring robust performance and enclosures. The Danfoss Box solution has been on the market for more than 30 years. It is still widely used within the marine sector.

Block transmitter



Used in applications where space has become an issue. The Danfoss “Block” design is more compact compared to the traditional “Box” design. Where a combination of sensor and valve is needed, Danfoss also offers the “Block” valve - MBV.

Cartridge transmitter



The cartridge transmitter can be mounted directly to the customer’s system at the point of measurement, even where there is very little space. This eliminates the need for extra piping and joints.


Cartridge transmitter with flush diaphragm



Often used in applications where measurement have to be made on highly viscous or slurry media. The front mounted diaphragm prevents blocking of the pressure port.


Pulse-snubber

In applications where there is a risk of liquid hammering and cavitation it is recommended to select a transmitter with an integral pulse-snubber. The Danfoss pressure transmitters with a pulse-snubber are indicated with a “5” in the third type digit (example: MBS 1750).



Temperature influence

Media temperature (t_m) [°C]	Heat isolator (L) [cm]	Transmitter temperature (t_t) [°C]
120	2	85
	5	75
	10	70
100	2	75
	5	65
	10	60



MBS transmitter made from expert know-how

A typical pressure transmitter has three general functional elements:

- The electronics
- The sensing element
- The packaging

It is the solution of each of these elements and the combination that determines the performance of the products. All Danfoss pressure transmitters are certified according to ISO 9001 and ISO 14001.

A variety of electrical connections available

1 Electronics

Danfoss MBS pressure transmitters are available with analogue electronic solutions and offer unique specifications in terms of:

- Accuracy
- Temperature range coverage
- EMI/RFI protection


2 Sensing element

- Piezoresistive semi-conductor technology covering pressure ranges from 0 – 600 bar. This technology is available in absolute or gauge versions.

3 Packaging

The transmitter design offers long-life stability through:

- High shock and vibration stability
- High enclosure grade IP67
- Pulse restriction solution which prevents liquid hammering and cavitation. (pulse-snubber) **A**
- Wetted parts that are all made from stainless steel (AISI 316L) **B**




A variety of process connections available


MBS 3000 compact pressure transmitter



Design



Temperature




The compact pressure transmitter MBS 3000 is designed for use in almost all industrial applications, and offers a reliable pressure measurement, even under harsh environmental conditions. The flexible pressure transmitter programme covers a 4 – 20 mA output signal, absolute and gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 600 bar and a wide range of pressure- and electrical connections.

Excellent vibration stability, robust construction, and a high degree of EMC/EMI protection equip the pressure transmitter to meet the most stringent industrial requirements.

- 4 – 20 mA output signal
- Operating temperature -40 – 85 °C
- Measuring range 0 – 600 bar
- Standard pressure connection G 1/4A ISO 228/1
- For use in severe industrial environments such as pumps, compressors, pneumatics and water treatment
- Wetted parts: stainless steel (AISI 316)

Dimensions:

Weight: 0.17 kg



All dimensions in millimetres

Approvals: CE, UL, UL Hazloc, Ex-N, Gost

MBS 3000 compact pressure transmitter

Accuracy: $\pm 0.5\%$ FS (typ.)

Media temperature: $-40 - 85\text{ }^{\circ}\text{C}$

Output signal: $4 - 20\text{ mA}$

Electrical connections: EN175301-803A, Pg 9

Range: Flexible, different electrical and pressure connections available



Measuring range P_e [bar] ¹⁾	Pressure connection			Output signal		Code number
	G ¼ EN 837	G ¼ A	M20 x 1.5	4 – 20mA	0 – 10V	
0 – 1	✓			✓		060G1113
0 – 1.6	✓			✓		060G1429
0 – 2.5	✓			✓		060G1122
0 – 4	✓			✓		060G1123
0 – 4		✓			✓	060G3812
0 – 4			✓		✓	060G3828
0 – 6	✓			✓		060G1124
0 – 6		✓			✓	060G3902
0 – 6			✓		✓	060G3829
0 – 10	✓			✓		060G1125
0 – 10		✓			✓	060G1650
0 – 10			✓		✓	060G3830
0 – 16	✓			✓		060G1133
0 – 16		✓			✓	060G3813
0 – 16			✓		✓	060G3831
0 – 25	✓			✓		060G1430
0 – 25		✓			✓	060G3814
0 – 25			✓		✓	060G3832
0 – 40	✓			✓		060G1105
0 – 40		✓			✓	060G3815
0 – 40			✓		✓	060G3833
0 – 60	✓			✓		060G1106
0 – 100	✓			✓		060G1107
0 – 160	✓			✓		060G1112
0 – 250	✓			✓		060G1111
0 – 400	✓			✓		060G1109
0 – 600	✓			✓		060G1110

¹⁾ Gauge / relative

Spare parts and accessories for MBS 3000

Plug



Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
EN 175301-803-A, Pg 11 plug	060G0007
EN 175301-803-A, plug with 5 m cable	060G1034

Plug in display




Type	Description	Code number
MBD 1000	Microprocessor controlled plug-in display	060G2850


MBS 3050 compact pressure transmitters with pulse snubber



Design



Temperature



The compact heavy duty pressure transmitter MBS 3050 is designed for use in hydraulic applications with severe medium influences like cavitation, liquid hammer or pressure peaks and offers a reliable pressure measurement, even under harsh environmental conditions.


The flexible pressure transmitter programme covers a 4 – 20 mA output signal, absolute and gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 600 bar and a wide range of pressure- and electrical connections.

Excellent vibration stability, robust construction, and a high

degree of EMC/EMI protection equip the pressure transmitter to meet the most stringent industrial requirements.

- 4 – 20 mA output signal
- Operating temperature -40 – 85 °C
- Measuring range 0 – 600 bar
- Standard pressure connection DIN 3852 - G 1/4A
- With integrated pulse-snubber to protect against cavitation, liquid hammer or pressure peaks
- Especially suited for hydraulic applications
- Wetted parts: stainless steel (AISI 316)

Dimensions and weight:



Weight: 0.17 kg

All dimensions in millimetres

Approvals: CE, UL, UL Hazloc, Ex-N, Gost

MBS 3050 compact pressure transmitters with pulse-snubber

Accuracy: + / - 0.5 % FS (typ.)

Media temperature: -40 – 85 °C

Electrical connections: EN175301-803A, Pg 9

Range: Flexible, different electrical and pressure connections available



Pressure range P _e [bar] ¹⁾	Output signal		Pressure connection:		Code number
	mA	V	G ¼ DIN3852-E	G ¼ DIN3852-G Special	
0 – 250	4 – 20		✓		060G3582
0 – 400	4 – 20		✓		060G3583
0 – 250		1 – 5	✓		060G3584
0 – 400		1 – 5	✓		060G3585
0 – 250		0 – 10	✓		060G3557
0 – 400		0 – 10	✓		060G3586
0 – 60	4 – 20			✓	060G1411
0 – 100	4 – 20			✓	060G1151
0 – 250	4 – 20			✓	060G1153
0 – 400	4 – 20			✓	060G1154

¹⁾Gauge/relative

Spare parts and accessories for MBS 3050

Plug in display



Type	Description	Code number
MBD 1000	Microprocessor controlled plug-in display	060G2850

Plug




Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
En 175301-803-A, Pg 11 plug	060G0007
En 175301-803-A, plug with 5 m cable	060G1034


MBS 3200 compact pressure transmitters



Design



Temperature



The compact high temperature pressure transmitter MBS 3200 is designed for use in almost all industrial applications, and offers a reliable pressure measurement, even under harsh environmental conditions.


The flexible pressure transmitter programme covers 4 – 20 mA, 0 – 5 V, 1 – 5 V, 1 – 6 V and 0 – 10 V output signal, absolute and gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 600 bar and a wide range of pressure and electrical connections. Excellent vibration stability, robust construction, a high degree of EMC/EMI protection and a high operating temperature, equip

the pressure transmitter to meet the most stringent industrial requirements.

- 4 – 20 mA, 0 – 5 V, 1 – 5 V, 1 – 6 V and 0 – 10 V output signal
- Operating temperature -40 – 125 °C
- Measuring range 0 – 600 bar
- A wide range of pressure and electrical connections are available
- For use in severe industrial environments
- Wetted parts: stainless steel (AISI 316)

Dimensions and weight:

Weight: 0.17 kg



All dimensions in millimetres

Approvals: CE, UL, UL Hazloc, Ex-N, Gost

MBS 3200 compact pressure transmitters

Accuracy: +/- 0.5% FS (typ.)
Media temperature: -40 – 125 °C
Output signal: 4 – 20 mA
Electrical connections: EN175301-803A, Pg 9
Range: Flexible - different electrical and pressure connections available



Pressure range P _e [bar] ¹⁾	Pressure connection: G ½ EN 837	Code number
0 – 6	✓	060G1874
0 – 10	✓	060G1875
0 – 16	✓	060G1876
0 – 25	✓	060G1877

¹⁾ Gauge / relative

Spareparts and accessories for MBS 3200

Plug in display



Type	Description	Code number
MBD 1000	Microprocessor controlled plug-in display	060G2850

Plug



Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
En 175301-803-A, Pg 11 plug	060G0007
En 175301-803-A, plug with 5 m cable	060G1034

Adapters




Description	Code number
G ½ female to G ¼ male	060G1021
G ½ female to G ¼ (DIN3852) male	060G1022
G ½ female to G ¾ male	060G1023
G ½ female to ¼ flare male	060G1024
G ½ with pulse-snubber	060G0252


MBS 3250 compact pressure transmitters with pulse-snubber



Design



Temperature



The compact high temperature pressure transmitter MBS 3250 is designed for use in hydraulic applications with severe medium influences like cavitation, liquid hammer or pressure peaks and offers a reliable pressure measurement, even under harsh environmental conditions.


The flexible heavy duty pressure transmitter programme covers 4 – 20 mA, 0 – 5 V, 1 – 5 V, 1 – 6 V and 0 – 10V output signal, absolute and gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 600 bar and a wide range of pressure- and electrical connections.

Excellent vibration stability, uniquely robust construction, a high degree of EMC/EMI protection and a high operating temperature equip the pressure transmitter to meet the most stringent industrial and hydraulic requirements.

- 4 – 20 mA, 0 – 5 V, 1 – 5 V, 1 – 6 V and 0 – 10 V output signal
- Operating temperature -40 – 125 °C
- Measuring range 0 – 600 bar
- A wide range of pressure and electrical connections are available
- For use in severe industrial environments
- With pulse-snubber
- Wetted parts: stainless steel (AISI 316)

Dimensions and weight:

Weight: 0.17 kg



All dimensions in millimetres

Approvals: CE, UL, UL Hazloc, Ex-N, Gost

MBS 3250 pressure transmitters with pulse-snubber

Accuracy: +/- 0.5% FS (typ.)

Media temperature: -40 – 125 °C

Output signal: 4 – 20 mA

Electrical connections: EN175301-803A, Pg 9

Range: Flexible - different electrical and pressure connections available



Pressure range P _e [bar] ¹⁾	Pressure connection G ¼ DIN 3852-E	Code number
0 – 2.5	✓	060G1861
0 – 4	✓	060G1862
0 – 6	✓	060G1863
0 – 10	✓	060G1791
0 – 16	✓	060G1864
0 – 25	✓	060G1865
0 – 40	✓	060G1790
0 – 60	✓	060G1866
0 – 100	✓	060G1867
0 – 160	✓	060G1868
0 – 250	✓	060G1779
0 – 400	✓	060G1869
0 – 600	✓	060G1778

¹⁾ Gauge / relative

Spareparts and accessories for MBS 3250

Plug in display



Type	Description	Code number
MBD 1000	Microprocessor controlled plug-in display	060G2850

Plug



Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
En 175301-803-A, Pg 11 plug	060G0007
En 175301-803-A, plug with 5 m cable	060G1034

Adapters




Description	Code number
G ½ female to G ¼ male	060G1021
G ½ female to G ¼ (DIN3852) male	060G1022
G ½ female to G ¾ male	060G1023
G ½ female to ¼ flare male	060G1024


MBS 3100 compact pressure transmitter



Design



Temperature



The compact ship approved pressure transmitter MBS 3100 is designed for use in almost all marine applications, and offers a reliable pressure measurement, even under harsh environmental conditions.


The flexible pressure transmitter programme covers a 4 – 20 mA output signal, absolute and gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 600 bar, plug and cable connections and a wide range of pressure connections.

Excellent vibration stability, robust construction, and a high degree of EMC/EMI protection equip the pressure transmitter to meet the most stringent marine requirements.

- 4 – 20 mA output signal
- Operating temperature -40 – 85 °C
- Measuring range 0 – 600 bar
- Standard pressure connection G 1/4A DIN 16288, G 1/4A, O-ring DIN 3852 G 1/2A DIN 16288
- Available with all relevant marine approvals
- Suited for marine applications
- Wetted parts: stainless steel (AISI 316)

Dimensions and weight:

Weight: 0.2 kg



All dimensions in millimetres

Approvals: CE, UL, UL Hazloc, Ex-N, Gost, LR, DNV, GL, RINA, ABS, BV, NKK, PRS, MRS, CSS

MBS 3100 compact pressure transmitter

Accuracy: +/- 0.5% FS (typ.)

Media temperature: -40 – 85 °C

Output signal: 4 – 20 mA

Electrical connections: EN 175301-803-A, Pg 11

Range: Flexible – many different electrical and pressure connections available



Measuring range P _e [bar] ¹⁾	Pressure connection			Code numbers
	G ¼ A EN 837	G ¼ A, O-ring DIN 3852	G½ A EN 837	
0 – 4	✓			060G1367
0 – 6	✓			060G1368
0 – 10	✓			060G1369
0 – 16	✓			060G1370
0 – 25	✓			060G1371
0 – 40	✓			060G1372
0 – 4		✓		060G1463
0 – 6		✓		060G1464
0 – 10		✓		060G1465
0 – 16		✓		060G1466
0 – 25		✓		060G1467
0 – 40		✓		060G1468
-1 – 1.5 ²⁾			✓	060G5600
-1 – 5 ²⁾			✓	060G5601
0 – 4			✓	060G1469
0 – 6			✓	060G1470
0 – 10			✓	060G1471
0 – 16			✓	060G1472
0 – 25			✓	060G1473
0 – 40			✓	060G3388

¹⁾ Gauge / relative

²⁾ Sealed gauge

Spare parts and accessories for MBS 3100

Plugs



Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
EN 175301-803-A, Pg 11 plug	060G0007
EN 175301-803-A, Pg 13.5 plug	060G0005
EN 175301-803-A, plug with 5 m cable	060G1034

Adapters



Description	Code number
G ½ female to G ¼ male	060G1021
G ½ female to G ¼ (DIN 3852) male	060G1022
G ½ female to ⅜ male	060G1023
G ½ female to ¼ flare male	060G1024
G ½ female with pulse-snubber	060G0252



Plug in display

Type	Description	Code number
MBD 1000	Microprocessor controlled plug-in display	060G2850



Isolating valve for pressure connection in compliance with DIN 3852-E

Type	Female thread	Male thread	Code number
MBV 2000	G ¼ DIN 3852	G ¼ DIN 3852-E	061B6001
MBV 2000	G ¼ DIN 3852	G ½ DIN 3852-E	061B6002
MBV 2000	G ½ DIN 3852	G ½A DIN 3852-E	061B6003
MBV 2000	G ¼ DIN 3852	¼-18 NPT DIN 3866-A	061B6004




Test valve

Type	Pressure range [bar]	Pressure connection	Transmitter connection	Code number
MBV 3000	0 – 120	DIN 3852-E-G¼	DIN 3852-X-G½	061B6100


MBS 3150 compact pressure transmitter with pulse-snubber



Design



Temperature



The compact ship approved pressure transmitter MBS 3150 is designed for use in marine applications with severe medium influences like cavitation, liquid hammer or pressure peaks and offers a reliable pressure measurement, even under harsh environmental conditions.


The flexible pressure transmitter programme covers a 4 – 20 mA output signal, absolute and gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 600 bar, plug and cable connections and a wide range of pressure connections.

Excellent vibration stability, uniquely robust construction, and a high degree of EMC/EMI protection equip the pressure transmitter to meet the most stringent marine requirements.

- 4 – 20 mA output signal
- Operating temperature - 40 – 85 °C
- Measuring range 0 – 600 bar
- Standard pressure connection G 1/4A, O-ring DIN 3852, G 1/2A DIN 16288
- With integrated pulse-snubber
- Available with all relevant marine approvals and designed to meet the strict demands on marine equipment
- Wetted parts: stainless steel (AISI 316)

Dimensions and weight:

Weight: 0.2 kg



All dimensions in millimetres

Approvals: CE, UL, UL Hazloc, Ex-N, Gost, LR, DNV, GL, RINA, ABS, BV, NKK, PRS, MRS, CSS

MBS 3150 compact pressure transmitter with pulse-snubber

Accuracy: +/- 0.5% FS (typ.)
Media temperature: -40 – 85 °C
Output signal: 4 – 20 mA
Electrical connections: EN 175301-803-A, Pg 11
Range: Flexible – many different electrical and pressure connections available



Measuring range P _e [bar] ¹⁾	Pressure connection		Code numbers
	G ½ A EN 837	G ¼ A, O-ring DIN 3852	
0 – 6	✓		060G1476
0 – 10	✓		060G1477
0 – 6		✓	060G1474
0 – 10		✓	060G1475

¹⁾ Gauge / relative

Spare parts and accessories for MBS 3150

Plugs



Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
EN 175301-803-A, Pg 11 plug	060G0007
EN 175301-803-A, Pg 13.5 plug	060G0005
EN 175301-803-A, plug with 5 m cable	060G1034

Adapters



Description	Code number
G ½ female to G ¼ male	060G1021
G ½ female to G ¼ (DIN 3852) male	060G1022
G ½ female to ⅜ male	060G1023
G ½ female to ¼ flare male	060G1024
G ½ female with pulse-snubber	060G0252

Plug in display



Type	Description	Code number
MBD 1000	Microprocessor controlled plug-in display	060G2850

Isolating valve for pressure connection in compliance with DIN 3852-E



Type	Female thread	Male thread	Code number
MBV 2000	G ¼ DIN 3852	G ¼ DIN 3852-E	061B6001
MBV 2000	G ¼ DIN 3852	G ½ DIN 3852-E	061B6002
MBV 2000	G ½ DIN 3852	G ½A DIN 3852-E	061B6003

Test valve




Type	Pressure range [bar]	Pressure connection	Transmitter connection	Code number
MBV 3000	0 – 120	DIN 3852-E-G½	DIN 3852-X-G¼	061B6100


MBS 1900, OEM pressure transmitter for compressed air and water pump applications



Design



Temperature °C




Pressure transmitter, type MBS 1900 is designed for use in air and water applications like booster pumps and air compressors. The pressure transmitter programme covers different output

signals, absolute and gauge (relative) versions, measuring ranges from 0 – 4 bar to 0 – 25 bar and a range of pressure and electrical connections.

Dimensions and weight:

Weight: 0.15 – 0.3 kg, depending on pressure / electrical connection



All dimensions in millimetres

Approvals: CE, UL

MBS 1900 pressure transmitter

Accuracy: $\pm 1\%$ FS

Media temperature: $0 - 80\text{ }^{\circ}\text{C}$

Digitally compensated



Measuring range P_e [bar] ¹⁾	Output signal		Pressure connection			Electrical connection			Code number
	[mA]	Ratio-metric	G 1/4 A EN 837	R 1/4 ISO 7-1	G 1/4 DIN 3852-E	No plug (EN 175301- 803-A)	Plug Pg 9 (EN 175301- 803-A)	Round Pack- ard Metripack 150.2	
0 - 6	4 - 20		✓			✓			064G6501
0 - 10	4 - 20		✓			✓			064G6502
0 - 10	4 - 20			✓			✓		064G6543
0 - 16	4 - 20		✓				✓		064G6523
0 - 16	4 - 20				✓	✓			064G6511
0 - 16	4 - 20				✓			✓	064G6533
0 - 16		✓			✓			✓	064G6532
0 - 16	4 - 20			✓			✓		064G6542
0 - 25	4 - 20		✓			✓			064G6504

¹⁾ Gauge / relative

Spareparts and accessories for MBS 1900

Plug




Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
EN 175301-803-A, plug with 5 m cable	060G1034


MBS 1200/1250 OEM pressure transmitters for use in severe hydraulic applications



Design



Temperature



The OEM pressure transmitter, types MBS 1200 & MBS 1250 are based on a thin-film technology ensuring an excellent vibration stability and an exceptional robustness as well as a high degree of EMI protection which enable them to meet the most severe hydraulic applications.


A wide choice of electrical outputs as well as pressure connections mean that the transmitters are suitable for most applications within the mobile hydraulic segment.

And the compact designs make them ideal for installations where space is at a premium.


- Measuring range: 0 – 20 bar to 0 – 2200 bar
- Accuracy: $\pm 0.5\%$ FS
- Pressure reference: Gauge (relative)
- Output signal: mA, voltage and ratiometric

Dimensions and weight:

Weight: 0.1 - 0.15 kg, depending on pressure / electrical connection



All dimensions in millimetres



MBS 1250 has an integrated pulse-snubber offering a high degree of protection against cavitations and liquid hammer. Cavitation, liquid hammer and pressure peaks may occur in liquid filled hydraulic systems with changes in flow velocity, e.g. fast closing of a valve or pump starts and stops. The problem may occur on the inlet and outlet side, even at rather low operating pressures.

For ordering please contact your nearest Danfoss dealer.

MBS1200**Accuracy:** ± 0.5 FS**Media temperature:** -40 -125°C

Measuring range P_e [bar] ¹⁾	Output signal		Pressure connection DIN 3852-E G 1/4	Electrical connection		Code number
	[mA]	[V]		EN 60947-5-2 M12x1	Rectangular connector	
0 – 7	4 – 20		✓	✓		063G1407
0 – 10		✓	✓	✓		063G1632
0 – 40	4 – 20		✓	✓		063G1159
0 → 250	4 → 20		✓	✓		063G1410


MBS1250**Accuracy:** ± 0.5 FS**Media temperature:** -40 -125°C

Measuring range P_e [bar] ¹⁾	Output signal		Pressure connection DIN 3852-E G 1/4	Electrical connection		Code number
	[mA]	[V]		EN 60947-5-2 M12x1	Rectangular connector	
0 – 400	4 – 20		✓	✓		063G1123
0 – 600	4 – 20		✓	✓		063G1125
0 – 10	4 – 20		✓	✓		063G1133
0 – 250		✓	✓	✓		063G1068
0 – 16	4 – 20		✓		✓	063G1218
0 – 250	4 – 20		✓	✓		063G1229


MBS 1300/1350 OEM electronic pressure switch with dual output for severe hydraulic applications



Design



Temperature



The OEM pressure switch and transmitter, types MBS 1300 and MBS 1350 are based on thin-film technology providing excellent vibration stability, robust construction and a high degree of EMI protection. These features among others ensure that the transmitters meet the most stringent industrial standards.


Two products in one:

The range is a compact dual-output product dedicated for hydraulic applications, where a combination of pressure signal output and/or pressure switch function is requested.

Pressure ranges (system):	20 – 2,200 bar
Pressure set point (typical):	10 – 110% calibrated range - switch point set at factory
DC switch current limit:	350mA (at 125 Centigrade)
Switch Options:	PNP (switch to Battery) or NPN (Open Collector format, switch to ground)
Mobile Hydraulic Certifications:	Designs compliant with ISO7637 standards
Supply voltage:	Compatible with 12V or 24V regulated supplies

Dimensions and weight:


Weight 0.1 – 0.15, depending on pressure / electrical connection



All dimensions in millimetres

MBS 1350 has an integrated pulse-snubber offering a high degree of protection against cavitations and liquid hammer.

Cavitation, liquid hammer and pressure peaks may occur in liquid filled hydraulic systems with changes in flow velocity, e.g. fast closing of a valve or pump starts and stops. The problem may occur on the inlet and outlet side, even at rather low operating pressures.




For ordering please contact your nearest Danfoss dealer.


MBS 5100 pressure transmitter



Design



Temperature



The ship approved high accuracy pressure transmitter MBS 5100 is designed for use in almost all marine applications, and offers a reliable pressure measurement, even under harsh environmental conditions.

The pressure transmitter programme in block design covers a 4 – 20 mA output signal, absolute and gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 600 bar, zero point and span adjustment, plug connection and female/flange pressure connections.


Excellent vibration stability, robust construction, and a high

degree of EMC/EMI protection equip the pressure transmitter to meet the most stringent industrial requirements.

- 4 – 20 mA output signal
- Operating temperature -40 – 85 °C
- Measuring range 0 – 600 bar
- Pressure connection G 1/4 female
- Available with all relevant marine approvals
- Designed to meet the strict demands in marine equipment
- Wetted parts: stainless steel (AISI 316)

Dimensions and weight:

Weight: 0.4 kg



All dimensions in millimetres

Approvals: CE, UL, UL Hazloc, Ex-N, Gost, LR, DNV, GL, RINA, ABS, BV, NKK, PRS, MRS, CSS

MBS 5100 pressure transmitter

Accuracy: $\pm 0.1\%$ FS (typ.)

Media temperature: $-40 - 85\text{ }^{\circ}\text{C}$

Output signal: $4 - 20\text{ mA}$

Electrical connections: EN 175301-803-A, Pg 11

Zero and span adjustment



Measuring range P_e [bar] ¹⁾	Pressure connection G 1/4 with flange	Code number
0 – 1	✓	060N1032
0 – 2,5	✓	060N1033
0 – 4	✓	060N1034
0 – 6	✓	060N1035
0 – 10	✓	060N1036
0 – 16	✓	060N1037
0 – 25	✓	060N1038
0 – 40	✓	060N1039
0 – 60	✓	060N1040
0 – 100	✓	060N1041

¹⁾ Gauge/relative

Spare parts and accessories for MBS 5100



Plugs

Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
EN 175301-803-A, Pg 11 plug	060G0007
EN 175301-803-A, Pg 13.5 plug	060G0005
EN 175301-803-A, plug with 5 m cable	060G1034


MBV 5000 pressure test valve

Media temperature: -20 – 120 °C

Pressure connection: G 1/4 (Input)
Flange / M5 x 8 (Output)






Output no.	Length (L ₁) [mm]	Code numbers
x1	36	061B7000
x2	76	061B7001
x3	116	061B7002
x4	156	061B7003
x5	196	061B7004
x2	76	061B7005
x3	116	061B7006
x4	156	061B7007
x5	196	061B7008
x2	76	061B7009
x3	116	061B7010
x4	156	061B7011
x5	196	061B7012



Weight: 0.4 - 2 kg
depending on the
different configurations

All dimensions in millimetres

Standard flange - G 1/8 adapters




Description	Code number
Cover	061B720001
Angleway adapter	061B720101
Straightway adapter	061B720201


MBS 5150 pressure transmitters with pulse-snubber



Design



Temperature



The ship approved high accuracy pressure transmitter MBS 5150 is designed for use in marine applications with severe medium influences like cavitation, liquid hammer or pressure peaks, and offers a reliable pressure measurement, even under harsh environmental conditions.


The pressure transmitter programme in block design covers a 4 – 20 mA output signal, absolute and gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 600 bar, zero point and span adjustment, plug connection and female/flange pressure connections.

Excellent vibration stability, robust construction, and a high degree of EMC/EMI protection equip the pressure transmitter to meet the most stringent industrial requirements.

- 4 – 20 mA output signal
- Operating temperature -40 – 85 °C
- Measuring range 0 – 600 bar
- Pressure connection G ¼ female
- With integrated pulse-snubber
- Available with all relevant marine approvals
- Designed to meet the strict demands in marine equipment
- Wetted parts: stainless steel (AISI 316)

Dimensions and weight:

Weight: 0.4 kg



All dimensions in millimetres

Approvals: CE, UL, UL Hazloc, Ex-N, Gost, LR, DNV, GL, RINA, ABS, BV, NKK, PRS, MRS, CSS

MBS 5150 pressure transmitter with pulse-snobber

Accuracy: +/- 0.1% FS (typ.)
Media temperature: -40 – 85 °C
Output signal: 4 – 20 mA
Electrical connections: EN 175301-803-A, Pg 11
Zero and span adjustment



Measuring range P_e [bar] ¹⁾	Pressure connection G 1/4 with flange	Code number
0 – 1	✓	060N1081
0 – 2,5	✓	060N1083
0 – 4	✓	060N1084
0 – 6	✓	060N1063
0 – 10	✓	060N1064
0 – 16	✓	060N1065
0 – 25	✓	060N1085
0 – 40	✓	060N1066
0 – 60	✓	060N1086
0 – 100	✓	060N1087

¹⁾ Relative / gauge

Spare parts and accessories for MBS 5150

Plugs



Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
EN 175301-803-A, Pg 11 plug	060G0007
EN 175301-803-A, Pg 13.5 plug	060G0005
EN 175301-803-A, plug with 5 m cable	060G1034


MBV 5000 pressure test valve

Media temperature: -20 – 120 °C

Pressure connection: G 1/4 (Input)
Flange / M5 x 8 (Output)




Output no.	Length (L ₁) [mm]	Code numbers
x1	36	061B7000
x2	76	061B7001
x3	116	061B7002
x4	156	061B7003
x5	196	061B7004
x2	76	061B7005
x3	116	061B7006
x4	156	061B7007
x5	196	061B7008
x2	76	061B7009
x3	116	061B7010
x4	156	061B7011
x5	196	061B7012



Weight: 0.4 - 2 kg
depending on the
different configura-
tions

All dimensions in millimetres

Standard flange - G 1/8 adapters




Description	Code number
Cover	061B720001
Angleway adapter	061B720101
Straightway adapter	061B720201


MBS 4510 flush diaphragm pressure transmitter



Design



Temperature




The high accuracy flush diaphragm pressure transmitter MBS 4510 is designed for use in non-uniform, high viscous or crystallizing media within industry, food and beverage, and offers a reliable pressure measurement, even under harsh environmental conditions.

The pressure transmitter programme covers a 4 – 20 mA output signal, absolute and gauge (relative) versions, measuring ranges from 0 – 250 mbar til 0 – 25 bar, zero point and span adjustment, plug connection and a G1A conic pressure connection with a flush mounted diaphragm.

Excellent vibration stability, robust construction, and a high degree of EMC/EMI protection equip the pressure transmitter to meet the most stringent industrial requirements.

- 4 – 20 mA output signal
- Operating temperature -10 – 85 °C
- Measuring ranges 0 – 250 mbar to 0 – 25 bar
- Available with many different pressure connections
- With zero point and span adjustment
- With flush diaphragm
- For use in food and beverage industry as well as industrial applications with aggressive, heterogeneous and highly viscous media
- Wetted parts: stainless steel (AISI 316)

Dimensions and weight:



Weight: 0.4 kg

All dimensions in millimetres

Approvals: CE, UL, UL Hazloc, Ex-N, Gost

MBS 4510 flush diaphragm pressure transmitter

Accuracy: +/- 0.2% FS (typ.)

Media temperature: -10 – 85 °C

Output signal: 4 – 20 mA

Electrical connections: EN 175301-803-A, Pg 9

Zero and span adjustment



Measuring range P_e [bar] ¹⁾	Pressure connection G 1 A with cone	Code number
0 – 0.25	✓	060G2418
0 – 0.4	✓	060G2419
0 – 0.6	✓	060G2420
0 – 1	✓	060G2421
0 – 1.6	✓	060G2422
0 – 2.5	✓	060G2423
0 – 4	✓	060G2424
0 – 6	✓	060G2425
0 – 10	✓	060G2426
0 – 16	✓	060G2427
0 – 25	✓	060G2428

¹⁾ Gauge / relative

Spare parts and accessories for MBS 4510

Adapters




Description	Code number
Welding nipple for conic metal/metal seal	060G2501
DIN 11851 (diary connection) DN40	060G2505
DIN 11851 (diary connection) DN50	060G2506
Clamp, ISO 2852, 1½ in	060G2502
Clamp, ISO 2852, 2 in	060G2510
SMS 1145 connection, 1½ in	060G2503


MBS 9200 Low pressure transmitter



Design



Temperature



The compact pressure transmitter MBS 9200 is designed for use in industrial applications e.g. crankcase and turbocharger on industrial engines, filter monitoring as well as applications within level measurement.


The programme cover 4 – 20 mA and ratiometric output signal, gauge versions, pressure span from 40 – 250 mbar as well as bidirectional ranges e.g. -70 – 70 mbar etc.

Excellent vibration stability, robust construction, and a high degree of EMC / EMI protection equip the pressure transmitter to meet the most stringent industrial requirements..

- 4 – 20 mA or ratiometric output signal
- Full scale span from 40 – 250 mbar as well as bidirectional ranges e.g. -70 – 70 mbar etc. (lowest zero point -100 mbar)
- Digital temperature compensated
- Reverse polarity protection
- With build-in clipping function and self-dianostic on request
- Enclosure and wetted parts of stainless steel (AISI 316L)
- Customer specific version on request

Dimensions and weight:

Weight: 0.2 kg



All dimensions in millimetres

Approvals: CE

MBS 9200 Low pressure transmitter

Accuracy: $\pm 0.5 - \pm 2\%$ FSS (depending on pressure span)
Media temperature: $-25^{\circ} - 100^{\circ}\text{C}$ (depending on gasket material)
Output signal: 4 – 20 mA
Electrical connections: EN 175301-803-A, Pg 9
Range: Flexible, different electrical and pressure connections available



Measuring range P_e [bar] ¹⁾	Pressure connection		Gasket		Code numbers
	DIN 3852-E-G1/4 Gasket: DIN 3869-14	DIN 3852-E-G1/4 Gasket: DIN 3869-14	FPM	NBR	
0.02 – 0.02		✓	✓		064G5225
0 – 0.1	✓		✓		064G5214
0 – 0.1		✓		✓	064G5222
0 – 0.15	✓		✓		064G5216
0 – 0.25	✓		✓		064G5215
0 – 0.25	✓			✓	064G5218

¹⁾ Gauge / relative

Spare parts and accessories for MBS 9200

Plugs



Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
EN 175301-803-A, Pg 11 plug	060G0007

Plug in display




Type	Description	Code number
MBD 1000	Microprocessor controlled plug-in display	060G2850


MBS 9300 Low pressure transmitter



Design



Temperature



The compact pressure transmitter MBS 9300 is designed for use in industrial applications e.g. crankcase and turbocharger on marine engines, filter monitoring as well as applications within level measurement.


The programme cover 4 – 20 mA output signal, gauge versions, pressure span from 40 – 250 mbar as well as bidirectional ranges e.g. -70 – 70 mbar etc.

Excellent vibration stability, robust construction, and a high degree of EMC / EMI protection equip the pressure transmitter to meet the most stringent industrial requirements..

- 4 – 20 mA output signal
- Full scale span from 40 – 250 mbar as well as bidirectional ranges e.g. -70 – 70 mbar etc. (lowest zero point -100 mbar)
- Digital temperature compensated
- Reverse polarity protection
- With build-in clipping function and self-dianostic on request
- Enclosure and wetted parts of stainless steel (AISI 316L)
- Customer specific version on request

Dimensions and weight:

Weight: 0.2 kg



All dimensions in millimetres

Approvals: CE, DNV, BV, ABS, LR, RINA, KR

MBS 9300 Low pressure transmitter

Accuracy: $\pm 0.5 - \pm 2\%$ FSS (depending on pressure span)
Media temperature: $-25^{\circ} - 100^{\circ}\text{C}$ (depending on gasket material)
Output signal: 4 – 20 mA
Electrical connections: EN 175301-803-A, Pg 9
Range: Flexible, different electrical and pressure connections available



Measuring range P_e [bar] ¹⁾	Pressure connection		Gasket		Code numbers
	DIN 3852-E-G1/4 Gasket: DIN 3869-14	DIN 3852-E-G1/2 Gasket: DIN 3869-14	FPM	NBR	
- 0.07 – 0.07	✓		✓		064G5202
- 0.03 – 0.03	✓		✓		064G5201
- 0.02 – 0.02	✓			✓	064G5207
0 – 0.25	✓		✓		064G5228
0 – 0.04	✓		✓		064G5221
0 – 0.06	✓		✓		064G5219
0 – 0.1	✓			✓	064G5224
0 – 0.1		✓		✓	064G5226

¹⁾ Gauge / relative

Spare parts and accessories for MBS 9300

Plugs



Description	Code number
EN 175301-803-A, Pg 9 plug	060G0008
EN 175301-803-A, Pg 11 plug	060G0007
EN 175301-803-A, Pg 13.5 plug	060G0005

Plug in display




Type	Description	Code number
MBD 1000	Microprocessor controlled plug-in display	060G2850


EMP 2 pressure transmitters



Design



Temperature




The ship approved pressure transmitter EMP 2 is designed for use in almost all marine and industrial applications, and offers a reliable pressure measurement, even under harsh environmental conditions.

The pressure transmitter programme in box design covers a 4 – 20 mA output signal, gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 400 bar, zero point and span adjustment, Pg 13.5 cable entry and different pressure connections. A robust construction enables the pressure transmitter to meet the strictest requirements.

- 4 – 20 mA output signal
- Operating temperature -10 – 70 °C
- Measuring range 0 – 400 bar
- Pressure connections G ¼, G ½ standard, G ¾ A mano
- With zero point and span adjustment
- Available with all relevant marine approvals
- For use in harsh industrial / marine environments
- Wetted parts: stainless steel (AISI 316)

Dimensions and weight:

Weight: 1 kg



All dimensions in millimeters

Approvals: CE, UL, UL Hazloc, Ex-N, Gost, LR, DNV, GL, RINA, ABS, BV, NKK, PRS, MRS, CSS

EMP 2 pressure transmitters

Accuracy: $\pm 0.3\%$ FS

Media temperature: $-40 - 100\text{ }^{\circ}\text{C}$

Output signal: $4 - 20\text{ mA}$

Electrical connections: Terminal block, Pg 13.5

Zero and span adjustment



Operating pressure P_e [bar] ¹⁾	Pressure connection		Code number
	G 1/2 A	G 3/8 A	
-1 - 1.5 ¹⁾	✓		084G2100
-1 - 5 ¹⁾	✓		084G2101
0.2 - 1	✓		084G2102
0 - 1	✓		084G2103
0 - 1.6	✓		084G2104
0 - 2.5	✓		084G2105
0 - 4	✓		084G2106
0 - 4		✓	084G2206
0 - 6	✓		084G2107
0 - 6		✓	084G2207
0 - 6	✓		084G2108
0 - 10	✓		084G2109
0 - 10		✓	084G2209
0 - 10	✓		084G2110
0 - 16	✓		084G2111
0 - 16		✓	084G2211
0 - 25	✓		084G2112
0 - 40	✓		084G2113
0 - 40		✓	084G2213
0 - 60	✓		084G2114
0 - 100	✓		084G2115
0 - 160	✓		084G2116
0 - 250	✓		084G2117
0 - 400	✓		084G2118
-1 - 9 ¹⁾	✓		084G2120

¹⁾ Gauge / relative

Spareparts and accessories for EMP



Damping coil

Description	Material	Code number
G 3/8 unions and 1.5 m capillary tube.	Copper	060-104766
G 1/2 unions and 1 m capillary tube.	Stainless steel	060-016966
G 3/8 unions and 1 m capillary tube. Armoured.	Copper	060-333366

Nipple

Description	Material	Code number
G 1/4 A x G 3/8 A with copper washer.	Brass	060-333266
G 1/4 A x M10 ext. x 1 with copper washer.	Brass	060-333866



Temperature sensors

Serving a broad, global market within diverse and demanding industries, Industrial Automation is your one-stop partner for industrial control components. Through Danfoss Industrial Automation you gain access to the entire Danfoss pool of technology for a wide range of industries.

HYDRAULICS

In a world depending on infrastructure, mobile hydraulic equipment is key to making modern living possible for an ever growing population. Whether used in construction, agriculture or for material handling, mobile hydraulics equipment offers efficiency, economy, safety and environmental advantages.

MARINE


From the handling of sewage water to the treatment of exhaust gasses: A modern ship contains most of the applications found on shore, albeit in a limited space. Danfoss Industrial Automation is a global leader in supplying pressure transmitters to equipment placed in and around the engine room: 2 and 4 stroke diesel and gas engines, propulsion systems, fuel treatment, oil separators among others.

AIR COMPRESSORS

Spanning from very small units for medical use to very large industrial compressors operating in the kilowatt power band, the air compressor industry covers a huge range of equipment. Equally varied are the fundamental compressor technologies used.

PUMPS

The global need for clean water is enormous and on the rise, calling for a dedicated common effort to control the water cycle. Danfoss is well prepared to contribute to such endeavors. To us, the pump is the key to controlling the water cycle – from intake to effluent. Consequently, we have developed a range of sensors and switches for pumps, tailored for the most common applications in the water industry.



Examples



Onboard complex, new ships, the MBT temperature sensor control that vital parts of the propulsion system all run perfectly, within the parameters of safe operation.



On wind turbines, helping to increase the amount of wind-produced power worldwide, the MBT temperature sensor gives reliable readings of hydraulic oil temperatures.

Temperature sensors

in this catalogue



		MBT3250	MBT 3270	MBT 3560	MBT 153	MBT 5250	MBT 5252	MBT 5113	MBT 5116
Segments	Transportation								
	Heating and sanitation								
	Machine and equipment								
	Energy								
Characteristics	Pt 100/Pt 1000	✓	✓		✓	✓	✓		✓
	NTC/PTC	✓	✓		✓	✓	✓	✓	
	Transmitter	mA/V d.c.							
	Transmitter as option						mA	mA	
	Measuring insert	Changeable	Fixed	Fixed	Fixed	Changeable	Changeable	Changeable	Changeable
	Medium temperature	-50 – 200 °C (-58 – 392 °F) 	-50 – 300 °C (-58 – 572 °F) 	-50 – 200 °C (-58 – 392 °F) 	-50 – 200 °C (-58 – 392 °F) 	-50 – 200 °C (-58 – 392 °F) 	-50 – 400 °C (-58 – 752 °F) 	-50 – 800 °C (-58 – 1472 °F) 	-50 – 600 °C (-58 – 1112 °F) 
	Enclosure	IP65 (NEMA 4)	IP65 (NEMA 4)	IP65/IP67 (NEMA 4/ NEMA 6)	IP67 (NEMA 6)	IP65 (NEMA 4)	IP65 (NEMA 4)	IP65 (NEMA 4)	IP65 (NEMA 4)
	Material protection tube	W.no. 1.4571 (AISI 316 Ti)	W.no. 1.4571 (AISI 316 Ti)	W.no. 1.4571 (AISI 316 Ti)	W.no. 1.4571 (AISI 316 Ti)	W.no. 1.4571 (AISI 316 Ti)	W.no. 1.4571 (AISI 316 Ti)	W.no. 1.4571 (AISI 316 Ti)	W.no. 1.4571 (AISI 316 Ti)
	Reaction time t0.5 in water (sec)	9 s	1.5 s	10 s	1 s	9 s	12 s	30 s	30 s
	Marine approvals					✓	✓	✓	✓



Marine and mobile hydraulics



Electric power and wind turbines



Boiler and boiler room equipment, sterilisers and autoclaves



Industrial hydraulics, air compressors, water pumps and industrial engines

Temperature sensors that can take the heat

An outstanding temperature sensor performance is characterised by:

- The element
- The ability to react fast and precise
- The packaging

1 Elements

- RTD (Pt100/Pt1000) – for standardised signals and high accuracy the RTD's are a perfect choice
- Changeable measuring insert

2 The ability to react fast and precise

Special care has been put into the design of the sensor in relation to the reaction time. A specially developed sensor element fixture ensures contact between the element and the housing material in order to secure a fast heat transfer from the media to the sensor element. On top of this the sensor construction ensures minimum radiation of heat, which results in a measurement very close to the actual temperature of the media.


3 Packaging

The sensor design offers long-life stability through:

- High shock and vibration stability
- High enclosure grade IP65

Sensor material:

- Stainless steel (AISI 316)
- Gold plated contacts to secure flawless signal



MBT 3250 temperature sensor



The MBT 3250 is a heavy-duty temperature sensor that can be used for controlling cooling water, lubrication oil, hydraulic oil and refrigeration plants within general industry applications.


This temperature sensor is based on a standardized Pt100 or Pt1000 element, which gives a reliable and accurate measurement. The MBT 3250 can be delivered with NTC/PTC elements on request.

The measuring insert is based on a silicone cable, which makes the sensor very resistant towards vibrations. All parts in contact with the media are made of stainless steel AISI 316 Ti. The MBT 3250 is equipped with a EN 175301-803-A, Pg 9 plug as standard, but can be delivered with M12 or DIN 72585 Bayonet on request.

- For gaseous or liquid media, e.g. air, gas, vapour, water or oil
- Up to 200 °C media temperatures
- Pt100 or Pt1000 resistance element
- Can be used with 2- or 3-wire connections
- Gold plated male and female connector
- Interchangeable measuring insert
- Wetted parts: Stainless Steel (AISI 316)

Dimensions and weight:

Weight: 0.145 – 0.220 kg
depending on insertion
length



All dimensions in millimetres

Approvals: CE

MBT 3250 temperature sensor

Measuring range: -50 – 200 °C

Resistance element: 1 x Pt 100

Extension length: None



Insertion length [mm]	Process connection size	Electrical connection: EN 175301-803-A		Code number
		Pg 9	Pg 11	
50	G ½ A	✓		084Z2446
50	G ½ A		✓	084Z2447
50	G ¾ A		✓	084Z2448
100	G ¾ A		✓	084Z2449
100	G ½ A	✓		084Z2450
100	G ½ A		✓	084Z2451
150	G ½ A		✓	084Z2452
150	G ½ A	✓		084Z2453
150	G ¾ A			084Z2454
150	G ¾ A		✓	084Z2455
200	G ½ A	✓		084Z2456
200	G ½ A		✓	084Z2457
200	G ¾ A			084Z2458
200	G ¾ A		✓	084Z2459
50	G ¾ A			084Z2460
100	G ¾ A			084Z2461

MBT 3270 temperature sensors



The flexible temperature sensor MBT 3270 can be used in many industrial applications such as: Air Compressors, Mobile Hydraulics and Exhaust gas return systems.


In other words application where robustness, size and performance are essentials.

The sensor can be equipped with different sensing element (RTD, NTC and PTC) and is available with different electrical connections (Cable, Delphi Metri Pack, AMP junior power Timer, Deutch DT04).



- Robust, high protection against moisture
- Fixed measuring insert
- Brass or stainless steel
- Very low response times
- Temperature range up to 300 °C
- Wetted parts: Stainless Steel (AISI 316)

Dimensions and weight:

Weight: 0.085 kg



-50 – 300 °C



-50 – 150 °C

All dimensions in millimetres

MBT 3270 temperature sensors

Fixed measuring insert

Very low response times

Resistance element		Insertion length (L _i) [mm]	Temperature range [°C]	Insertion Ø [mm]	Electrical connection			Code number
Pt 100	Pt 1000				AMP	Cable [m]	Deutsch	
✓		24	-50 – 150	6	✓			084Z2014
	✓	28	-50 – 150	4.2	✓			084Z2012
✓		40	-50 – 300	3	✓			084Z2018
✓		40	-50 – 300	3			✓	084Z2019
✓		40	-50 – 300	3		2		084Z2021



Approvals: CE

MBT 3560 temperature sensors with built-in transmitter




With MBT 3560 we have combined the technology of our standard temperature sensors and the electrical connections from the MBS pressure transmitters with a new developed electronics which has resulted in a compact temperature sensor with a built-in transmitter. The MBT 3560 is designed for use in harsh industrial environments where reliable, robust and accurate equipment is required. Available with a wide selection of process and electrical connections. Can be delivered with a 33 mm extension length which makes it possible to measure temperatures up to 200 °C without damaging the built-in electronics.

- Ultra compact design
- Acid-resistant stainless steel enclosure (AISI 316L)
- Temperature range -50 – 200 °C
- Pt 1000 resistance element
- Output signals: 4 – 20 mA or Ratiometric
- Protection tube: $\varnothing$ 8 mm
- Multiple insertion lengths: 50 – 250 mm
- Wetted parts: Stainless Steel (AISI 316)

Dimensions and weight:

Weight: 0.15 kg – 0.22 kg
depending on insertion length



L = Insertion length
 H = 9 mm

All dimensions in millimetres

Approvals: CE

MBT 3560 Temperature sensors with built-in transmitter

Measuring range: -50 – 200 °C
 Electrical connection: EN175301-803A, Pg 9
 Resistance element: Pt 1000
 Protection tube: Ø 8 mm
 Process connection: G ¼ A



Insertion length [mm]	Transmitter output 4 – 20 mA	Transmitter settings [°C]	Extension length [mm]	Code number
50	✓	0 – 100	-	084Z4030
100	✓	0 – 100	-	084Z4031
150	✓	0 – 100	-	084Z4032
200	✓	0 – 100	-	084Z4033
250	✓	0 – 100	-	084Z4034
50	✓	0 – 200	33	084Z4035
100	✓	0 – 200	33	084Z4036
150	✓	0 – 200	33	084Z4037
200	✓	0 – 200	33	084Z4038
250	✓	0 – 200	33	084Z4039

Spare part and accessories

Sensor pocket

Insertion length [mm]	Pocket insertion length [mm]	Process connection G ½ A	Protection tube Ø 11 [mm]	Code number
50	37.50	✓	✓	084Z7258
100	87.50	✓	✓	084Z7259
150	137.50	✓	✓	084Z7260
200	187.50	✓	✓	084Z7261
250	237.50	✓	✓	084Z7262



Plug in display

Type	Description	Code number
MBD 1000	Microprocessor controlled plug-in display	060G2850



MBT 153 cable-type temperature sensors




The MBT 153 is a heavy-duty temperature sensor that can be used for controlling cooling water and ventilation systems within general industry and marine applications.

This temperature sensor is based on a standardized Pt100 or Pt1000 element, which gives a reliable and accurate measurement. On request the MBT 153 can also be delivered with NTC/PTC elements. The sensor is based on a stainless steel housing with a cable, which makes the sensor extremely flexible.

The MBT 153 can be combined with a sensor pocket to protect the silicone cable from the media. The MBT 153 has a PVC or silicone cable as standard but it can be delivered with teflon cable on request.

- Temperature range -50 – 200 °C
- Short response times
- Pt100 or Pt1000 resistance element
- 2- or 4-wire connection
- Wetted parts: Stainless Steel (AISI 316)

Dimensions and weight:



*Weight: 0.120 kg – 0.425 kg
depending on cable length*

All dimensions in millimetres

Approvals: CE, LR, DNV, ClassNK

MBT 153 cable-type temperature sensors

Measuring range: -50 – 200 °C

Short response time

Resistance element		Cable length [m]	Cable type		Wires [pcs]	Code number
Pt 100	Pt 1000		PVC	Silicone		
✓		3.5	✓		2	084Z6030
✓		8.5	✓		2	084Z6032
	✓	3.5	✓		2	084Z6033
	✓	5.5	✓		2	084Z6034
	✓	8.5	✓		2	084Z6035
✓		3.5		✓	2	084Z6036
✓		5.5		✓	2	084Z6037
✓		8.5		✓	2	084Z6038
	✓	3.5		✓	2	084Z6039
✓		3.5		✓	4	084Z6215
✓		5.5		✓	4	084Z6042
✓		8.5		✓	4	084Z6216

Spare parts and accessories

Sensor pocket MBT 120

Insertion length [mm]	Process connections G ½ A	External diameter [mm]	Code number
50	✓	8	084Z6050
100	✓	8	084Z6051
200	✓	8	084Z6053
250	✓	8	084Z6054

MBT 5250 temperature sensor




The MBT 5250 is a heavy-duty temperature sensor that can be used for controlling cooling water, lubrication oil, hydraulic oil and refrigeration plants within general industry and marine applications. This temperature sensor is based on a standardized Pt100 or Pt1000 element, which gives a reliable and accurate measurement. The MBT 5250 can be delivered with NTC/PTC elements on request. The measuring insert is based on a silicone cable, which makes the sensor very resistant towards vibrations. All parts in contact with the media are made of stainless steel AISI 316 Ti. The MBT 5250 is equipped with a EN 175301-803-A, Pg 9 plug as standard, but can be delivered with M12 or DIN 72585 Bayonet on request.

- For gaseous or liquid media, e.g. air, gas, vapour, water or oil
- Up to 200 °C media temperatures
- Pt100 or Pt1000 resistance element
- Can be used with 2- or 3-wire connections
- Gold plated male and female connector
- Interchangeable measuring insert
- Available with all relevant marine approvals
- Wetted parts: Stainless Steel (AISI 316)

Dimensions and weight:

Weight: 0.145 – 0.220 kg
depending on insertion
length



All dimensions in millimetres

Approvals: CE, LR, GL BV, DNV, ClassNK, RINA, ABS, CCS

MBT 5250 temperature sensor

Measuring range: -50 – 200 °C

Resistance element: 1 x Pt 100

Extension length: None



Insertion length [mm]	Process connection size	Electrical connection: EN 175301-803-A			Code number
		Pg 9	Pg 11	Pg 13.5	
50	G ½ A	✓			084Z8011
50	G ½ A		✓		084Z8036
50	G ¾ A		✓		084Z8037
100	G ¾ A		✓		084Z8006
100	G ½ A	✓			084Z8012
100	G ½ A		✓		084Z8039
150	G ½ A		✓		084Z8008
150	G ½ A	✓			084Z8010
150	G ¾ A			✓	084Z8014
150	G ¾ A		✓		084Z8041
200	G ½ A	✓			084Z8022
200	G ½ A		✓		084Z8043
200	G ¾ A			✓	084Z8218
200	G ¾ A		✓		084Z8044
50	G ¾ A			✓	084Z8058
100	G ¾ A			✓	084Z8013

MBT 5252 temperature sensors



The MBT 5252 is a heavy-duty temperature sensor that can be used for controlling cooling water, lubrication oil, hydraulic oil and refrigeration plants within general industry and marine applications. This temperature sensor is based on a standardized Pt100 or Pt1000 element, which gives a reliable and accurate measurement. NTC/PTC elements available on request.


MBT 5252 can also be delivered with transmitter insert for 4 – 20 mA output. In the low temperature version (-50 – 200 °C) the measuring insert is based on a silicone cable, which makes the sensor very resistant towards vibrations.

All parts in contact with the media are made of stainless steel AISI 316 Ti. The MBT 5252 is equipped with a B-head as standard, but can be delivered with B-mini on request.

- For gaseous or liquid media, e.g. air, gas, vapour, water or oil
- Up to +400 °C media temperatures
- Available with built-in transmitter
- Available with all relevant marine approvals
- Wetted parts: Stainless Steel (AISI 316)

Dimensions and weight:

*Weight: 0.37 – 0.45 kg
depending on insertion length*



All dimensions in millimetres

Approvals: CE, LR, BV, DNV, ClassNK, RINA, ABS, KRS, CCS

MBT 5252 temperature sensors

Measuring range: -50 – 200 °C

Resistance element: Pt 100

Connection head: B-head

Extension length: 50 mm



Insertion length [mm]	Transmitter output 4 – 20 mA	Transmitter setting 0 – 100 °C	Code Number G ½A	Code Number G ¾A
50	-	-	084Z8210	084Z8230
80	-	-	084Z6140	084Z6164
100	-	-	084Z8211	084Z8231
150	-	-	084Z8212	084Z8232
200	-	-	084Z8213	084Z8233
250	-	-	084Z6139	084Z6141
50	✓	✓	084Z8214	084Z8234
80	✓	✓	084Z6142	084Z6144
100	✓	✓	084Z8215	084Z8235
150	✓	✓	084Z8216	084Z8236
200	✓	✓	084Z8217	084Z8237
250	✓	✓	084Z6143	084Z6145

MBT 5113 Temperature sensor




The MBT 5113 is a heavy-duty temperature sensor that can be used for measuring and regulating exhaust gas from diesel engines, turbines and compressors within stationary and marine applications. This temperature sensor is based on a type K thermo couple, which measures temperatures up to 800 °C. The measuring insert can be changed even while operating the application.

All parts in contact with the media are made of stainless steel AISI 316 Ti. The sensor is delivered with B-head as standard and, if needed, a transmitter (MBT 9110) can be ordered as an integrated part of the sensor.

- With thermocouple up to 800 °C media temperature
- Available with built-in transmitter - with or without Eex ia IIC T4/ T6 approval
- Available with all relevant marine approvals

Dimensions and weight:

*Weight: 0.48 – 1.04 kg
depending on insertion length
and process connection
(excl. transmitter)*



All dimensions in millimetres

Approvals: CE, LR, BV, DNV, GL, Class NK, RINA, ABS, KRS CCS

MBT5113 Temperature sensor

Measuring range: -50 – 800 °C
Measuring element: Thermocouple
Connection head: B-head
Process connection: $\frac{3}{4}$ A

Insertion length [mm]	Transmitter output 4 – 20 mA	Transmitter range 0 – 600 °C	Extension length [mm]	Code number
100	-	-	50	084Z5052
200	-	-	50	084Z5248
100	✓	✓	100	084Z5276
200	✓	✓	100	084Z5277

MBT 5116 Temperature sensors




The MBT 5116 is a heavy-duty temperature sensor that can be used for measuring and regulating exhaust gas from diesel engines, turbines and compressors within stationary and marine applications. This temperature sensor is based on a standardized Pt100 element, which gives a reliable and accurate measurement. The Pt100 element is a thin film element specially designed for heavy-duty applications up to 600 °C.

The measuring insert can be changed even while operating the application. All parts in contact with the media are made of stainless steel AISI 316 Ti. The sensor is constructed to fit where there is limited space.

- Up to 600 °C media temperature
- Can be used with 2- or 3-wire connections
- Robust and compact construction with extremely high resistance to shock and vibration according to IEC 68-2-6
- Easy exchange of measuring insert
- Pt 100 thin film technology specially developed for heavy duty applications
- Can be mounted in all positions
- Solid drilled protection tube
- Available with all relevant marine approvals

Dimensions and weight:

Weight: 0.52 – 1.04 kg
depending on insertion length
and process connection
(excl. transmitter)



All dimensions in millimetres

Approvals: CE, LR, GL, RINA, ABS, BV, DNV, Class NK, KRS, CCS

MBT5116 Temperature sensors

Measuring range: -50 – 600 °C

Measuring element: Pt 100

Extension length: 50 mm

Process connection: $\frac{3}{4}$ A

B-head	Sensor design		Insertion length [mm]	Code number
	Slim-line Pg 9	Slim-line Pg 13.5		
✓			100	084Z5160
✓			200	084Z5025
✓			250	084Z5034
✓			300	084Z5026
	✓		100	084Z3257
	✓		200	084Z3260
	✓		250	084Z3261
	✓		300	084Z3262
		✓	100	084Z8150
		✓	200	084Z8154
		✓	250	084Z8155
		✓	300	084Z8156

Pressure and temperature switches

When it comes to demanding applications, Danfoss' know-how and expertise is unsurpassed. Our robust switches offer flawless performance day after day and are trusted in the most challenging situations in a variety of industries and applications, of which some are mentioned in the following.

Marine and railway equipment

Break down of essential functions in trains and ships due to failures in the controls and safety equipment can be dangerous, very costly and time consuming. These customers therefore choose partners who have a good reputation and superior products to offer, among others:

- Temperature and pressure control and alarm functions in lubrication oil systems – type KPS, CAS and MBC.
- Pressure control for air compressors – type MBC, KP and RT.
- Essential safety control on trains – type RT and CAS.

Water pumps and air compressors

In water pumps and air compressors it is important to keep a constant pressure and a continuous flow. To ensure this Danfoss offers a range of switches for:

- Monitoring and direct start/stop of single or three phase motors – type RT, MBC, CS, CAS and KP/KPI.
- Dry run protection of pumps – type KP/KPI and RT.

Industrial boilers and boiler room equipment

For boilers and in boiler rooms, accurate monitoring of steam/hot water installations, heat exchangers and water treatment equipment for feed water is vital. Danfoss' programme for steam and high-pressure hot water boilers and burners includes:

- Safety approved pressure controls – type BCP and RT.
- Reliable alarm and safety functions – type BCP, RT and KP.



Hydraulic equipment and windmills

Danfoss switches are intended for flawless alarm indication, shut down, control and diagnostics in a variety of demanding applications:

- Cooling and lubrication systems for generators and gear-boxes – type MBC, KPS, KPI, KP, CAS and RT.
- Hydraulic units such as disk brakes and pitch cylinders – type MBC, KPS and RT.
- Power packs – type MBC and KP.

Autoclaves and sterilisers

High control and safety are essential within the autoclave process.

Temperatures and pressures must be controlled within narrow limits over time by products with high repeatability and trustworthy performance:

- Check of door sealing – type KP, BCP and RT.
- Pressure controls of steam supply – type KP, RT and BCP.
- Control and alarm of pressure in the process chamber – type BCP, KP and RT.

Examples



The BCP pressure switch packs all our expertise into a sleek, modern design. The advanced technology built into this durable boiler control sets new standards for reliability - and ensures a long life with a minimum of maintenance.



Marine applications where space and reliability are the most important features are the natural habitat of the MBC 5100 block-type pressure switch. With their high vibration resistance and all common marine approvals, they are trusted at high seas.



On wind turbines, helping to increase the amount of wind-produced power world-wide, the KPS temperature switch provides on-off limits when critical temperatures are reached.

Industrial Switches

In this catalogue

Pressure switches



Type

RT

BCP

KPS

CAS

KP/KPI

CS

Segments

Marine and railway equipment



Industrial boilers and boiler room equipment



Autoclaves and sterilisers



Water pumps and air compressors



Hydraulic equipment



Windmills



Characteristics

Setting range

-1 – 30 bar

0.03 – 40 bar

0 – 60 bar

0 – 60 bar

-0.2 – 28 bar

2 – 20 bar

Contact system

SPDT

SPDT

SPDT

SPDT

SPDT

TPST and SPST

Electrical rating AC-3
Electrical rating AC-15

4 A, 400 V
3 A, 400 V

3 A, 250 V
2 A, 250 V

6 A, 400 V
4 A, 400 V

-
0.1 A, 220 V

16/ 6 A, 400 V
10/4 A, 400 V

12 A, 400 V
-

Electrical connection

Screw terminals

DIN plug

Screw terminals

Screw terminals

Screw terminals

Screw terminals

Contact material

Silver or Gold

Silver or Gold

Gold

Silver

Silver or Gold

Silver

Differential

Adjustable

Adjustable

Adjustable

Fixed

Adjustable

Adjustable

Special approvals

Marine, TÜV

TÜV

Marine, UL

Marine

Marine

Degree of enclosure

IP66 or IP54

IP65

IP67

IP67

IP30, IP44 or
IP55

IP43 or IP55

Design

Box industrial

Box industrial

Box heavy duty

Box heavy duty

Box

Box

Adjustable neutral zone

Yes

Railways and marine

Industrial hydraulics, air compressors and water pumps

Electric power and wind turbines

Boiler and boiler room equipment, sterilisers and autoclaves

Differential pressure switches				Temperature switches			
							
MBC	RT	CAS	MBC	RT	KPS	KP	MBC
							
							
							
							
							
							
-0.2 – 400 bar	0 – 11 bar	0.2 – 2.5 bar	0.3 – 5 bar	-60 – 300 °C	-10 – 200 °C	0 – 150 °C	-10 – 200 °C
SPDT	SPDT	SPDT	SPDT	SPDT	SPDT	SPDT	SPDT
3 A, 250 V 0.5 A, 250 V	4 A, 400 V 3 A, 400 V	- 0.1 A, 220 V	3 A, 250 V 0.5 A, 250 V	4 A, 400 V 3 A, 400 V	6 A, 400 V 4 A, 400 V	16 A, 400 V 10 A, 400 V	3 A, 250 V 0.5 A, 250 V
DIN plug	Screw terminals	Screw terminals	DIN plug	Screw terminals	Screw terminals	Screw terminals	DIN plug
Silver	Silver or Gold	Silver	Silver	Silver or Gold	Gold	Silver	Silver
Fixed	Fixed	Fixed	Fixed	Adjustable	Adjustable	Adjustable	Fixed
Marine	Marine	Marine	Marine	Marine	Marine, UL	Marine, UL	Marine
IP65	IP66	IP67	IP65	IP66 or IP54	IP67	IP30, IP44 or IP55	IP65
Compact	Box industrial	Box heavy duty	Compact	Box industrial	Box heavy duty	Box	Compact
	Yes			Yes			

Discover a variety of built-in benefits



Ongoing development of new technology and new features is at the very heart of Danfoss. We want our switches to be among the very best on the market – living up to your expectations.

1 Adjustable differential switching

Pressure and temperature controls have either fixed or adjustable differential settings, good readability, and high accuracy of range setting with use of the scale.

2 Bellows technology

The lifetime of a pressure and temperature switch is determined by the quality of the bellows. Using advanced technology, and being world leader, Danfoss' bellows are manufactured without any welding points, which makes them stress free and completely tight.

3 Designed for various applications

Danfoss offers a very broad range of purpose-specific enclosures and connections.

4 Snap action contacts

All contacts are "snap-action" types, maintaining the contact force until the moment of contact break. Units with gold-plated contacts are ideal for low electrical loads while the silver-cadmium contacts are developed for high loads.

15 international approvals

Danfoss offers a wide range of approvals suited for different industries and geographical markets.

High vibration stability

Outstanding vibration stability in switches ensures flawless operation even in heavy-duty applications.

Wide pressure ranges

The programme covers working ranges from -1 bar up to 400 bar.

High reliability

All switches feature high accuracy, repeatability and stability over time.

Different temperature sensing elements

As experts in charging technologies Danfoss offers temperature switches that operate in a wide temperature range.

Selection Made Easy

Need help selecting the right component for your application? With only a few clicks, Danfoss product selectors can help you find the right product for standard applications.

Developed to help wholesalers, retailers, installers and end-users pinpoint the solenoid valve needs, the web-based tool makes product selection quick and easy.

All it takes is an internet connection to access the pressure switch selector tool from your desk or laptop, tablet or smart-phone.

To discover just how easy the product selectors are to use, please visit:

<http://switchselector.danfoss.com>

To visit by mobile, scan the QR code:



Pressure and temperature switches – Introduction

Setting range


All Danfoss pressure and temperature switches have a given pressure / temperature range which can be set by the user from a scale on the unit. The given cut-in / cut-out temperature or pressure is indicative only. For accurate setting a thermometer or pressure gauge must be used.

Differential

Differential is a difference between cut-in and cut-out values. It is not recommended to see small differential as it causes system hunting. The bigger differential the less switch over cycles per ahour what benefits in longer life of the contact system.


Contact function, setting for rising pressure / temperature

- RT with maximum reset
- KPI
- KP and BCP with automatic and maximum reset
- KPS (except KPS 31)



Contact function, setting for falling pressure / temperature

- RT with automatic and minimum reset
- KP and BCP with minimum reset
- CAS
- KPS 31



RT pressure switches




RT switches are used in general industrial, heating and marine sectors. The RT single pressure switches series consist of a variety of controls including neutral zone pressure switches and safety pressure switches for steam boiler plant.

RT switches have been in service for more than 70 years.

- Pressure ranges: -1 – 30 bar
- Replaceable contact system
- Also available with gold plated contact systems
- Fail-safe design
- Adjustable differential
- Adjustable neutral zone
- Enclosure IP66
- Available with TÜV approvals
- Available with min. and max. reset function (IP54)
- Also available as differential switch
- Available with all relevant marine approvals

Dimensions and weight:

Weight: Appr. 1 kg



Approvals: CE marked in accordance with EN60947-4/-5. Relevant marine approvals.

RT pressure switches

Contact type: Single pole double throw (SPDT)
Contact material: Silver cadmium oxide (other contact types - see accessories)
Loads: AC-1 ohmic 10A 400V
AC-3 (motor) 4A 400V
AC-15 (inductive) 3A 400V
Ambient temperature: -50 – 70 °C
Media temperature: -40 – 100 °C

RT pressure switches

Pressure connection: G 3/8 A

Type	Setting range P _e [bar]	Mechanical differential [bar]	Max. working pressure P _e [bar]	Reset			Code number
				Auto- matic	Min.	Max.	
RT121	-1 – 0	0.09 – 0.4	7.0	✓			017-521566
RT113 ¹⁾	0 – 0.3	0.01 – 0.05	0.4	✓			017-519666
RT112	0.1 – 1.1	0.07 – 0.16	7.0	✓			017-519166
RT112	0.1 – 1.1	0.07	7.0			✓	017-519266
RT110	0.2 – 3	0.08 – 0.25	7	✓			017-529166
RT200	0.2 – 6	0.25 – 1.2	22	✓			017-523766
RT200	0.2 – 6	0.25	22			✓	017-523866
RT200	0.2 – 6	0.25	22		✓		017-523966
RT116	1 – 10	0.3 – 1.3	22	✓			017-520366
RT116	1 – 10	0.3	22			✓	017-520466
RT116	1 – 10	0.3	22		✓		017-519966
RT116 ²⁾	1 – 10	0.3 – 1.3	22	✓			017-520066
RT5	4 – 17	1.2 – 1.3	22			✓	017-509466
RT5	4 – 17	1.2 – 4	22	✓			017-525566
RT117	10 – 30	1 – 4	42	✓			017-529566

¹⁾Ambient temperature: -10 – 70 °C

²⁾Tamper proof setting knob

RT pressure switches with neutral zone

Pressure connection: G 3/8 A

Type	Setting range P _e [bar]	Mechanical differential [bar]	Adjustable neutral zone [bar]	Max. working pressure P _e [bar]	Code number
RT 200L	0.2 – 6	0.25	0.25 – 0.7	22	017L003266

RT pressure switches for steam plant

Pressure connection: G 1/2 A



Type	Setting range P _e [bar]	Mechanical differential [bar]	Max. working pressure P _e [bar]	Reset			Code number
				Auto- matic	Min.	Max.	

PED approved. For rising pressure. Ambient temperature: -40 – 70 °C

RT112W	0.1 – 1.1	0.07	7	✓			017-528266
RT35W	0 – 2.5	0.1	7	✓			017-528066
RT30AS	1 – 10	0.4	22			✓	017-518966
RT30AB	1 – 10	0.6	22			✓	017-518866
RT30AW	1 – 10	0.8	22	✓			017-518766
RT19B	5 – 25	1.0	42			✓	017-518266
RT19W	5 – 25	1.2	42	✓			017-518166

PED approval. For falling pressure. Ambient temperature: -40 – 70 °C

RT33B	0 – 2.5	0.1	7		✓		017-526266
RT31W	2 – 10	0.3 – 1	22	✓			017-526766
RT31B	2 – 10	0.3	22		✓		017-526866
RT31S	2 – 10	0.3	22		✓		017-526966

All RT pressure switches for steam plant are TÜV approved. Media temperature: -40 – 150 °C

Differential pressure switches

Pressure connection: G 3/8 A



Type	Setting range P _e [bar]	Mechanical differential [bar]	Operation range [bar]	Max. working pressure P _e [bar]	Code number
RT262A	0.1 – 1.5	0.1	-1 – 9	11	017D002566
RT262A	0 – 0.3	0.035	-1 – 10	11	017D002766
RT260A	0.5 – 4	0.3	-1 – 18	22	017D002166
RT260A	0.5 – 6	0.5	-1 – 36	42	017D002366
RT260A	1.5 – 11	0.5	-1 – 31	42	017D002466

Differential pressure switches with adjustable neutral zone

Pressure connection: G 3/8 A



Type	Setting range P _e [bar]	Mechanical differential [bar]	Adjustable neutral zone [bar]	Operation range [bar]	Max. working pressure P _e [bar]	Code number
RT263AL	0.1 – 1	0.05	0.05 – 0.23	-1 – 6	7	017D004566
RT260AL	0.5 – 4	0.3	0.3 – 0.9	-1 – 18	22	017D004866

Spareparts and accessories for RT pressure switches

Type	Version	Description	
Contact system	Standard	Snap action single-pole changeover switch (SPDT) with silver cadmium oxide contact. Fitted in all standard versions of type RT	017-403066
Contact system	Standard	Snap action single-pole changeover switch (SPDT) with gold plated (oxide free) contact surfaces. Increases cut-in reliability on alarm and monitoring systems etc.	017-424066
Contact system	Max reset	Snap action single-pole changeover switch (SPDT) with silver cadmium oxide contact. Designed for RT units performing max reset function.	017-404266
Contact system	Min reset	Snap action single-pole changeover switch (SPDT) with silver cadmium oxide contact. Designed for RT units performing min reset function.	017-404166

Setting knob



Seal cap



Seal screws



Solder nipple



Reducer



Adaptor



Type	Description	
Setting knob	Replacement. Pale grey Ral 7035	017-436366
Seal cap	Seal cap to replace setting knob so that setting can only be altered with tools (tamper proof seal cap). Black	017-436066
Screws	Seal screws for cover and seal cap	017-425166
Solder nipple	Pipe thread ISO 228/1, G 3/8 connector, nipple and AL washer (10 mm ext. / 8 mm int. diam). for soldering onto steel or copper tubing. Steel span of jaws: 22	017-436866
Reducer	Pipe thread ISO 228/1, G 1/2 A x G 3/8, steel, span of jaws 22	017-421966
Reducer	Pipe thread ISO 228/1, G 3/8 x 7/16 - 20 UNF reducer, washer, brass, span of jaws 22	017-420566
Adaptor	Pipe thread ISO 228/1, G 3/8 A x R 3/8 (ISO 7/1) brass, span of jaws 17	060-324166

Damping coil, 7/16 - 20 UNF connectors



Damping coil, G 3/8 connectors



Damping coil, armoured



Air bell for liquid level control



Type	Description	
Damping coil	1 m. damping coil with 7/16 - 20 UNF connectors. Reducer code no 017-420566 is necessary if the damping coil is to be used with RT units with pipe thread: ISO 228/1, G 3/8 connection.	060-019166
Damping coil	Pipe thread ISO 228/1, damping coil with G 3/8 connector and 1.5 m copper capillary tube. Standard washers are supplied	060-104766
Armoured damping coil	Pipe thread ISO 228/1, damping coil with G 3/8 connector and 1 m. copper capillary tube. Standard washers are supplied	060-333366
Air bell for liquid level control	Air bell for liquid level control RT113. 62 mm diam. ext x 204 mm length. Pipe thread ISO 228/1, G 3/8 connector and nipple (10 mm o.d./6.5 mm i.d.) for welding or brazing on to steel or copper tubing. Brass.	017-401366

The BCP pressure switch for reliable boiler control

A series of dedicated pressure switches, BCPs control, monitor and limit the pressure in steam and hot water boilers. Simple to install and operate, BCP pressure switches combine advanced technology, durability and design to provide failsafe boiler operation.

Fluid temperature

The BCP can cope with fluid temperatures up to 120 °C. For temperatures above 120°C, a water-filled loop must be installed.

Pressure range from 0 to 40 bar

The BCP is designed to handle a wide pressure range from low pressure BCP1 with a narrow differential, to high pressure BCP7.

Plug and play (DIN 43650)

A DIN 43650 plug and an external reset – operated by a screwdriver – makes electrical installation and operation easy.

Manual reset with a standard screwdriver

All BCP pressure switches are available with an automatic reset for boiler operations, or a manual reset to be used as a safety limit switch.

Failsafe versions

For added safety, dual bellows enable an off function (safety cut-out) if a fault occurs.

Approvals


The BCP range is CE-marked in accordance with EN 60730-1, VdTÜV-Merkblatt Druck 100 TÜV. SDWFS/SDBFS. 08 – 335 and PED 97/23/ED, category IV, safety equipment. It is tested according to EN12952-11 and EN12953-9.

Bracket for wall and DIN rail mounting

The BCP can be directly mounted on the pressure connection or wall mounted with a bracket.

User friendly

- Easy external adjustment of the pressure setting and pressure differential
- Separate scales for pressure setting and differential setting



BCP pressure controller / pressure limiter




The BCP type is a series of dedicated pressure switches for control, monitoring and safety of steam and hot water boilers. The BCP incorporates a single-pole changeover microswitch where the contact position depends on the pressure in the connection port and the range set value. For installations, in which operation is particularly critical for safety reason, the use of fail-safe control is recommended.

- Available as high and low pressure limiters as well as pressure controllers
- Wide pressure range: from low pressure BCP1 with narrow differential to high pressure BCP7
- The fail-safe dual bellows enable premature cut-out when fault occurs
- Din plug mounted on the top of control for easy electrical wiring
- Single-pole changeover switch (SPDT), switch + alarm
- Direct mounting on pressure connection or wall mounting by means of a bracket
- Versions with automatic and manual resets available
- Screw adjustments made on top of housing
- Manual reset for pressure limiters possible only by means of tools
- Version with gold plated contact for electronic devices

Dimensions and weight:

Weight: 0.5 kg



Dimensions in millimetres

Approvals: CE marked in accordance with EN60730-1 and PED 97/23.

BCP pressure controller/ pressure limiter

Contact type:	Single pole double throw (SPDT)
Contact material:	Gold plated silver. <i>(On request silver cadmium oxide is available for higher loads)</i>
Loads:	AC-1 (ohmic) 6A 250V AC-15 (inductive) 1 A 250V
Pressure connection:	G $\frac{1}{2}$ A
Enclosure:	IP65
Ambient temperature:	-20 – 70 °C
Media temperature:	Up to 120 °C



BCP pressure controller, automatic reset

Type	Setting range P _e [bar]	Differential [bar]	Max. working pressure P _e [bar]	Max. test pressure P _e [bar]	Code number
BCP1	0.1 – 1.1	0.15 – 0.6	6	7	017B0002
BCP2	0 – 2.5	0.4 – 1	10	11	017B0006
BCP3	0 – 6	0.7 – 1.4	16	18	017B0010
BCP4	1 – 10	1 – 2.5	25	28	017B0014
BCP5	2 – 16	2 – 3.2	32	35	017B0018
BCP6	5 – 25	2.5 – 4	40	45	017B0022
BCP7	10 – 40	3 – 6	63	70	017B0026



BCP pressure limiter


Type	Setting range P _e [bar]	Differential [bar]	Max. working pressure P _e [bar]	Max. test pressure P _e [bar]	Code number
For falling pressure, minimum reset					
BCP2L	0 – 2.5	0.2	10	11	017B0058
BCP3L	0 – 6	0.4	16	18	017B0062
BCP4L	1 – 10	0.45	25	28	017B0066
BCP5L	2 – 16	1.2	32	35	017B0070
BCP6L	5 – 20	1.2	40	45	017B0074

For rising pressure, maximum reset

BCP1H	0.1 – 1.1	0.1	6	7	017B0030
BCP2H	0 – 2.5	0.2	10	11	017B0034
BCP3H	0 – 6	0.4	16	18	017B0038
BCP4H	1 – 10	0.45	25	28	017B0042
BCP5H	2 – 16	1.2	32	35	017B0046
BCP6H	5 – 25	1.5	40	45	017B0050
BCP7H	10 – 40	2.3	63	70	017B0054

Spareparts for BCP pressure switch

Description	Code numbers
Bracket for wall mounting	017B1018
Bracket for 35 mm rail mounting	017B1019



For wall mounting

For 35 mm rail mounting

KPS heavy-duty pressure switches





In the KPS series, special attention has been given to meeting important demands for a high level of enclosure, a robust, compact construction and resistance to shock and vibration. The KPS range covers most outdoor as well as indoor application requirements, and are suitable for use in alarm and regulation systems in factories, diesel plant, compressors, powerstation and on board ships.

- Pressure ranges: 0 – 60 bar
- Gold plated contact systems
- Adjustable or fixed differential
- Robust and compact construction
- Resistance to shock and vibrations
- Diaphragm version for applications with: Pulsations/pressure peaks
- Also sea water as media
- Enclosure IP67. Sturdy and sea water resistant.
- Available with all relevant marine approvals

Dimensions and weight:

Weight:
KPS 31 – 39: 1.0 kg
KPS 43 – 47 1.3 kg



Dimensions in millimetres

Approvals: CE marked in accordance with EN60947-4/-5. UL E73170. All relevant marine approvals

KPS heavy-duty pressure switches

Contact type: Single pole double throw (SPDT)
Contact material: Gold plated silver
Loads: AC-1 (ohmic) 10A 440V
 AC-3 (motor) 6A 440V
 AC-15 (inductive) 4A 440V
Enclosure: IP67



Type	Setting range	Differential	Max. working pressure	Connection size		Code number
	P _e [bar]	[bar]	P _e [bar]	G ¼ A	G ¾ A	

Controls for low and medium pressure. Ambient temperature: -40 – 70 °C. Media temperature: -40 – 100 °C.

KPS31	0 – 2.5	0.1	6		✓	060-310966
KPS31	0 – 2.5	0.1	6	✓		060-311066
KPS33	0 – 3.5	0.2	10		✓	060-310366
KPS33	0 – 3.5	0.2	10	✓		060-310466
KPS35	0 – 8	0.4 – 1.5	12		✓	060-310066
KPS35	0 – 8	0.4 – 1.5	12	✓		060-310566
KPS35	0 – 8	0.4	12	✓		060-310866
KPS37	6 – 18	0.85 – 2.5	22		✓	060-310166
KPS37	6 – 18	0.85 – 2.5	22	✓		060-310666
KPS39	10 – 35	2 – 6	45		✓	060-310266
KPS39	10 – 35	2 – 6	45	✓		060-310766


Controls for high pressure and strongly pulsating media. Ambient temperature: -25 – 70 °C. Media temperature: -25 – 100 °C.

KPS43	1 – 10	0.7 – 2.8	120	✓		060-312066
KPS45	4 – 40	2.2 – 11	120	✓		060-312166
KPS47	6 – 60	3.5 – 17	120	✓		060-312266

Spareparts for KPS



Description	Code numbers
Reducer. G ¾ x 7/16 - 20 UNF (¼ flare) reduction with washer	017-420566
Adaptor G ¾ A x ¼ - 18 NPT with washer	060-333666
Nipple G ¼ A x G ¾ A	060-333266
Damping coil with ¼ flare connectors and 1 m copper capillary tube. Damping coils used for applications with ¾ RG connector requires the use of reducer.	060-007166
Damping coil with G ¾ connectors and 1.5 m copper capillary tube	060-104766
Armoured damping coil with ¾ connectors and 1 m armoured capillary tube. Standard washers included.	060-333366



CAS heavy-duty pressure switches



In the CAS pressure switches series, special attention has been given to meeting demands for a high level of enclosure, low differential, robust, compact construction and resistance to shock and vibration. The CAS series covers most outdoor as well as indoor application requirements. CAS pressure switches are suitable for use in alarm and regulation systems in factories, diesel plant, compressors, power stations and on board ships.



- Pressure ranges: 0 – 60 bar
- Low differential (fixed) micro switch
- Enclosure IP67. Sturdy and sea water resistant
- Robust and compact construction
- Resistance to shock and vibrations
- Diaphragm version applications with: Pulsations/pressure peaks and seawater as media
- Also available as differential pressure switch
- Available with all relevant land and marine approvals

Dimensions and weight:

Weight:

CAS 133 – 139 1.0 kg.

CAS 143 – 147 1.3 kg.



All dimensions in millimetres

Approvals: CE marked in accordance with EN 60947-5. All relevant land and marine approvals.

CAS Heavy-duty pressure switches with pipe thread connection

Contact type: Single pole double throw (SPDT)

Loads: AC-1 (ohmic)
AC-3 (motor)
AC15 (inductive) 0.1 A 220V

Pressure connection: G 1/4 A



Type	Setting range P_e [bar]	Differential [bar]	Max. working pressure P_e [bar]	Code number
------	------------------------------	-----------------------	--------------------------------------	-------------

Ambient temperature: -40 – 70 °C. Media temperature: -40 – 100 °C.

CAS133	0 – 3.5	0.1	10	060-315066
CAS136	0 – 10	0.2	22	060-315166
CAS137	6 – 18	0.3	27	060-315266
CAS139	10 – 35	0.6	53	060-315366

CAS pressure switches for high pressure and strongly pulsating media

Ambient temperature: -25 – 70 °C. Media temperature: -25 – 100 °C.

CAS143	1 – 10	0.2 – 0.6	120	060-316066
CAS145	4 – 40	0.8 – 2.4	120	060-316166
CAS147	6 – 60	1 – 3	120	060-316266

CAS differential pressure switch


Pressure connection: 2 x G 1/4. Ambient temperature: -25 – 70 °C



Type	Setting range P_e [bar]	Differential [bar]	Max. working pressure P_e [bar]	Code number
------	------------------------------	-----------------------	--------------------------------------	-------------

CAS155	0.2 – 2.5	0.1	0 – 8	060-313066
--------	-----------	-----	-------	------------

Spare parts for CAS pressure switch



Description	Code numbers
Connector with nipple. Pipe thread ISO 228/1, G 3/8 connector, nipple and AL washer (10 mm ext. / 8 mm int. diam). for soldering onto steel or copper tubing. Steel span of jaws: 22	017-436866
Connector with nipple. G 3/8 connector nipple and washer (10 mm ext. / 6.5 mm int. diam). For welding. Steel span of jaws: 22	017-422966
Reducer. G 3/8 x 7/16 - 20 UNF (1/4 flare) reduction with washer	017-420566
Adaptor G 3/8 A x 1/4 - 18 NPT with washer	060-333666
Nipple G 1/4 A x G 3/8 A	060-333266
Damping coil with G 3/8 connectors and 1.5 m copper capillary tube	060-104766
Armoured damping coil with 3/8 connectors and 1 m armoured capillary tube. Standard washers included.	060-333366



The KPI pressure switch for liquid and gaseous media

Designed to control and monitor industrial application systems, the KPI is a compact and robust solution that offers safety and longevity.

Wide setting range

Available in pressure ranges from -0.2 – 28 bar, there is a KPI with the pressure setting you require.

Pressure control for most industrial applications

Easy and stable setting values make it easy to control liquid and gaseous media in most industrial applications, e.g. pumps and compressors

Easy to install

The small dimensions of the KPI saves space and makes it easy to install.

Shock and impact resistant

Vibration-proof from 0 – 1000 Hz, 4g (1g = 9.81 m/s²), the KPI is ideal for mobile applications where shock and strokes occur.

Ultra-short bounce times

The perfect Single Pole Double Throw (SPDT) snap-function minimises wear during each operation and extends contact life.

Cable entry for 6 – 14 mm diameter cables


Two cable entries on the front of the pressure switch provide a number of possible electrical cable connections.

High contact load

The SPDT's silver contacts can cope with loads up to 16A, 400V AC3. And gold contacts are also available to ensure perfect function with low electrical loads.

Longevity

On average, the KPI can perform more than 400,000 electrical operations during its lifetime, which is four times more than approval requirements.



KPI pressure switches for light industry




Danfoss KPI pressure switches are used for control, monitoring and alarm systems in industrial applications. The KPI series are suitable for plant in connection with liquid and gaseous media. They are fitted with a single-pole switch changeover (SPDT).

- Pressure ranges: -0.2 – 28 bar
- High contact load
- Ultra short bounce-time
- Available with gold plated contact systems
- Adjustable differential
- Scale for setting of range and differential
- Enclosure IP44 when mounted with top cover and back plate
- Snap action contact system with omega spring

Dimensions and weight:

Weight: 0.3 kg



All dimensions in millimetres

Approvals: CE marked in accordance with EN60947-4/-5. Electrical safety certificate - FM. UL E31024.

KPI pressure switches for light industry with pipe thread connection

Contact function:	Single pole double throw (SPDT)
Contact material:	Silver cadmium oxide
Loads:	AC-1 ohmic 10A 440V AC-3 (motor) 6A 440V AC-15 (inductive) 4A 440V
Reset:	Automatic
Pressure connection:	G 1/4A
Ambient temperature:	-40 – 65 °C
Media temperature:	-40 – 100 °C
Enclosure:	IP30, IP33 when wall mounted, IP44 with top plate




Type	Setting range P _e [bar]	Differential [bar]	Max. working pressure P _e [bar]	Code number
KPI 35	-0.2 – 8	0.4 – 1.5	18	060-121766
KPI 35 ¹⁾	-0.2 – 8	0.4 – 1.5	18	060-316466
KPI 35	-0.2 – 8	0.5 – 2	18	060-121966
KPI 36	2 – 12	0.5 – 1.6	18	060-316966
KPI 36 ¹⁾	4 – 12	0.5 – 1.6	18	060-113866
KPI 36	2 – 12	0.5 – 1.6	18	060-319366
KPI 36	4 – 12	0.5 – 1.6	18	060-118966
KPI 38	8 – 28	1.8 – 6	30	060-508166

¹⁾ Contact material: Gold plated silver

Spareparts and accessories for KPI pressure switch

Type	Description	Code numbers
Wall bracket	Mounting screw and washers included	060-105566
Angle bracket	Mounting screw and washers included	060-105666
Seal screw for locking plate	Seal screw according to DIN 405, for locking of setting point	060-105766
Screwed cable entry	Pg 13.5 with special nut. For 6 – 14 mm diameter cables	060-105966
Top cover	For single control. If a wall or angle bracket is mounted on the backplate of the housing, the KP will have an IP44 grade of enclosure by means of this cover	060-109766
IP55 enclosure	For single control. Specially designed IP55 enclosure, not transparent	060-033066

Brackets



For wall mounting



For 35 mm rail mounting




Seal screw




Screwed cable entry



Top cover



IP55 enclosure



KP pressure switches for light industry




Danfoss KP pressure switches are used for control, monitoring and alarm systems in industrial applications.

The KP series are suitable for gaseous media and air. They are fitted with a single-pole switch changeover (SPDT), and can control single-phase ac motors of up to 2 kW directly.

- Pressure ranges: -0.2 – 21 bar
- High contact load - Ultra short bounce-time
- Also available with gold plated contact systems
- Media: Gaseous media and air
- Enclosure IP44 when mounted with top cover and back plate
- Small dimensions - space saving - easy to install

Dimensions and weight:

Weight: 0.34 kg



KP 35 and KP 36

All dimensions in millimetres

Approvals: CE marked in accordance with EN60947-4/-5. Electrical Safety Certificate - FM. UL E31024. Relevant marine approvals.

KP pressure switches for light industry with pipe thread connection

Contact system: Single pole double throw (SPDT)
Contact material: Silver cadmium oxide
Loads: AC-1 ohmic 16A 400V
AC-3 (motor) 16A 400V
AC-15 (inductive) 10A 400V
Reset function: Automatic
Ambient temperature: -40 – 65 °C
Media temperature: -40 – 100 °C



Type	Setting range P _e [bar]	Differential P _e [bar]	Max. working pressure P _e [bar]	Enclosure	Code number
Pressure connection: G 1/4A					
KP2	-0.2 – 3.5	0.3 – 1.0	10	IP30	060-131866
KP35	-0.2 – 7.5	0.7 – 4	17	IP30	060-113366
KP35	-0.2 – 7.5	0.7 – 4	17	IP55	060-538666
KP35 ¹⁾	-0.2 – 7.5	0.7 – 4	17	IP30	060-504766
KP36 ¹⁾	2 – 14	0.7 – 4	17	IP30	060-113766
KP36	2 – 14	0.7 – 4	17	IP30	060-110866
KP36	2 – 14	0.7 – 4	17	IP55	060-538766
KP36 ¹⁾	4 – 12	0.5 – 1.6	17	IP30	060-114466
KP36	4 – 12	0.5 – 1.6	17	IP30	060-122166

¹⁾ Contact material: Gold plated silver

KP pressure switches for boilers

Contact system: Single pole double throw (SPDT)
Contact material: Silver cadmium oxide
Loads: AC-1 (ohmic) 16 A 400 V
AC-3 (motor) 16 A 400 V
AC-15 (inductive) 10 A 400 V
Reset function: Manual or Automatic
Ambient temperature: -40 – 65 °C
Media temperature: - 40 – 100 °C
Pressure connection: G1/2 A
Enclosure: IP30, IP33 when wall mounted, IP44 with top plate




Type	Setting range P _e [bar]	Differential P _e [bar]	Max. working pressure P _e [bar]	Reset	Code number
KP 34	0.1 – 1	0.1 – 4	4.0	Automatic	060-216466
KP 34	0.1 - 1	0.2 fixed	4.0	Manual	060-216366
KP 35	0.4 – 3.4	0.4 – 2.2	10	Automatic	060-216666
KP 35	0.4 – 3.4	0.5 fixed	10	Manual	060-216566
KP36	1 – 10	0.7 – 4	17	Automatic	060-215966
KP 36	1 - 10	0.7 fixed	17	Manual	060-216066
KP 37	4 – 20	1.8 – 3.1	28	Automatic	060-216166
KP 37	4 – 20	3.0 fixed	28	Manual	060-216266

Spareparts and accessories for KP pressure switch

Type	Description	
Wall bracket	Mounting screw and washers included	060-105566
Angle bracket	Mounting screw and washers included	060-105666
Seal screw for locking plate	Seal screw according to DIN 405, for locking of setting point	060-105766
Screwed cable entry	Pg 13.5 with special nut. For 6 – 14 mm diameter cables	060-105966
Top cover	For single control. If a wall or angle bracket is mounted on the backplate of the housing, the KP will have an IP44 grade of enclosure by means of this cover	060-109766
IP55 enclosure	For single control. Specially designed IP55 enclosure , not transparent	060-033066

Brackets



For wall mounting



For 35 mm rail mounting




Seal screw




Screwed cable entry




Top cover



IP55 enclosure



The CS pressure switch for excellent pressure control



Designed for air compressors and water pump applications, the CS pressure switch has a built-in, pressure-operated three-pole contact system. Made for the direct start of pumps and as on/off functions in control circuits, the CS switch is robust and reliable.

Adjustable range and differential

The CS switch can be adjusted to suit a variety of working conditions and pressures, ranging from 2 – 20 bar.

Special compressor application accessory

To prevent air compressors starting under load, a pressure relief valve can be used with the CS switch to relieve pressure on the compressor piston.

Robust and tight

Enclosed in heavy-duty plastic, the CS switch is available in IP43 or IP55 versions to ensure high performance in wet or dusty environments.

Safe and reliable

For added safety in the event of system failure or maintenance purposes, the CS is fitted with a manual switch to lock the contact system in the open position, independent of the pressure in the system.

CS pressure switches for air and water




CS pressure switches have a three-pole switch and adjustable differential.

The pressure switches are fitted with a manual switch that will lock the contact system in the open position independently of the pressure in the system.

- For automatic start and stop of air compressors and water pumps
- Pressure ranges: 2 – 20 bar
- Contact system: 3-pole (standard) and 1-pole (accessory)
- Adjustable differential from 0.7 – 7 bar
- Manual switch to lock the contact system
- Relief valve (accessory)
- Enclosure IP43 or IP55
- Versions for drinking water

Dimensions and weight:

Weight: 0.5 kg



All dimensions in millimetres

Approvals: CE according to EN 60947-4-5

CS pressure switches

Contact function: Triple pole single throw (TPST)
Contact material: Silver cadmium oxide
Loads: AC-3 12A 220 – 415V
 9A 600V
Ambient temperature: -20 – 70 °C
Media temperature: Water: 0 – 70 °C
 Air: -20 – 70 °C



Setting range P _e [bar]	Factory setting P _e [bar]	Min. differential [bar]	Max. differential [bar]	Max. working pressure P _e [bar]	Connection size		Enclosure	Code number
					G ¼ A	G ½ A		
2 – 6	4	0.72 – 1	1 – 2	6	✓		IP43	031E020066
2 – 6	4	0.72 – 1	1 – 2	6	✓		IP55	031E020566
2 – 6	4	0.72 – 1	1 – 2	6		✓	IP43	031E021066
2 – 6	4	0.72 – 1	1 – 2	6		✓	IP55	031E021566
4 – 12	4	1 – 1.5	2 – 4	12	✓		IP43	031E022066
4 – 12	4	1 – 1.5	2 – 4	12	✓		IP55	031E022566
4 – 12	4	1 – 1.5	2 – 4	12		✓	IP43	031E023066
4 – 12	4	1 – 3	2 – 4	12		✓	IP55	031E023566
7 – 20	7	2 – 3.5	3.5 – 7	20	✓		IP55	031E024566
7 – 20	7	2 – 3.5	3.5 – 7	20		✓	IP43	031E025066
7 – 20	7	2 – 3.5	3.5 – 7	20		✓	IP55	031E025566



Contact function: SPST

Setting range P _e [bar]	Min. differential [bar]	Max. differential [bar]	Max. working pressure P _e [bar]	Connection size G ¼ A	Enclosure	Code number
2 – 6	0.72 – 1	1 – 2	6	✓	IP43	031E020266

Spareparts for CS pressure switch

Description	Code number
Three pole contact system TPST	031E029166
Pressure relief valve, incl. fixing screw for 6 mm pipe/hose	031E029866
Pressure relief valve, incl. fixing screw for ¼ in. pipe/hose	031E029766
Two Pg 16 screwed cable entries with gaskets, cable diam. 6.5 – 15 mm	031E029366
Nipple with 7/16 - 20 UNF and M10 x 1 int.	031E029666

TPST contact system



Pressure relief valve



Screwed cable entries

Nipple

MBC 5100 block-type compact pressure switches




MBC pressure switches are used in industry and marine applications where space and reliability are the most important features. MBCs are compact pressure switches, designed according to our new block design to survive in the harsh conditions known from machine rooms onboard ships. MBCs have high vibration resistance and feature all commonly marine approvals. The fixed, but low differential guarantees accurate monitoring of critical pressures. MBV test valves can be delivered as standard option for MBC pressure switches.

- All relevant marine approvals
- Pressure ranges: -0.2 – 400 bar
- Low differential (fixed) micro switch
- Resistant to shock and vibrations
- Enclosure IP65
- Diaphragm version for applications with pulsations/pressure peaks
- Compact design
- Low installations costs
- Fast and easy to operate
- Easy to mount on block test valve
- Available as differential pressure switch

Dimensions and weight:

Weight: 0.4 kg.



All dimensions in millimetres

Approvals: CE marked in accordance with EN60947-5. All relevant marine approvals

MBC 5100 block-type compact pressure switches

Contact function: Single pole double throw (SPDT)

Contact material: Silver

Loads: AC-1 (ohmic) 10A, 250V

AC-3 (motor) 3A, 250V

AC-15 (inductive) 0.5A, 250V

Plug Pg 11. Other electrical connections available on request



Setting range P _e [bar]	Min. differential setting [bar]	Max differential setting [bar]	Max. working pressure P _e [bar]	Connection		Code number
				G ¼ A	Flange	
Low pressure bellows. Ambient temperature: -40 to 85 °C						
-0.2 – 1	0.15	0.45	15	✓	✓	061B000566
-0.2 – 4	0.15	0.45	15	✓	✓	061B000466
-0.2 – 4	0.15	0.45	15	✓		061B001066
-0.2 – 10	0.15	0.6	15	✓	✓	061B000266
Low pressure diaphragm. Ambient temperature: -10 to 85 °C						
1 – 10	0.30	2.5	150	✓	✓	061B100466
1 – 10	0.30	2.5	150	✓		061B100866
5 – 20	0.4	2.5	150	✓	✓	061B100266
High pressure diaphragm. Ambient temperature: -10 to 85 °C						
5 – 40	1.0	7	150	✓	✓	061B100566
10 – 100	1.7	14	150	✓	✓	061B100366
High pressure piston. Ambient temperature: -40 to 85 °C						
16 – 160	12	30	600	✓		061B510066
25 – 250	12	40	600	✓		061B510166
40 – 400	15	50	600	✓		061B510266

MBC 5180 block-type differential pressure switch



Setting range P_e [bar]	Operating range LP side P_e [bar]	Max. working pressure P_e [bar]	Connection		Code number
			G ¼ A	G ¼ A w. flange	
0.3 – 5	0 – 30	45		✓	061B128066
0.3 – 5	0 – 30	45	✓		061B129066

Spareparts for MBC5100

Type	Description	
Pulse-snobber	Male, G ¼A, length 20 mm	061B400101
Pulse-snobber	Male, G ¼A, length 34 mm	061B400201
Pulse-snobber	For flange connection	061B722101



Pulse snubber
20 mm



Pulse snubber
34 mm



Pulse snubber for
flange connection

MBV 5000 pressure test valve



The MBV 5000 is a part of a block concept covering block pressure switches, block pressure transmitters, block test valves and accessories.

The block concept has been developed to save space, weight, and costs and meet the strict demands on marine equipment, including EU stipulations on such products.


MBV 5000 is designed in many different configurations for use in many different marine applications, for example: Monitoring, alarm indication, shut-down, diagnosing on equipment such as motors, gears, thrusters, pumps, filters, compressors, etc.

The block valve meets demands for fast installation, simple isolation, and easy test pressure connection.

- The MBV block valves designed in many configurations are for use with the MBC pressure switch or the MBS block pressure transmitter within the marine industry
- The valve meets demands for fast installation, simple isolation and easy test pressure connection

Dimensions and weight:

Weight: 0.4 – 2.0 kg



All dimensions in millimetres

MBV 5000 pressure test valve

Max working pressure, liquid media: 180 bar P_e / gaseous media: 120 bar P_e

Ambient temperature: -20 – 120 °C

Media temperature: -20 – 120 °C




Type	Output no.	Length [mm]	Weight [kg]	Code number
MBV5000-1111	x1	36	0.4	061B7000
MBV5000-1211	x2	76	0.8	061B7001
MBV5000-1311	x3	116	1.2	061B7002
MBV5000-1411	x4	156	1.6	061B7003
MBV5000-1511	x5	196	2.0	061B7004
MBV5000-2211	x2	76	0.8	061B7005
MBV5000-2311	x3	116	1.2	061B7006
MBV5000-2411	x4	156	1.6	061B7007
MBV5000-2511	x5	196	2.0	061B7008
MBV5000-3211	x2	76	0.7	061B7009
MBV5000-3311	x3	116	1.0	061B7010
MBV5000-3411	x4	156	1.3	061B7011
MBV5000-3511	x5	196	1.6	061B7012

Spareparts for MBV 5000

Standard flange - G 1/8 adapters

Description	Code number
Cover	061B720001
Angleway adapter	061B720101
Straightway adapter	061B720201



RT temperature switches for temperature regulation



Suitable for a wide range of demanding industrial applications, RT temperature switches are designed to maintain a specific temperature difference between two media.

Wide regulating range

The RT has a wide temperature regulating range from $-60 - 300^{\circ}\text{C}$. Precise scales make it easy to set the temperature range and differential.

Variety of sensors and functions

An IP66 enclosure and a range of sensor types – such as capillary tube sensors, room sensors and duct sensors – enable neutral zone adjustment and manual reset functions.

Contact systems

RT temperature switches are available with standard contact systems for 3A, 400V AC15 loads and 4A, 400V AC3. Special contact versions are also available as spare parts.

Ultra-short bounce times

The perfect Single Pole Double Throw (SPDT) snap function minimises wear during each operation and extends the contact life.

Cable entry for 6-14 mm diameter cables

Two cable entries provide a number of possible electrical cable connections.

Longevity

The RT has a mechanical lifetime of one million cycles over the full temperature range, and an electrical lifetime of 100,000 cycles at maximum load.

RT temperature switches




RT controls are used in general industrial and marine sectors. The RT temperature switch series consist of a variety of room temperature switches and remote sensor temperature switches including neutral zone temperature switches. RT temperature switches are generally recommended for applications where safety or economical consequences are critical factors. RT controls have been in service for more than 70 years.

- Temperature range: -60 – 300 °C
- Replaceable contact system
- Also available with gold plated contact systems
- Adjustable differential
- Enclosure IP66
- Available with external max. reset function (IP54)
- Available with dead zone
- Available with all relevant marine approvals

Dimensions and weight:

Weight: Appr. 1 kg



All dimensions in millimetres

Approvals: CE marked in accordance with EN60947-4/-5. Relevant marine approvals

RT temperature switches - remote sensor with capillary tube

Contact function: Single pole double throw (SPDT)
Contact material: Silver cadmium oxide (other contact material - see accessories)
Loads: AC-1 ohmic 10A 400V
AC-3 (motor) 4A 400V
AC-15 (inductive) 3A 400V
Ambient temperature: -50 – 70 °C
Media Temperature: -40 – 100 °C



Type	Setting range [°C]	Adjustable differential range		Max sensor temperature [°C]	Capillary tube length [m]	Code number
		at lowest setting [°C]	at highest setting [°C]			

Reset: Automatic. Enclosure: IP66

RT14	-5 – 30	2 – 8	2 – 10	150	2	017-509966
RT106	20 – 90	4 – 20	2 – 7	120	2	017-504866
RT101	25 – 90	2.4 – 10	3.5 – 20	300	2	017-500366
RT101	25 – 90	2.4 – 10	3.5 – 20	300	3	017-500666
RT101	25 – 90	2.4 – 10	3.5 – 20	300	5	017-502266
RT108	30 – 140	5 – 20	4 – 14	220	2	017-506066
RT107	70 – 150	6 – 25	1.8 – 8	215	2	017-513566
RT107	70 – 150	6 – 25	1.8 – 8	215	3	017-513966
RT107	70 – 150	6 – 25	1.8 – 8	215	5	017-514066
RT120	120 – 215	7 – 30	1.8 – 9	260	2	017-520866
RT123	150 – 250	6.5 – 30	1.8 – 9	300	2	017-522066
RT124	200 – 300	5 – 25	2.5 – 10	350	2	017-522766

Reset: Max. Enclosure: IP54

RT101	25 – 90	2.4	4.1	300	2	017-500466
RT107	70 – 150	6	1.8	215	2	017-513666
RT107	70 – 150	6	1.8	215	5	017-514166
RT120	120 – 215	7	1.8	260	2	017-521466
RT123	150 – 250	6.5	1.8	300	2	017-522466
RT124	200 – 300	5	2.5	350	2	017-523166

RT temperature switches - room sensor

Enclosure: IP66



Type	Setting range [°C]	Adjustable differential range		Max sensor temperature [°C]	Code number
		at lowest setting [°C]	at highest setting [°C]		
RT4	-5 – 30	1.5 – 7	1.2 – 4	75	017-503666
RT103	10 – 45	1.3 – 7	1 – 5	100	017-515566
RT34	-25 – 15	2 – 10	1 – 12	100	017-511866
RT16L ¹⁾	0 – 38	1.5 – 5	0.7 – 1.9	100	017L002466

¹⁾ Neutral zone setting: 0.7 – 1.5 bar

RT temperature switches - duct sensor

Enclosure: IP66



Type	Setting range [°C]	Adjustable differential setting range		Max sensor temperature [°C]	Capillary tube length [m]	Code number
		at lowest setting [°C]	at highest setting [°C]			
RT140	15 – 45	1.8 – 8	2.5 – 11	240	2	017-523666

Spareparts and accessories for RT temperature switches

Sensor pockets with stuffing box

Type / application	Sensor length [mm]	Pocket material		Pocket dimensions			Code number
		Brass	18/8 steel	L [mm]	d [mm]		
RT120, RT101, RT14, RT107, RT123	80	✓		112	11		017-437066
RT120, RT101	80/97		✓	112	11		017-436966
RT14	150	✓		182	11		017-436766
RT108	410	✓		465	11		017-421666
RT106	76	✓		110	15		060L333066

Type	Version	Description	
Contact system	Standard	Single-pole changeover switch (SPDT) with terminal board proof against leakage current. Fitted in all stand versions of type RT	017-403066
Contact system	Standard	Single-pole changeover switch (SPDT) with gold plated (oxide free) contact surfaces. Increases cut-in reliability on alarm and monitoring systems etc.	017-424066
Contact system	Max reset	Snap action single-pole changeover switch (SPDT) with silver cadmium oxide contact. Designed for RT units performing max reset function.	017-404266

Type	Description	
Setting knob	Replacement. Pale grey Ral 7035	017-436366
Seal cap	Seal cap to replace setting knob so that setting can only be altered with tools (tamper proof seal cap). Black	017-436066
Screws	Seal screws for cover and seal cap	017-425166
Stuffing box kit	For all thermostats with remote sensor. G 1/2A (pipe thread ISO228/1), oil resistant rubber washer for max 110 °C/90 bar	017-422066
Stuffing box kit	For all thermostats with remote sensor. G 3/4A (pipe thread ISO228/1), oil resistant rubber washer for max 110 °C/90 bar	003N0155
Sensor clip	For all RT units with remote sensor. L = 76 mm	017-420366
Heat conductive compound	For RT thermostats with the sensor insert in a pocket. Tube with 3.5cm ³ compound to be filled in the sensor pocket to improve heat transfer between pocket and sensor. Application range for compound: -20 – 150 °C, momentarily up to 220 °C.	041E0114



KPS temperature switches




In the KPS thermostats series, special attention has been given to meeting important demands for a high level of enclosure, a robust, compact construction and resistance to shock and vibration. The KPS range covers most outdoor as well as indoor application requirements, and are suitable for use in monitoring, alarm and regulation systems in factories, diesel plant, compressors, powerstation and on board ships.


- Temperature setting ranges: -10 – 200 °C
- Gold plated contact systems
- Adjustable or fixed differential
- Robust and compact construction
- Resistance to shock and vibrations
- Enclosure IP67. Sturdy and sea water resistant.
- Available with all relevant marine approvals

Dimensions and weight:


Weight: 1.0 – 1.4 kg



Weight:
Including 2 m capillary tube:
Appr. 1.2 kg



Weight:
Including 2 m armoured
capillary tube: Appr. 1.4 kg



Weight:
Including rigid sensor:
Appr. 1.0 kg

All dimensions in millimetres

Approvals: CE marked in accordance with EN60947-4/-5. UL E73170. All relevant marine approvals.

KPS temperature switches

Contact function: Single pole double throw (SPDT)
Contact material: Gold plated silver
Load: AC-1 (ohmic): 10A, 440V
 AC-3 (motor): 6A, 440V
 AC-15 (inductive): 4A, 440V

Ambient temperature: -40 – 70 °C

KPS, remote sensor with armoured capillary tube



Type	Setting range [°C]	Adjustable differential range [°C]	Max sensor temperature [°C]	Capillary tube length [m]	Sensor size (ØxL) [mm]	Code number
KPS76	-10 – 30	3 – 10	80	2	13 x 63	060L311266
KPS77	20 – 60	3 – 14	130	2	13 x 63	060L310166
KPS79	50 – 100	4 – 16	200	2	13 x 63	060L310466
KPS81	60 – 150	5 – 25	250	2	13 x 63	060L310666
KPS80	70 – 120	4.5 – 18	220	2	13 x 63	060L312866
KPS80	70 – 120	4.5 – 18	220	5	13 x 90	060L313066
KPS80	70 – 120	4.5 – 18	220	3	13 x 63	060L315666
KPS83	100 – 200	6.5 – 30	300	2	13 x 63	060L310866

KPS, rigid sensor



Type	Setting range [°C]	Adjustable differential range [°C]	Max sensor temperature [°C]	Sensor size (ØxL) [mm]	Code number
KPS77	20 – 60	3 – 14	130	13 x 63	060L310066
KPS77	20 – 60	3 – 14	130	13 x 63	060L311866
KPS79	50 – 100	4 – 16	200	13 x 63	060L310366
KPS79	50 – 100	4 – 16	200	13 x 63	060L312166
KPS80	70 – 120	4.5 – 18	220	13 x 63	060L312666

KPS, remote sensor with capillary tube




Type	Setting range [°C]	Adjustable differential range [°C]	Max sensor temperature [°C]	Capillary tube length [m]	Sensor size (ØxL) [mm]	Code number
KPS77	20 – 60	3 – 14	130	2	13 x 63	060L310266
KPS79	50 – 100	4 – 16	200	2	13 x 63	060L310566
KPS80	70 – 120	4.5 – 18	220	2	13 x 63	060L312966

Spareparts and accessories for KPS temperature switches

Sensor pockets without stuffing box

Pocket length - A [mm]	Pocket thread - B				Pocket material		Code number
	G 1/2 A	G 3/8 A	G 3/4 A	G 1/2 A	Brass	18/8 steel	
75	✓				✓		060L326266
75		✓			✓		060L326666
75				✓	✓		060L328166
110	✓				✓		060L327166
110			✓		✓		060L340366
160	✓				✓		060L326366
200	✓				✓		060L320666
250	✓				✓		060L325466
75	✓					✓	060L326766
110	✓					✓	060L326866
160	✓					✓	060L326966



Stuffing box kits

Description	Code number
For KPS thermostats without armoured capillary tube	060L327366
For KPS thermostats with armoured capillary tube	060L036666

Heat conductive compound

Description	Code number
For KPS thermostats with sensor fitted in a sensor pocket. Compound for filling sensor pocket pocket to improve heat transfer between pocket and sensor. Application temperature range: -20 to 150 °C, momentarily up to 220 °C	041E0114

KP temperature switches




Danfoss KP thermostats are used for control, monitoring and alarm systems in industry. The KP thermostat series are temperature activated electric switches fitted with a single-pole double throw switch (SPDT), which can control single-phase ac motors of up to 2 kW directly.

- Temperature ranges: -30 – 150 °C
- High contact load - Ultra short bounce-time
- Also available with gold plated contact systems
- Enclosure IP44 when mounted with top cover and back plate
- Also available with enclosure IP55 for OEM customers
- Small dimensions - space saving - easy to install


Dimensions and weight:

Weight: Appr. 0.4 kg




KP 62

KP 75: Sensor tinned copper Cu/Sn 5



KP 61, 62, 68, 75, KP 78, KP 79, KP 81



KP 78, 79, 81: Sensor tinned copper Cu/Sn 5

All dimensions in millimetres

Approvals: CE marked in accordance with EN60947-4/-5. Electrical Safety Certificate - FM. UL E31024. Relevant marine approvals

KP temperature switches

Contact system: Single pole double throw (SPDT)
Contact material: Silver cadmium oxide
Load: AC-1 (ohmic): 16A 400V
 AC-3 (motor): 16A 400V
 AC-15 (inductive): 10A 400V

Enclosure: IP30
Ambient temperature: -40 – 65 °C
Reset: Automatic

Remote sensor with capillary tube

Type	Setting range [°C]	Adjustable differential range [°C]	Max sensor temperature [°C]	Sensor size (ØxL) [mm]	Capillary tube length [m]	Code number
KP71	-5 – 20	2.2 – 10	80	9.5 x 115	2	060L111366
KP77	20 – 60	3.5 – 10	130	9.5 x 85	2	060L112166
KP78	30 – 90	5 – 15	150	9.5 x 85	2	060L118466
KP79	50 – 100	5 – 15	150	9.5 x 85	2	060L112666
KP81	80 – 150	7 – 20	200	9.5 x 85	2	060L112566
KP81 ¹⁾	80 – 150	8	200	9.5 x 85	2	060L115566

¹⁾ Maximum reset function



Straight capillary tube sensor

Type	Setting range [°C]	Adjustable differential range [°C]	Max sensor temperature [°C]	Sensor Ø [mm]	Capillary tube sensor length [m]	Code number
KP61	-30 – 15	1.5 – 23	120	2.5	5	060L110166
KP61	-30 – 15	1.5 – 23	120	2.5	2	060L110066



Room sensor

Type	Setting range [°C]	Adjustable differential range [°C]	Max sensor temperature [°C]	Sensor size (ØxL) [mm]	Code number
KP62	-30 – 15	2 – 20	80	25 x 78	060L111066
KP68	-5 – 35	1.8 – 25	120	40 x 30	060L111166
KP75 ¹⁾	0 – 40	3 – 10	80	25 x 78	060L117166
KP76	5 – 45	2 – 20	120	25 x 78	060L120066

¹⁾ Contact material: Gold plated silver




Spareparts and accessories for KP temperature switch



Type	Description	Code numbers
Wall bracket	Mounting screw and washers included	060-105566
Angle bracket	Mounting screw and washers included	060-105666
Screwed cable entry	Pg 13.5 with special nut. For 6 – 14 mm diameter cables	060-105966
Top cover	For single control. If a wall or angle bracket is mounted on the backplate of the housing, the KP will have an IP44 grade of enclosure by means of this cover	060-109766
IP55 enclosure	For single control. Specially designed IP55 enclosure , not transparent	060-033066
Sensor pocket	Application: KP 77, 78, 79, 81. Brass. Pocket dimension: L 110 x Ø 15 mm. With stuffing box	060L333066
Sensor pocket	Application: KP 77, 78, 79, 81. Stainless steel. Pocket dimension: L 110 x Ø 15 mm. With stuffing box	060L333166
Heat conductive compound	For sensor pockets. Tube with 3.5cm ³ compound to be filled in the sensor pocket to improve heat transfer between pocket and sensor. Application range for compound: -20 – 150 °C, momentarily up to 220 °C.	041E0114

Brackets




For wall mounting




For 35 mm rail mounting




Screwed cable entry



Top cover



IP55 enclosure



The MBC 8100 compact temperature switches

MBC 8100 temperature switches are suitable for use in monitoring and alarm systems in factories, diesel plants, compressors and power stations, as well as in marine applications.

Alarm and monitoring

As part of alarm and control circuits, the switches give signals within narrow non-drifting limits, typically in lubrication and cooling oil applications, including diesel engines and gear boxes.

Compact space-saving solution

The block design allows packed mounting, providing a high degree of integrity for your machinery.

Excellent vibration and shock resistance

Ideal for heavy-duty applications, the MBC 8100's high vibration resistance increases the reliability of the entire system.

Adjustable range with fixed differential

The MBC 8100 comes pre-set from the factory, but it also has as an adjustable range and low fixed differential for accurate monitoring of critical temperatures.

Resistance to media

The sensor pocket is available in brass or stainless steel.




MBC 8100 block-type compact temperature switches for marine applications



MBC 8100 thermostats are used in marine applications where space and reliability are the most important features. MBCs are compact thermostats, designed according to our new block design to survive in the harsh conditions known from machine rooms onboard ships. MBCs have high vibration resistance and feature all commonly marine approvals. The fixed, but low differential guarantees accurate monitoring of critical temperatures. Also available without marine approvals (MBC 8000; please contact Danfoss for information)

- Block design
- Fully electromechanical
- -10 – 200 °C temperature range
- Available with all relevant marine approvals
- Designed to meet the strict demands in the marine equipment

Dimensions and weight:



All dimensions in millimetres

Approvals: CE marked in accordance with EN60947-5. All relevant marine approvals.

MBC 8100 block-type compact temperature switches

Contact function: Single pole double throw (SPDT)
Loads: AC-1 (ohmic) 10A, 250V
AC-3 (motor) 3A, 250V
AC-15 (inductive) 0.5A, 250V
Ambient temperature: -40 – 85 °C
Enclosure: IP65
Electrical connection: Plug Pg 11. Other connections available on request.



MBC 8100 with rigid sensor

Temp. setting range [°C]	Fixed diff. [°C]	Max. sensor temp. [°C]	Sensor size (ØxL) [mm]	Sensor pocket, length [mm]	Code number
20 – 60	3	130	13 x 50	75	061B800266
50 – 100	4	200	13 x 50	75	061B800366
60 – 150	6	250	13 x 50	75	061B800566
70 – 120	5	220	13 x 50	75	061B800466




MBC 8100 with armoured capillary tube, length: 2 m

Temp. setting range [°C]	Fixed diff. [°C]	Max. sensor temp. [°C]	Sensor size (ØxL) [mm]	Code number
-10 – 30	3	80	13 x 50	061B810166
20 – 60	3	130	13 x 50	061B810266
50 – 100	4	200	13 x 50	061B810366
70 – 120	5	220	13 x 50	061B810466
60 – 150	6	250	13 x 50	061B810566

Spareparts and accessories for MBC 8100 temperature switches

Sensor pockets without stuffing box

Pocket length - A [mm]	Pocket thread - B				Pocket material		Code number
	G ½ A	G ¾ A	G ¾ A	ISO 228/1 G½ A	Brass	18/8 steel	
75	✓				✓		060L326266
75		✓			✓		060L326666
75				✓	✓		060L328166
110	✓				✓		060L327166
110			✓		✓		060L340366
160	✓				✓		060L326366
200	✓				✓		060L320666
250	✓				✓		060L325466
75	✓					✓	060L326766
110	✓					✓	060L326866
160	✓					✓	060L326966



Stuffing box kits

Description	Code number
For MBC thermostats without armoured capillary tube	060L327366
For MBC thermostats with armoured capillary tube	060L036666



Type	Description	Code number
Heat conductive compound	For thermostats with sensor fitted in a sensor pocket. Compound for filling sensor pocket to improve heat transfer between pocket and sensor. Application temperature range: -20 – 150 °C, momentarily up to 220 °C	041E0114

Code number index

Code number	page	Code number	page	Code number	page	Code number	page
003N0042	62	017-422066.....	162	017-528266.....	137	018F6703	43
003N0043	62	017-422966.....	145	017-529166.....	136	018F6703	43
003N0045	62	017-424066.....	138	017-529566.....	136	018F6703	48
003N0046	62	017-424066.....	162	017B0002	141	018F6703	48
003N0047	62	017-425166.....	138	017B0006	141	018F6703	51
003N0050	64	017-425166.....	162	017B0010	141	018F6703	51
003N0062	64	017-436066.....	138	017B0014	141	018F6707	28
003N0075	64	017-436066.....	162	017B0018	141	018F6707	32
003N0078	64	017-436366.....	138	017B0022	141	018F6707	38
003N0091	64	017-436366.....	162	017B0026	141	018F6707	43
003N0107	62	017-436766.....	64	017B0030	141	018F6707	48
003N0108	62	017-436766.....	162	017B0034	141	018F6707	51
003N0109	62	017-436866.....	138	017B0038	141	018F6709	28
003N0155	64	017-436866.....	145	017B0042	141	018F6709	32
003N0155	162	017-436966.....	162	017B0046	141	018F6709	38
003N0192	64	017-437066.....	162	017B0050	141	018F6709	43
003N0196	64	017-500366.....	161	017B0054	141	018F6709	48
003N0278	64	017-500466.....	161	017B0058	141	018F6709	51
003N0388	64	017-500666.....	161	017B0062	141	018F6711	28
003N1132	62	017-502266.....	161	017B0066	141	018F6711	32
003N1144	62	017-503666.....	161	017B0070	141	018F6711	38
003N1162	62	017-504866.....	161	017B0074	141	018F6711	43
003N1182	62	017-506066.....	161	017B1018	141	018F6711	48
003N2132	62	017-509466.....	136	017B1019	141	018F6711	51
003N2150	62	017-509966.....	161	017D002166.....	137	018F6756	28
003N2162	62	017-511866.....	161	017D002366.....	137	018F6756	32
003N2182	62	017-513566.....	161	017D002466.....	137	018F6756	38
003N3132	62	017-513666.....	161	017D002566.....	137	018F6756	43
003N3150	62	017-513966.....	161	017D002766.....	137	018F6756	48
003N3162	62	017-514066.....	161	017D004566.....	137	018F6756	51
003N3182	62	017-514166.....	161	017D004866.....	137	018F6757	28
003N4132	62	017-515566.....	161	017L002466.....	161	018F6757	32
003N4150	62	017-518166.....	137	017L003266.....	136	018F6757	38
003N4162	62	017-518266.....	137	018F0091	28	018F6757	43
003N4182	62	017-518766.....	137	018F0091	33	018F6757	48
016D0075	44	017-518866.....	137	018F0091	40	018F6757	51
016D0076	44	017-518966.....	137	018F0091	43	018F6968	55
016D0077	44	017-519166.....	136	018F0091	49	018F7351	28
016D0078	44	017-519266.....	136	018F4511	55	018F7351	32
016D0079	44	017-519666.....	136	018F4511	55	018F7351	38
016D0080	44	017-519966.....	136	018F4517	55	018F7351	43
016D0095	44	017-520066.....	136	018F4517	55	018F7351	48
016D0096	44	017-520366.....	136	018F4519	55	018F7351	51
016D3330	43	017-520466.....	136	018F6701	28	018F7352	28
016D3331	43	017-520866.....	161	018F6701	32	018F7352	32
016D6065	43	017-521466.....	161	018F6701	38	018F7352	38
016D6080	43	017-521566.....	136	018F6701	43	018F7352	43
016D6100	43	017-522066.....	161	018F6701	48	018F7352	48
017-401366.....	138	017-522466.....	161	018F6701	51	018F7352	51
017-403066.....	138	017-522766.....	161	018F6702	28	018F7353	28
017-403066.....	162	017-523166.....	161	018F6702	32	018F7353	28
017-404166.....	138	017-523666.....	161	018F6702	38	018F7353	32
017-404266.....	138	017-523766.....	136	018F6702	43	018F7353	32
017-404266.....	162	017-523866.....	136	018F6702	48	018F7353	38
017-420366.....	162	017-523966.....	136	018F6702	51	018F7353	38
017-420566.....	138	017-525566.....	136	018F6703	28	018F7353	43
017-420566.....	143	017-526266.....	137	018F6703	28	018F7353	43
017-420566.....	145	017-526766.....	137	018F6703	32	018F7353	48
017-421666.....	162	017-526866.....	137	018F6703	32	018F7353	48
017-421966.....	138	017-526966.....	137	018F6703	38	018F7353	51
017-422066.....	64	017-528066.....	137	018F6703	38	018F7353	51

Code number	page	Code number	page	Code number	page	Code number	page
018F7358.....	28	018Z0291.....	58	032U0296.....	39	032U3621.....	27
018F7358.....	32	018Z6987.....	58	032U0299.....	39	032U3622.....	27
018F7358.....	38	027N3065.....	44	032U0681.....	40	032U3623.....	27
018F7358.....	43	027N3080.....	44	032U0682.....	40	032U3624.....	27
018F7358.....	48	027N3100.....	44	032U0683.....	40	032U3629.....	26
018F7358.....	51	031E020066.....	154	032U1062.....	32	032U3630.....	27
018F7360.....	28	031E020266.....	154	032U1063.....	32	032U3631.....	27
018F7360.....	28	031E020566.....	154	032U1065.....	32	032U3632.....	27
018F7360.....	32	031E021066.....	154	032U1066.....	32	032U3633.....	27
018F7360.....	32	031E021566.....	154	032U1067.....	32	032U3636.....	27
018F7360.....	38	031E022066.....	154	032U1068.....	32	032U3637.....	27
018F7360.....	38	031E022566.....	154	032U1069.....	32	032U3638.....	27
018F7360.....	43	031E023066.....	154	032U1070.....	32	032U3639.....	27
018F7360.....	43	031E023566.....	154	032U1071.....	39	032U3640.....	27
018F7360.....	48	031E024566.....	154	032U1072.....	39	032U3641.....	27
018F7360.....	48	031E025066.....	154	032U1073.....	39	032U3642.....	26
018F7360.....	51	031E025566.....	154	032U1074.....	39	032U3643.....	26
018F7360.....	51	031E029166.....	154	032U1075.....	39	032U3802.....	54
018F7361.....	28	031E029366.....	154	032U1076.....	39	032U3803.....	54
018F7361.....	32	031E029666.....	154	032U1077.....	39	032U3804.....	54
018F7361.....	38	031E029766.....	154	032U1078.....	39	032U3805.....	54
018F7361.....	43	031E029866.....	154	032U1079.....	39	032U3806.....	54
018F7361.....	48	032H8000.....	16	032U1080.....	39	032U3807.....	54
018F7361.....	51	032H8001.....	16	032U1081.....	39	032U4901.....	23
018F7396.....	28	032H8002.....	16	032U1082.....	39	032U4904.....	23
018F7396.....	32	032H8003.....	16	032U1200.....	26	032U4916.....	23
018F7396.....	38	032H8004.....	16	032U1205.....	26	032U4919.....	23
018F7396.....	43	032H8005.....	17	032U1220.....	26	032U5250.....	47
018F7396.....	48	032H8006.....	17	032U1225.....	26	032U5251.....	47
018F7396.....	51	032H8007.....	17	032U1231.....	26	032U5252.....	47
018F7397.....	28	032H8008.....	17	032U1236.....	31	032U5253.....	47
018F7397.....	32	032H8009.....	17	032U1237.....	31	032U5254.....	47
018F7397.....	38	032H8014.....	17	032U1238.....	31	032U5255.....	47
018F7397.....	43	032H8015.....	17	032U1239.....	31	032U5256.....	47
018F7397.....	48	032H8016.....	17	032U1241.....	31	032U5257.....	47
018F7397.....	51	032H8017.....	17	032U1242.....	31	032U5271.....	49
018F7655.....	28	032H8018.....	17	032U1246.....	31	032U5273.....	49
018F7655.....	28	032H8019.....	17	032U1247.....	31	032U5315.....	49
018F7655.....	32	032H8027.....	16	032U1249.....	31	032U5317.....	49
018F7655.....	32	032H8029.....	17	032U1251.....	31	032U5319.....	49
018F7655.....	38	032H8031.....	17	032U1252.....	31	032U5320.....	49
018F7655.....	38	032H8033.....	17	032U1255.....	31	032U5321.....	49
018F7655.....	48	032H8039.....	17	032U1256.....	31	032U5322.....	49
018F7655.....	48	032H8041.....	17	032U1260.....	31	032U5350.....	47
018F7658.....	28	032H8043.....	17	032U1261.....	31	032U5352.....	47
018F7658.....	28	032H8087.....	15	032U1263.....	31	032U5354.....	47
018F7658.....	32	032H8089.....	15	032U1266.....	31	032U5356.....	47
018F7658.....	32	032H8095.....	15	032U3171.....	55	032U5701.....	26
018F7658.....	38	032H8097.....	15	032U3172.....	55	032U5702.....	26
018F7658.....	38	032H8099.....	15	032U3173.....	55	032U5704.....	26
018F7658.....	48	032H8125.....	15	032U3601.....	26	032U5705.....	26
018F7658.....	48	032U0082.....	40	032U3605.....	26	032U5706.....	26
018F7663.....	28	032U0084.....	40	032U3606.....	26	032U5707.....	26
018F7663.....	28	032U0085.....	40	032U3607.....	26	032U5708.....	26
018F7663.....	32	032U0086.....	40	032U3608.....	26	032U5709.....	26
018F7663.....	32	032U0087.....	40	032U3615.....	26	032U5710.....	26
018F7663.....	38	032U0150.....	39	032U3616.....	26	032U5815.....	36
018F7663.....	38	032U0165.....	32	032U3617.....	26	032U5820.....	36
018F7663.....	48	032U0166.....	32	032U3618.....	26	032U5825.....	36
018F7663.....	48	032U0167.....	32	032U3619.....	27	032U5825.....	36
018Z0290.....	58	032U0295.....	39	032U3620.....	27	032U5832.....	36

Code number	page	Code number	page	Code number	page	Code number	page
032U5840	37	032U8363	51	032U380731	54	042N0185	52
032U5850	37	032U8364	51	032U451402	36	042N0263	15
032U6013	39	032U8365	51	032U451416	36	042N0263	15
032U6014	39	032U8500	36	032U451431	36	042N0263	17
032U6015	39	032U8501	36	032U453002	36	042N0263	17
032U6016	39	032U8502	36	032U453016	36	042N0263	20
032U6017	39	032U8503	37	032U453031	36	042N0263	23
032U6018	39	032U8504	37	032U453402	36	042N0263	28
032U6156	52	032U8505	37	032U453416	36	042N0263	28
032U6157	52	032U8506	36	032U453431	36	042N0263	28
032U6158	52	032U8507	36	032U456802	36	042N0263	32
032U6159	52	032U8508	36	032U456816	36	042N0263	32
032U6160	52	032U8509	37	032U456831	36	042N0263	32
032U6161	52	032U8510	37	032U458502	36	042N0263	38
032U7115	36	032U8511	37	032U458516	36	042N0263	38
032U7116	36	032U145802	26	032U458531	36	042N0263	38
032U7117	37	032U145816	26	032U460402	36	042N0263	43
032U7120	36	032U145831	26	032U460416	36	042N0263	48
032U7121	36	032U147002	26	032U460431	36	042N0263	48
032U7122	37	032U147016	26	032U528602	31	042N0263	51
032U7125	36	032U147031	26	032U528616	31	042N0265	15
032U7126	36	032U148002	26	032U528631	31	042N0265	15
032U7127	37	032U148016	26	032U528702	31	042N0265	17
032U7132	37	032U148031	26	032U528716	31	042N0265	17
032U7133	37	032U151802	31	032U528731	31	042N0265	20
032U7134	37	032U151816	31	032U537431	47	042N0265	23
032U7140	37	032U151831	31	032U537631	47	042N0265	28
032U7141	37	032U153802	31	041E0114	162	042N0265	28
032U7142	37	032U153816	31	041E0114	165	042N0265	28
032U7150	37	032U153831	31	041E0114	168	042N0265	32
032U7151	37	032U157102	47	041E0114	171	042N0265	32
032U7152	37	032U157116	47	042N0156	15	042N0265	32
032U7170	36	032U157131	47	042N0156	15	042N0265	38
032U7171	36	032U158002	47	042N0156	17	042N0265	38
032U7172	36	032U158016	47	042N0156	17	042N0265	38
032U7173	37	032U158031	47	042N0156	20	042N0265	43
032U7174	37	032U161402	47	042N0156	23	042N0265	48
032U7175	37	032U161416	47	042N0156	28	042N0265	48
032U7180	37	032U161431	47	042N0156	28	042N0265	51
032U7181	37	032U162402	47	042N0156	28	042N0840	15
032U7182	37	032U162416	47	042N0156	32	042N0840	15
032U7183	37	032U162431	47	042N0156	32	042N0840	17
032U7184	37	032U380402	54	042N0156	32	042N0840	17
032U7185	37	032U380416	54	042N0156	38	042N0840	20
032U7390	39	032U380420	54	042N0156	38	042N0841	15
032U7390	44	032U380429	54	042N0156	38	042N0841	15
032U8039	58	032U380431	54	042N0156	43	042N0841	17
032U8040	58	032U380502	54	042N0156	48	042N0841	17
032U8041	58	032U380516	54	042N0156	48	042N0841	20
032U8042	58	032U380520	54	042N0156	51	042N0842	15
032U8052	58	032U380529	54	042N0156	55	042N0842	15
032U8053	58	032U380531	54	042N0156	55	042N0842	17
032U8054	58	032U380602	54	042N0185	15	042N0842	17
032U8055	58	032U380616	54	042N0185	17	042N0842	20
032U8056	58	032U380620	54	042N0185	20	042N0843	15
032U8057	58	032U380629	54	042N0185	23	042N0843	17
032U8118	52	032U380631	54	042N0185	28	042N0843	20
032U8119	52	032U380702	54	042N0185	33	042N0845	15
032U8360	51	032U380716	54	042N0185	40	042N0845	15
032U8361	51	032U380720	54	042N0185	43	042N0845	17
032U8362	51	032U380729	54	042N0185	49	042N0845	17

Code number	page	Code number	page	Code number	page	Code number	page
042N0845	20	042N7508	28	060-019166	138	060-316266	145
042N0848	15	042N7508	32	060-033066	148	060-316466	148
042N0848	17	042N7508	38	060-033066	151	060-316966	148
042N0848	20	042N7510	23	060-033066	168	060-319366	148
042N4191	15	042N7510	28	060-104766	108	060-324166	138
042N4191	15	042N7510	32	060-104766	138	060-333266	108
042N4191	17	042N7510	38	060-104766	143	060-333266	143
042N4191	17	042N7512	23	060-104766	145	060-333266	145
042N4192	15	042N7512	28	060-105566	148	060-333366	108
042N4192	17	042N7512	32	060-105566	151	060-333366	138
042N4193	15	042N7512	38	060-105566	168	060-333366	143
042N4193	17	042N7550	23	060-105666	148	060-333366	145
042N4400	68	042N7550	28	060-105666	151	060-333666	143
042N4401	68	042N7550	32	060-105666	168	060-333666	145
042N4402	68	042N7550	38	060-105766	148	060-333866	108
042N4403	68	042N7551	23	060-105766	151	060-504766	150
042N4404	68	042N7551	28	060-105966	148	060-508166	148
042N4406	68	042N7551	32	060-105966	151	060-538666	150
042N4407	68	042N7551	38	060-105966	168	060-538766	150
042N4408	68	042U1000	20	060-109766	148	060G0005	85
042N4409	68	042U1001	20	060-109766	151	060G0005	88
042N4411	68	042U1003	20	060-109766	168	060G0005	96
042N4430	68	042U1004	20	060-110866	150	060G0005	99
042N4431	68	042U1006	20	060-113366	150	060G0005	106
042N4432	68	042U1007	20	060-113766	150	060G0007	77
042N4433	68	042U1009	28	060-113866	148	060G0007	79
042N4435	68	042U1009	40	060-114466	150	060G0007	81
042N4436	68	042U1010	28	060-118966	148	060G0007	83
042N4450	68	042U1010	40	060-121766	148	060G0007	85
042N4451	68	042U1037	20	060-121966	148	060G0007	88
042N4452	68	042U1038	20	060-122166	150	060G0007	96
042N4453	68	042U1039	20	060-131866	150	060G0007	99
042N4454	68	042U1040	20	060-215966	150	060G0007	104
042N4455	68	042U1041	20	060-216066	150	060G0007	106
042N4456	68	042U1042	20	060-216166	150	060G0008	77
042N4457	68	042U4001	19	060-216266	150	060G0008	79
042N4459	68	042U4003	19	060-216366	150	060G0008	81
042N4480	68	042U4011	19	060-216466	150	060G0008	83
042N4481	68	042U4012	19	060-216566	150	060G0008	85
042N4482	68	042U4013	19	060-216666	150	060G0008	88
042N4483	68	042U4014	19	060-310066	143	060G0008	90
042N4484	68	042U4022	19	060-310166	143	060G0008	96
042N4485	68	042U4023	19	060-310266	143	060G0008	99
042N4486	68	042U4024	19	060-310366	143	060G0008	104
042N4820	69	042U4031	19	060-310466	143	060G0008	106
042N4821	69	042U4032	19	060-310566	143	060G0252	81
042N4822	69	042U4041	19	060-310666	143	060G0252	85
042N4823	69	042U4042	19	060-310766	143	060G0252	88
042N7501	23	042U4053	19	060-310866	143	060G1021	81
042N7501	28	042U4063	19	060-310966	143	060G1021	83
042N7501	32	042U4074	19	060-311066	143	060G1021	85
042N7501	38	042U4082	19	060-312066	143	060G1021	88
042N7502	23	042U4084	19	060-312166	143	060G1022	81
042N7502	28	042U4085	19	060-312266	143	060G1022	83
042N7502	32	042U4086	19	060-313066	145	060G1022	85
042N7502	38	042U4087	19	060-315066	145	060G1022	88
042N7504	23	042U4088	19	060-315166	145	060G1023	81
042N7504	28	042U4089	19	060-315266	145	060G1023	83
042N7504	32	042U4092	19	060-315366	145	060G1023	85
042N7504	38	060-007166	143	060-316066	145	060G1023	88
042N7508	23	060-016966	108	060-316166	145	060G1024	81

Code number	page	Code number	page	Code number	page	Code number	page
060G1024.....	83	060G1865.....	83	060L111366.....	167	060N1063.....	99
060G1024.....	85	060G1866.....	83	060L112166.....	167	060N1064.....	99
060G1024.....	88	060G1867.....	83	060L112566.....	167	060N1065.....	99
060G1034.....	77	060G1868.....	83	060L112666.....	167	060N1066.....	99
060G1034.....	79	060G1869.....	83	060L115566.....	167	060N1081.....	99
060G1034.....	81	060G1874.....	81	060L117166.....	167	060N1083.....	99
060G1034.....	83	060G1875.....	81	060L118466.....	167	060N1084.....	99
060G1034.....	85	060G1876.....	81	060L120066.....	167	060N1085.....	99
060G1034.....	88	060G1877.....	81	060L310066.....	164	060N1086.....	99
060G1034.....	90	060G2418.....	102	060L310166.....	164	060N1087.....	99
060G1034.....	96	060G2419.....	102	060L310266.....	164	061B000266.....	156
060G1034.....	99	060G2420.....	102	060L310366.....	164	061B000466.....	156
060G1105.....	77	060G2421.....	102	060L310466.....	164	061B000566.....	156
060G1106.....	77	060G2422.....	102	060L310566.....	164	061B001066.....	156
060G1107.....	77	060G2423.....	102	060L310666.....	164	061B6001.....	86
060G1109.....	77	060G2424.....	102	060L310866.....	164	061B6001.....	88
060G1110.....	77	060G2425.....	102	060L311266.....	164	061B6002.....	86
060G1111.....	77	060G2426.....	102	060L311866.....	164	061B6002.....	88
060G1112.....	77	060G2427.....	102	060L312166.....	164	061B6003.....	86
060G1113.....	77	060G2428.....	102	060L312666.....	164	061B6003.....	88
060G1122.....	77	060G2501.....	102	060L312866.....	164	061B6004.....	86
060G1123.....	77	060G2502.....	102	060L312966.....	164	061B6100.....	86
060G1124.....	77	060G2503.....	102	060L313066.....	164	061B6100.....	88
060G1125.....	77	060G2505.....	102	060L315666.....	164	061B7000.....	97
060G1133.....	77	060G2506.....	102	060L320666.....	165	061B7000.....	100
060G1151.....	79	060G2510.....	102	060L320666.....	171	061B7000.....	158
060G1153.....	79	060G2850.....	77	060L325466.....	165	061B7001.....	97
060G1154.....	79	060G2850.....	79	060L325466.....	171	061B7001.....	100
060G1367.....	85	060G2850.....	81	060L326266.....	165	061B7001.....	158
060G1368.....	85	060G2850.....	83	060L326266.....	171	061B7002.....	97
060G1369.....	85	060G2850.....	86	060L326366.....	165	061B7002.....	100
060G1370.....	85	060G2850.....	88	060L326366.....	171	061B7002.....	158
060G1371.....	85	060G2850.....	104	060L326666.....	165	061B7003.....	97
060G1372.....	85	060G2850.....	106	060L326666.....	171	061B7003.....	100
060G1411.....	79	060G2850.....	115	060L326766.....	165	061B7003.....	158
060G1429.....	77	060G3388.....	85	060L326766.....	171	061B7004.....	97
060G1430.....	77	060G3557.....	79	060L326866.....	165	061B7004.....	100
060G1463.....	85	060G3582.....	79	060L326866.....	171	061B7004.....	158
060G1464.....	85	060G3583.....	79	060L326966.....	165	061B7005.....	97
060G1465.....	85	060G3584.....	79	060L326966.....	171	061B7005.....	100
060G1466.....	85	060G3585.....	79	060L327166.....	165	061B7005.....	158
060G1467.....	85	060G3586.....	79	060L327166.....	171	061B7006.....	97
060G1468.....	85	060G3812.....	77	060L327366.....	165	061B7006.....	100
060G1469.....	85	060G3813.....	77	060L327366.....	171	061B7006.....	158
060G1470.....	85	060G3814.....	77	060L328166.....	165	061B7007.....	97
060G1471.....	85	060G3815.....	77	060L328166.....	171	061B7007.....	100
060G1472.....	85	060G3828.....	77	060L333066.....	162	061B7007.....	158
060G1473.....	85	060G3829.....	77	060L333066.....	168	061B7008.....	97
060G1474.....	88	060G3830.....	77	060L333166.....	168	061B7008.....	100
060G1475.....	88	060G3831.....	77	060L340366.....	165	061B7008.....	158
060G1476.....	88	060G3832.....	77	060L340366.....	171	061B7009.....	97
060G1477.....	88	060G3833.....	77	060N1032.....	96	061B7009.....	100
060G1650.....	77	060G3902.....	77	060N1033.....	96	061B7009.....	158
060G1778.....	83	060G5600.....	85	060N1034.....	96	061B7010.....	97
060G1779.....	83	060G5601.....	85	060N1035.....	96	061B7010.....	100
060G1790.....	83	060L036666.....	165	060N1036.....	96	061B7010.....	158
060G1791.....	83	060L036666.....	171	060N1037.....	96	061B7011.....	97
060G1861.....	83	060L110066.....	167	060N1038.....	96	061B7011.....	100
060G1862.....	83	060L110166.....	167	060N1039.....	96	061B7011.....	158
060G1863.....	83	060L111066.....	167	060N1040.....	96	061B7012.....	97
060G1864.....	83	060L111166.....	167	060N1041.....	96	061B7012.....	100

Code number	page	Code number	page	Code number	page	Code number	page
061B7012	158	064G6532	90	084Z4037	115	084Z8212	123
061B100266	156	064G6533	90	084Z4038	115	084Z8213	123
061B100366	156	064G6542	90	084Z4039	115	084Z8214	123
061B100466	156	064G6543	90	084Z5025	127	084Z8215	123
061B100566	156	084G2100	108	084Z5026	127	084Z8216	123
061B100866	156	084G2101	108	084Z5034	127	084Z8217	123
061B128066	156	084G2102	108	084Z5052	125	084Z8218	121
061B129066	156	084G2103	108	084Z5160	127	084Z8230	123
061B400101	156	084G2104	108	084Z5248	125	084Z8231	123
061B400201	156	084G2105	108	084Z5276	125	084Z8232	123
061B510066	156	084G2106	108	084Z5277	125	084Z8233	123
061B510166	156	084G2107	108	084Z6030	117	084Z8234	123
061B510266	156	084G2108	108	084Z6032	117	084Z8235	123
061B720001	97	084G2109	108	084Z6033	117	084Z8236	123
061B720001	100	084G2110	108	084Z6034	117	084Z8237	123
061B720001	158	084G2111	108	084Z6035	117		
061B720101	97	084G2112	108	084Z6036	117		
061B720101	100	084G2113	108	084Z6037	117		
061B720101	158	084G2114	108	084Z6038	117		
061B720201	97	084G2115	108	084Z6039	117		
061B720201	100	084G2116	108	084Z6042	117		
061B720201	158	084G2117	108	084Z6050	117		
061B722101	156	084G2118	108	084Z6051	117		
061B800266	171	084G2120	108	084Z6053	117		
061B800366	171	084G2206	108	084Z6054	117		
061B800466	171	084G2207	108	084Z6139	123		
061B800566	171	084G2209	108	084Z6140	123		
061B810166	171	084G2211	108	084Z6141	123		
061B810266	171	084G2213	108	084Z6142	123		
061B810366	171	084Z2012	113	084Z6143	123		
061B810466	171	084Z2014	113	084Z6144	123		
061B810566	171	084Z2018	113	084Z6145	123		
063G1068	92	084Z2019	113	084Z6164	123		
063G1123	92	084Z2021	113	084Z6215	117		
063G1125	92	084Z2446	119	084Z6216	117		
063G1133	92	084Z2447	119	084Z7258	115		
063G1159	92	084Z2448	119	084Z7259	115		
063G1218	92	084Z2449	119	084Z7260	115		
063G1229	92	084Z2450	119	084Z7261	115		
063G1407	92	084Z2451	119	084Z7262	115		
063G1410	92	084Z2452	119	084Z8006	121		
063G1632	92	084Z2453	119	084Z8008	121		
064G5201	106	084Z2454	119	084Z8010	121		
064G5202	106	084Z2455	119	084Z8011	121		
064G5207	106	084Z2456	119	084Z8012	121		
064G5214	104	084Z2457	119	084Z8013	121		
064G5215	104	084Z2458	119	084Z8014	121		
064G5216	104	084Z2459	119	084Z8022	121		
064G5218	104	084Z2460	119	084Z8036	121		
064G5219	106	084Z2461	119	084Z8037	121		
064G5221	106	084Z3257	127	084Z8039	121		
064G5222	104	084Z3260	127	084Z8041	121		
064G5224	106	084Z3261	127	084Z8043	121		
064G5225	104	084Z3262	127	084Z8044	121		
064G5226	106	084Z4030	115	084Z8058	121		
064G5228	106	084Z4031	115	084Z8150	127		
064G6501	90	084Z4032	115	084Z8154	127		
064G6502	90	084Z4033	115	084Z8155	127		
064G6504	90	084Z4034	115	084Z8156	127		
064G6511	90	084Z4035	115	084Z8210	123		
064G6523	90	084Z4036	115	084Z8211	123		

ENGINEERING TOMORROW

Danfoss Ltd. | Industrial Automation | 3F, 4F 651, Non hyeon-ro, Gang nam-gu, seoul 06116, Korea
| danfosskorea@danfoss.com | ia.danfoss.kr
Tel: 82-2-567-0090



Danfoss is a leading global player within the development and production of mechanical and electronic products and controls. Since 1933, our extensive know-how has made modern life easier and we continue to break new ground within our core business areas.

Every day, more than 250,000 items are produced at 70 factories in 25 countries. Impressive as these figures are, we are most proud of the way our dedicated employees apply the high-quality components in customer solutions, adding value to the end products. Building strong partnerships is of great importance to us, because it is purely by understanding our customers' needs that we can meet the expectations of tomorrow.

This is also true in Industrial Automation, a Danfoss entity dedicated to focusing on the industrial world of today. Through us, you gain access to the entire Danfoss pool of technologies, with special emphasis on sensors and controls.

We offer safer, more reliable and more efficient solutions in a close cooperation based on firm values.