

Solenoid Valves

SV08-24-08


Solenoid Valve, 4-way, 2-position, Spool Type

230 bar [3300 psi] • 18 l/min [4.7 US gpm]

OPERATION AND DESCRIPTION


This is a 4-way, 2-position, spool type, direct acting solenoid valve. In the de-energized condition, ports 2 and 4 are open to port 1 with port 3 closed. When energized, port 1 is open to 2 and port 3 to 4. In the de-energized condition, these valves can allow a motor into a free-wheel mode or a cylinder to float condition. Energizing the valve will provide unidirectional flow. Always check the operating envelope to make sure the valve will work under the required application conditions. Port 1 is not intended for use as inlet (Tank only).

SCHEMATIC



DIMENSIONS

mm [in]





PERFORMANCE DATA

Rated Pressure*	230 bar [3300 psi]**
Flow Capability	18 l/min [4.7 US gpm]
Coil Options	M13, R13
Weight	0.45 kg [0.99 lb]
Cavity	SDC08-4

*Rated Pressure based on NFPA fatigue test standards (at 1 million cycles)

**Valve can operate with an inlet pressure of 315 bar [4600 psi] at port 3 for 500,000 cycles

PERFORMANCE CURVES



MODEL CODE

SV08 - 24 - 08 - 12D - DE - B - 4S

Coil Voltage

Standard Code	Robust Coil Code	Coil Voltage
00	R00	No Coil, nut included*
10D	R10D	10 VDC
12D	R12D	12 VDC
20D	R20D	20 VDC
24D	R24D	24 VDC
110A		110 VAC**
220A		220 VAC**

*Standard Coil - Plastic coil nut and o-rings (p/n 173800588)

**Robust Coil - Steel coil nut and no o-rings (p/n 173800539)

**DIN only - external rectifier needed

Connector Type

Standard Coil Code	Robust Coil Code	Connector Type
00	00	No Coil
AJ		Amp Junior
AJD		Amp Junior with Diode
AS	AS	AMP SuperSeal 1.5
ASD	ASDB*	AMP SuperSeal with Diode
DE	DE	Deutsch
DED	DEDB*	Deutsch with Diode
FL	FL	Flying Leads
FLD	FLDB*	Flying Leads with Diode
DN		DIN 43650

*Bi-directional diode

Housing

Code	Ports	Housing Model Code
00	No Housing	
4S	#4 SAE, AL	CP08-4-4S
6S	#6 SAE, AL	CP08-4-6S
S6S	#6 SAE, Steel	CP08-4-S6S
L2B	1/4 BSP, AL	SDC08-4-L2B
S3B	3/8 BSP, Steel	CP08-4-S3B

* Aluminum bodies are to be used for pressures less than 210 bar [3000 psi].

* Additional housings available

Seal Option

Code	Seal kit
B-Buna - N	354003319
V-Viton	354003919