



SEMiX® 33c

Trench IGBT Modules


SEMiX653GD176HDc

Features

- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- UL recognised file no. E63532

Typical Applications*

- AC inverter drives
- UPS
- Electronic welders



GD

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
IGBT				
V _{CES}			1700	V
I _C	T _j = 150 °C	T _c = 25 °C	619	A
		T _c = 80 °C	438	A
I _{Cnom}			450	A
I _{CRM}	I _{CRM} = 2xI _{Cnom}		900	A
V _{GES}			-20 ... 20	V
t _{psc}	V _{CC} = 1000 V V _{GE} ≤ 20 V V _{CES} ≤ 1700 V	T _j = 125 °C	10	μs
T _j			-55 ... 150	°C
Inverse diode				
I _F	T _j = 150 °C	T _c = 25 °C	545	A
		T _c = 80 °C	365	A
I _{Fnom}			450	A
I _{FRM}	I _{FRM} = 2xI _{Fnom}		900	A
I _{FSM}	t _p = 10 ms, sin 180°, T _j = 25 °C		2900	A
T _j			-40 ... 150	°C
Module				
I _{t(RMS)}			600	A
T _{stg}			-40 ... 125	°C
V _{isol}	AC sinus 50Hz, t = 1 min		4000	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
V _{CE(sat)}	I _C = 450 A V _{GE} = 15 V chiplevel	T _j = 25 °C		2	2.45	V
		T _j = 125 °C		2.45	2.9	V
V _{CE0}	V _{GE} = 15 V	T _j = 25 °C		1	1.2	V
		T _j = 125 °C		0.9	1.1	V
r _{CE}		T _j = 25 °C		2.2	2.8	mΩ
		T _j = 125 °C		3.4	4.0	mΩ
V _{GE(th)}	V _{GE} =V _{CE} , I _C = 18 mA		5.2	5.8	6.4	V
I _{CES}	V _{GE} = 0 V	T _j = 25 °C	3			mA
	V _{CE} = 1700 V	T _j = 125 °C				mA
C _{ies}	V _{CE} = 25 V V _{GE} = 0 V	f = 1 MHz	39.6			nF
C _{oes}		f = 1 MHz	1.65			nF
C _{res}		f = 1 MHz	1.31			nF
Q _G	V _{GE} = - 8 V...+ 15 V		4200			nC
R _{Gint}	T _j = 25 °C		1.67			Ω
t _{d(on)}	V _{CC} = 1200 V I _C = 450 A	T _j = 125 °C	290			ns
t _r		T _j = 125 °C	90			ns
E _{on}	R _{G on} = 3.6 Ω R _{G off} = 3.6 Ω	T _j = 125 °C	300			mJ
t _{d(off)}		T _j = 125 °C	975			ns
t _f		T _j = 125 °C	190			ns
E _{off}		T _j = 125 °C	180			mJ
R _{th(j-c)}	per IGBT		0.054			K/W



SEMiX® 33c

Trench IGBT Modules

SEMiX653GD176HDc


Features

- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- UL recognised file no. E63532

Typical Applications*

- AC inverter drives
- UPS
- Electronic welders

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Inverse diode						
V _F = V _{EC}	I _F = 450 A V _{GE} = 0 V chip	T _j = 25 °C		1.7	1.90	V
		T _j = 125 °C		1.7	1.9	V
V _{F0}		T _j = 25 °C	0.9	1.1	1.3	V
		T _j = 125 °C	0.7	0.9	1.1	V
r _F		T _j = 25 °C	1.3	1.3	1.3	mΩ
		T _j = 125 °C	1.8	1.8	1.8	mΩ
I _{RRM}	I _F = 450 A	T _j = 125 °C	380			A
Q _{rr}	di/dt _{off} = 4200 A/μs	T _j = 125 °C	130			μC
E _{rr}	V _{GE} = -15 V V _{CC} = 1200 V	T _j = 125 °C	73			mJ
R _{th(j-c)}	per diode		0.11			K/W
Module						
L _{CE}			20			nH
R _{CC'+EE'}	res., terminal-chip	T _C = 25 °C	0.7			mΩ
		T _C = 125 °C	1			mΩ
R _{th(c-s)}	per module		0.014			K/W
M _s	to heat sink (M5)		3	5		Nm
M _t		to terminals (M6)	2.5	5		Nm
						Nm
w			900			g
Temperatur Sensor						
R ₁₀₀	T _C =100°C (R ₂₅ =5 kΩ)		493 ± 5%			Ω
B _{100/125}	R _(T) =R ₁₀₀ exp[B _{100/125} (1/T-1/T ₁₀₀)]; T[K];		3550 ±2%			K



GD




Fig. 1: Typ. output characteristic, inclusive $R_{CC'} + E_E$




Fig. 2: Rated current vs. temperature $I_C = f(T_C)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times vs. I_C




Fig. 8: Typ. switching times vs. gate resistor R_G




Fig. 9: Typ. transient thermal impedance




Fig. 10: Typ. CAL diode forward charact., incl. $R_{CC'+EE'}$




Fig. 11: Typ. CAL diode peak reverse recovery current






Fig. 12: Typ. CAL diode recovery charge

SEMiX653GD176HDc

Case: SEMiX 33c
general tolerance:
ISO 2768-mK
ISO 8015



SEMiX 33c



This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.