

# SK30GD066ETp



**SEMITOP® 3 Press-Fit**

## Sixpack Open Emitter

### SK30GD066ETp

#### Features\*

- One screw mounting module
- Low inductive design
- Press-Fit contact technology
- Fully compatible with other SEMITOP® Press-Fit types
- 600V Trench IGBT3 technology
- Robust and soft switching CAL HD diode technology
- Integrated NTC temperature sensor
- UL recognized, file no. E 63 532


#### Typical Applications

- Motor drives
- Servo drives
- Air conditioning
- Auxiliary Inverters
- UPS

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
IGBT 1				
V <sub>CES</sub>	T <sub>j</sub> = 25 °C		600	V
I <sub>C</sub>	T <sub>j</sub> = 150 °C	T <sub>s</sub> = 25 °C	33	A
		T <sub>s</sub> = 70 °C	25	A
I <sub>C</sub>	T <sub>j</sub> = 175 °C	T <sub>s</sub> = 25 °C	40	A
		T <sub>s</sub> = 70 °C	31	A
I <sub>Cnom</sub>			30	A
I <sub>CRM</sub>			60	A
V <sub>GES</sub>			-20 ... 20	V
t <sub>psc</sub>	V <sub>CC</sub> = 360 V V <sub>GE</sub> ≤ 15 V V <sub>CES</sub> ≤ 600 V	T <sub>j</sub> = 150 °C	6	μs
T <sub>j</sub>			-40 ... 175	°C

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
Diode 1				
V <sub>RRM</sub>	T <sub>j</sub> = 25 °C		600	V
I <sub>F</sub>	T <sub>j</sub> = 150 °C	T <sub>s</sub> = 25 °C	32	A
		T <sub>s</sub> = 70 °C	24	A
I <sub>F</sub>	T <sub>j</sub> = 175 °C	T <sub>s</sub> = 25 °C	36	A
		T <sub>s</sub> = 70 °C	28	A
I <sub>FRM</sub>			60	A
I <sub>FSM</sub>	10 ms, sin 180°, T <sub>j</sub> = 150 °C		160	A
T <sub>j</sub>			-40 ... 175	°C

Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
Module			
I <sub>t(RMS)</sub>	ΔT <sub>terminal</sub> at PCB joint = 30 K, per pin	35	A
T <sub>stg</sub>		-40 ... 125	°C
V <sub>isol</sub>	AC, sinusoidal, t = 1 min	2500	V



**GD-ET**



**SEMITOP® 3 Press-Fit**

## Sixpack Open Emitter


### SK30GD066ETp

#### Features\*

- One screw mounting module
- Low inductive design
- Press-Fit contact technology
- Fully compatible with other SEMITOP® Press-Fit types
- 600V Trench IGBT3 technology
- Robust and soft switching CAL HD diode technology
- Integrated NTC temperature sensor
- UL recognized, file no. E 63 532

#### Typical Applications

- Motor drives
- Servo drives
- Air conditioning
- Auxiliary Inverters
- UPS




**GD-ET**

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT 1						
V <sub>CE(sat)</sub>	I <sub>C</sub> = 30 A V <sub>GE</sub> = 15 V chiplevel	T <sub>j</sub> = 25 °C		1.45	1.85	V
		T <sub>j</sub> = 150 °C		1.65	2.05	V
V <sub>CE0</sub>	chiplevel	T <sub>j</sub> = 25 °C		0.90	1.10	V
		T <sub>j</sub> = 150 °C		0.80	1.00	V
r <sub>CE</sub>	V <sub>GE</sub> = 15 V chiplevel	T <sub>j</sub> = 25 °C		18	25	mΩ
		T <sub>j</sub> = 150 °C		28	35	mΩ
V <sub>GE(th)</sub>	V <sub>GE</sub> = V <sub>CE</sub> , I <sub>C</sub> = 0.43 mA		5	5.8	6.5	V
I <sub>CES</sub>	V <sub>GE</sub> = 0 V V <sub>CE</sub> = 600 V	T <sub>j</sub> = 25 °C			0.01	mA
				-		mA
C <sub>ies</sub>	V <sub>CE</sub> = 25 V V <sub>GE</sub> = 0 V	f = 1 MHz		1.63		nF
C <sub>oes</sub>		f = 1 MHz		0.108		nF
C <sub>res</sub>		f = 1 MHz		0.05		nF
Q <sub>G</sub>	V <sub>GE</sub> = -7V ... +15V			275		nC
R <sub>Gint</sub>	T <sub>j</sub> = 25 °C			0		Ω
t <sub>d(on)</sub>	V <sub>CC</sub> = 300 V I <sub>C</sub> = 30 A	T <sub>j</sub> = 150 °C		24		ns
t <sub>r</sub>		T <sub>j</sub> = 150 °C		27		ns
E <sub>on</sub>	V <sub>GE neg</sub> = -7 V V <sub>GE pos</sub> = 15 V	T <sub>j</sub> = 150 °C		0.97		mJ
t <sub>d(off)</sub>	R <sub>G on</sub> = 25 Ω	T <sub>j</sub> = 150 °C		328		ns
t <sub>f</sub>	R <sub>G off</sub> = 25 Ω	T <sub>j</sub> = 150 °C		54		ns
E <sub>off</sub>	di/dt <sub>on</sub> = 2335 A/μs di/dt <sub>off</sub> = 2335 A/μs	T <sub>j</sub> = 150 °C		1.77		mJ
R <sub>th(j-s)</sub>	per IGBT, λ <sub>paste</sub> =0.8 W/(mK)			1.65		K/W

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Diode 1						
V <sub>F</sub>	I <sub>F</sub> = 30 A	T <sub>j</sub> = 25 °C		1.45	1.99	V
	chiplevel	T <sub>j</sub> = 150 °C		1.61	1.92	V
V <sub>F0</sub>	chiplevel	T <sub>j</sub> = 25 °C		0.99	1.10	V
		T <sub>j</sub> = 150 °C		0.80	0.89	V
r <sub>F</sub>	chiplevel	T <sub>j</sub> = 25 °C		18	30	mΩ
		T <sub>j</sub> = 150 °C		27	34	mΩ
I <sub>RRM</sub>	I <sub>F</sub> = 30 A	T <sub>j</sub> = 150 °C		30		A
Q <sub>rr</sub>	di/dt <sub>off</sub> = 2335 A/μs	T <sub>j</sub> = 150 °C		1.6		μC
E <sub>rr</sub>	V <sub>GE</sub> = -7 V	T <sub>j</sub> = 150 °C		0.26		mJ
	V <sub>CC</sub> = 300 V					
R <sub>th(j-s)</sub>	per Diode			2.1		K/W

# SK30GD066ETp



**SEMITOP® 3 Press-Fit**

## Sixpack Open Emitter

### SK30GD066ETp

#### Features\*


- One screw mounting module
- Low inductive design
- Press-Fit contact technology
- Fully compatible with other SEMITOP® Press-Fit types
- 600V Trench IGBT3 technology
- Robust and soft switching CAL HD diode technology
- Integrated NTC temperature sensor
- UL recognized, file no. E 63 532

#### Typical Applications

- Motor drives
- Servo drives
- Air conditioning
- Auxiliary Inverters
- UPS

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
<b>Module</b>					
$M_s$	to heatsink	2.25		2.5	Nm
w	weight		30		g

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
<b>Temperature Sensor</b>					
$R_{100}$	$T_r = 100\text{ °C}$		$493 \pm 5\%$		$\Omega$
$B_{100/125}$	$R(T) = R_{100} \exp[B_{100/125}(1/T - 1/T_{100})]$ ; $T[K]$		$3550 \pm 2\%$		K



**GD-ET**




Fig. 1: Typ. IGBT output characteristic, incl.  $R_{CC+EE'}$




Fig. 2: IGBT rated current vs. temperature  $I_C=f(T_s)$




Fig. 3: Typ. turn-on /-off energy =  $f(I_C)$




Fig. 4: Typ. turn-on /-off energy =  $f(R_G)$




Fig. 5: Typ. IGBT transfer characteristic




Fig. 6: Typ. IGBT gate charge characteristic




Fig. 7: Typ. switching times = f(I<sub>C</sub>)




Fig. 8: Typ. switching times = f(R<sub>G</sub>)




Fig. 9: Typ. transient thermal impedance





Fig. 10: Typ. Diode forward charact., incl. R<sub>CC'+EE'</sub>

Dimensions: mm

Tolerance system: ISO 2768-m



Suggested drilled hole diameter for terminal pins in the circuit board:


- minimum: 1.575 mm
- typical: 1.6 mm
- maximum: 1.625 mm

Suggested hole diameter for the mounting post in the circuit board:

- 2 mm

These documents are SEMIKRON properties. SEMIKRON reserves all copyrights. All copying and transmitting of this information requires written permission. For the case of industrial property rights, SEMIKRON reserves all rights.

## SEMITOP 3 Press-Fit



GD-ET

This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

## **\*IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.