


# SK80MB120CR03TE1



SEMITOP®E1

## Half-Bridge (Full SiC)

### SK80MB120CR03TE1

#### Features\*

- Optimized design for superior thermal performance
- Extremely low inductance design
- Press-Fit contact technology
- 1200V Planar Gen3 SiC MOSFET
- Simple to drive with +15V gate voltage
- Optimized switching stability thanks to module integrated gate resistors
- Integrated NTC temperature sensor
- UL recognized file no. E 63 532

#### Typical Applications


- Switched Mode Power Supplies
- Energy Storage Systems
- Electric Vehicle charging
- UPS
- Solar
- Motor Driver

#### Remarks

- Recommended  $T_{jop} = -40^{\circ}\text{C} \dots +150^{\circ}\text{C}$
- Recommended turn-off / turn-on gate voltage  $V_{GS} = -4 \dots 0 / +15\text{V}$


Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
<b>MOSFET</b>			
$V_{DSS}$	$T_j = 25^{\circ}\text{C}$	1200	V
$I_D$	HPTP / HP-PCM	$T_s = 25^{\circ}\text{C}$	100
	$T_j = 175^{\circ}\text{C}$	$T_s = 70^{\circ}\text{C}$	83
$I_{DM}$	Pulse width $t_p$ limited by $T_{vjmax}$	240	A
$V_{GS}$	Transient Gate - Source voltage ( $t < 100\text{ns}$ )	-8 ... 19	V
$T_j$		-40 ... 175	$^{\circ}\text{C}$
<b>Integrated body diode</b>			
$I_{FM}$	Pulse width $t_p$ limited by $T_{vjmax}$	240	A
$I_{FSM}$	$t_p = 10\text{ ms}$ , $\sin 180^{\circ}$ , $T_j = 150^{\circ}\text{C}$	403	A

Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
<b>Module</b>			
$I_{t(RMS)}$	$\Delta T_{terminal}$ at PCB joint = 30 K, per pin	30	A
$T_{stg}$	module without TIM	-40 ... 125	$^{\circ}\text{C}$
$V_{isol}$	AC, sinusoidal, $t = 1\text{ min}$	2500	V



MB-T

# SK80MB120CR03TE1



## Half-Bridge (Full SiC)

### SK80MB120CR03TE1

#### Features\*


- Optimized design for superior thermal performance
- Extremely low inductance design
- Press-Fit contact technology
- 1200V Planar Gen3 SiC MOSFET
- Simple to drive with +15V gate voltage
- Optimized switching stability thanks to module integrated gate resistors
- Integrated NTC temperature sensor
- UL recognized file no. E 63 532

#### Typical Applications

- Switched Mode Power Supplies
- Energy Storage Systems
- Electric Vehicle charging
- UPS
- Solar
- Motor Drives

#### Remarks

- Recommended  $T_{jop} = -40^{\circ}\text{C} \dots +150^{\circ}\text{C}$
- Recommended turn-off / turn-on gate voltage  $V_{GS} = -4 \dots 0/+15\text{V}$



Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
<b>MOSFET</b>					
$V_{(BR)DSS}$	$V_{GS} = 0\text{ V}, I_D = 0.2\text{ mA}, T_j = 25^{\circ}\text{C}$	1200			V
$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 23\text{ mA}, T_j = 25^{\circ}\text{C}$	1.8	2.5	3.6	V
$I_{DSS}$	$V_{GS} = 0\text{ V}, V_{DS} = 1200\text{ V}, T_j = 25^{\circ}\text{C}$			0.2	mA
$I_{GSS}$	$V_{DS} = 0\text{ V}, V_{GS} = 15\text{ V}, T_j = 25^{\circ}\text{C}$			400	nA
$R_{DS(on)}$	$V_{GS} = 15\text{ V}, I_D = 83\text{ A}, \text{chiplevel}$	$T_j = 25^{\circ}\text{C}$		16	mΩ
		$T_j = 150^{\circ}\text{C}$		25	mΩ
$C_{iss}$	$V_{GS} = 0\text{ V}, f = 0.1\text{ MHz}$		6800		pF
$C_{oss}$	$V_{DS} = 1000\text{ V}, f = 0.1\text{ MHz}$		260		pF
$C_{rss}$	$T_j = 25^{\circ}\text{C}, f = 0.1\text{ MHz}$		20		pF
$Q_G$	$V_{GS} = -4 \dots 15\text{ V}, V_{DD} = 800\text{ V}, I_D = 83\text{ A}$		236		nC
$R_{Gint}$	$T_j = 25^{\circ}\text{C}$		5.9		Ω
$t_{d(on)}$	$V_{DD} = 600\text{ V}, T_j = 150^{\circ}\text{C}$		36		ns
$t_{d(off)}$	$I_D = 80\text{ A}, T_j = 150^{\circ}\text{C}$		90		ns
$t_r$	$V_{GS} = -4/+15\text{ V}, T_j = 150^{\circ}\text{C}$		16		ns
$t_f$	$R_{Gon/off} = 1\text{ Ω}, T_j = 150^{\circ}\text{C}$		23		ns
$E_{on}$	$di/dt_{off} = 5.6\text{ kA/μs}, T_j = 150^{\circ}\text{C}$		1.02		mJ
$E_{off}$	$dv/dt = 28\text{ kV/μs}, L_s = 17\text{ nH}, T_j = 150^{\circ}\text{C}$		0.71		mJ
$R_{th(j-s)}$	per MOSFET, HPTP / HP-PCM		0.49		K/W
<b>Integrated body diode</b>					
$V_F = V_{SD}$	$-I_D = 80\text{ A}, V_{GS} = -4\text{ V}, \text{chiplevel}$	$T_j = 25^{\circ}\text{C}$	4.6		V
		$T_j = 150^{\circ}\text{C}$	4.3		V
$V_{F0} = V_{SD0}$	chiplevel	$T_j = 25^{\circ}\text{C}$	3.8		V
		$T_j = 150^{\circ}\text{C}$	3.6		V
$r_F = r_{SD}$	chiplevel	$T_j = 25^{\circ}\text{C}$	19		mΩ
		$T_j = 150^{\circ}\text{C}$	17		mΩ
$t_{rr}$	$V_{DD} = 600\text{ V}, T_j = 150^{\circ}\text{C}$		33		μs
$Q_{rr}$	$-I_D = 80\text{ A}, T_j = 150^{\circ}\text{C}$		1.4		μC
$I_{rr}$	$V_{GS} = -4\text{ V}, T_j = 150^{\circ}\text{C}$		86		A
$E_{rr}$	$R_{Gon} = 1\text{ Ω}, di/dt_{off} = 7\text{ kA/μs}, T_j = 150^{\circ}\text{C}$		0.74		mJ

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
<b>Module</b>					
$L_{CE}$			9		nH
$M_s$	to heatsink	1.6		2.3	Nm
w	weight		35		g

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
<b>Temperature Sensor</b>					
$R_{100}$	$T_r = 100^{\circ}\text{C}$		$493 \pm 5\%$		Ω
$B_{100/125}$	$R_{(T)} = R_{100} \cdot \exp[B_{100/125} \cdot (1/T - 1/T_{100})], T[K];$		$3550 (\pm 2\%)$		K




Fig. 1: Typ. MOSFET forward output characteristic, incl.  $R_{DS(on)}$  vs  $V_{DS}$




Fig. 1a: Typ. MOSFET reverse output characteristic, incl.  $R_{DS(on)}$  vs  $V_{DS}$




Fig. 2: MOSFET Rated current vs. temperature  $I_D = f(T_S)$




Fig. 3: Typ. MOSFET switching energy  $E = f(I_D)$  at  $R_{G1}$




Fig. 3a: Typ. MOSFET switching energy  $E = f(I_D)$  at  $R_{G2}$




Fig. 4: Typ. MOSFET switching energy  $E = f(R_G)$  at  $I_{D1}$




Fig. 4a: Typ. MOSFET switching energy  $E = f(R_G)$  at  $I_{D2}$




Fig. 5: Typ. MOSFET transfer characteristic




Fig. 6: Typ. MOSFET gate charge characteristic




Fig. 7: Typ. MOSFET switching times  $t = f(I_D)$  at  $R_{G1}$




Fig. 7a: Typ. MOSFET switching times  $t = f(I_D)$  at  $R_{G2}$













Fig. 8: Typ. MOSFET switching times  $t = f(R_G)$  at  $I_{D1}$





- Pin-Grid 3.2 mm
- Tolerance of PCB hole pattern  $\pm 0.1$
- Diameters of drill  $\varnothing 1.15\text{mm}$
- Copper thickness in hole 25 - 50  $\mu\text{m}$
- Hole specification for contacts:  
refer to SEMITOP E1/E2 Mounting Instruction

## Pinout and Dimensions



MB-T

This is an electrostatic discharge sensitive device (ESDS) according to international standard IEC 61340.

## **\*IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as any guarantee or assurance of product characteristics ("Beschaffheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of SEMIKRON products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Resulting from this, application adjustments of any kind may be necessary. Any user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing any physical injury, fire or other problem, also if any SEMIKRON product becomes faulty. Any user is responsible for making sure that the application design and realization are compliant with all laws, regulations, norms and standards applicable to the scope of application. Unless otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not convey any license under its or a third party's patent rights, copyrights, trade secrets or other intellectual property rights, neither does it make any representation or warranty of non-infringement of intellectual property rights of any third party which may arise from a user's applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all previous SEMIKRON information of comparable content and scope. SEMIKRON may update and/or revise this document at any time.