



SEMITRANS® 2

Fast Diode Modules


SKKD400F06

Features*

- Soft recovery
- Short recovery times
- Low switching losses
- Heat transfer through aluminum oxide ceramic insulated metal baseplate
- Hard soldered joints for high reliability
- UL recognized, file no. E63532

Typical Applications

- Self-commutated inverters
- DC choppers
- AC motor speed control
- Inductive heating
- Uninterruptible power supplies
- Electronic welders



SKKD

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
Diode				
VRRM	Tj = 25 °C		600	V
IF	Tj = 175 °C	Tc = 85 °C	402	A
		Tc = 100 °C	355	A
IFRM			800	A
IFSM	10 ms	Tj = 25 °C	3000	A
		Tj = 150 °C	2700	A
i²t	10 ms	Tj = 25 °C	45000	A²s
		Tj = 150 °C	36450	A²s
Tj			-40 ... 175	°C
Module				
Tstg			-40 ... 125	°C
Visol	a.c.; 50 Hz; r.m.s.	1 min	4000	V
		1 s	4800	V

Characteristics					
Symbol	Conditions		min.	typ.	max. Unit
Diode					
V _F	I _F = 400 A chiplevel	T _J = 25 °C	1.34	1.55	V
		T _J = 150 °C	1.26	1.50	V
V _{F0}	chiplevel	T _J = 25 °C	0.90	1.00	V
		T _J = 150 °C	0.70	0.78	V
r _F	chiplevel	T _J = 25 °C	1.10	1.37	mΩ
		T _J = 150 °C	1.40	1.80	mΩ
I _R	V _R = V _{RRM}	T _J = 25 °C	1		mA
		T _J = 150 °C	50		mA
Q _{rr}	I _F = 400 A di/dtoff = 2000 A/μs V _R = 300 V	T _J = 150 °C	35		μC
I _{RRM}		T _J = 150 °C	190		A
t _{rr}		T _J = 150 °C	235		ns
E _{rr}		T _J = 150 °C	7.0		mJ
R _{th(j-c)}	per diode		0.15		K/W
	per module		0.075		K/W
R _{th(c-s)}	per diode (λ _{grease} =0.81 W/(m*K))		0.065		K/W
	per module (λ _{grease} =0.81 W/(m*K))		0.035		K/W
Module					
L _{CE}			30		nH
R _{CC'+EE'}		T _C = 25 °C	0.40		mΩ
		T _C = 125 °C	0.55		mΩ
M _s	to heatsink M6		3.0	5.0	Nm
M _t	to terminals M5		2.5	5.0	Nm
a			5 * 9.81		m/s ²
w			165		g




Fig. 1: Typ. recovery charge vs. current decrease




Fig. 2: Peak recovery current vs. current decrease




Fig. 3: Transient thermal impedance vs. time




Fig. 4: Typ. forward charecteristics (terminal level)




Fig. 5: Surge overload current vs. time






Fig. 6: Typ. turn-off energy dissipation per pulse

Dimensions in mm



General tolerance ± 0.5 mm

SEMITRANS 2



SKKD

This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.