



SEMITRANS® 10

IGBT R8 Modules

SKM1000GAR17R8

Features*

- Symmetrical current sharing
- Low-inductive module design
- High mechanical robustness
- UL recognized, file no. E63532

Typical Applications

- Brake chopper
- Wind turbines

Remarks


Recommended $T_{jop} = -40 \dots +150^{\circ}\text{C}$

Absolute Maximum Ratings

Symbol	Conditions	Values	Unit
IGBT			
V_{CES}	$T_j = 25^{\circ}\text{C}$	1700	V
I_C	$T_j = 175^{\circ}\text{C}$	$T_c = 25^{\circ}\text{C}$	1574
		$T_c = 100^{\circ}\text{C}$	1027
I_{Cnom}		1000	A
I_{CRM}		2000	A
V_{GES}		-20 ... 20	V
t_{psc}	$V_{CC} = 1200\text{ V}$ $V_{GE} \leq 15\text{ V}$ $V_{CES} \leq 1700\text{ V}$	$T_j = 150^{\circ}\text{C}$	10
T_j		-40 ... 175	$^{\circ}\text{C}$
Inverse diode			
V_{RRM}	$T_j = 25^{\circ}\text{C}$	1700	V
I_F	$T_j = 175^{\circ}\text{C}$	$T_c = 25^{\circ}\text{C}$	1449
		$T_c = 100^{\circ}\text{C}$	905
I_{FRM}		2000	A
I_{FSM}	$t_p = 10\text{ ms, sin } 180^{\circ}, T_j = 25^{\circ}\text{C}$	6240	A
T_j		-40 ... 175	$^{\circ}\text{C}$
Freewheeling diode			
V_{RRM}	$T_j = 25^{\circ}\text{C}$	1700	V
I_F	$T_j = 175^{\circ}\text{C}$	$T_c = 25^{\circ}\text{C}$	1449
		$T_c = 100^{\circ}\text{C}$	905
I_{FRM}		2000	A
I_{FSM}	$t_p = 10\text{ ms, sin } 180^{\circ}, T_j = 25^{\circ}\text{C}$	6240	A
T_j		-40 ... 175	$^{\circ}\text{C}$
Module			
T_{stg}		-40 ... 150	$^{\circ}\text{C}$
V_{isol}	AC sinus 50 Hz, $t = 1\text{ min}$	4000	V

Characteristics

Symbol	Conditions	min.	typ.	max.	Unit
IGBT					
$V_{CE(sat)}$	$I_C = 1000\text{ A}$ $V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25^{\circ}\text{C}$	1.66	1.99	V
		$T_j = 150^{\circ}\text{C}$	2.01	2.33	V
V_{CE0}	chipelevel	$T_j = 25^{\circ}\text{C}$	1.06	1.12	V
		$T_j = 150^{\circ}\text{C}$	0.95	1.05	V
r_{CE}	$V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25^{\circ}\text{C}$	0.60	0.87	m Ω
		$T_j = 150^{\circ}\text{C}$	1.06	1.28	m Ω
$V_{GE(th)}$	$V_{CE} = 10\text{ V}, I_C = 36\text{ mA}$	5	5.8	6.5	V
I_{CES}	$V_{GE} = 0\text{ V}, V_{CE} = 1700\text{ V}, T_j = 25^{\circ}\text{C}$			6.0	mA
C_{ies}	$V_{CE} = 25\text{ V}$ $V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$	90.0		nF
C_{oes}		$f = 1\text{ MHz}$	3.00		nF
C_{res}		$f = 1\text{ MHz}$	0.24		nF
Q_G	$V_{GE} = -15\text{ V} \dots +15\text{ V}$		5640		nC
R_{Gint}	$T_j = 25^{\circ}\text{C}$		1.7		Ω



GAR



SEMITRANS® 10

IGBT R8 Modules

SKM1000GAR17R8

Features*


- Symmetrical current sharing
- Low-inductive module design
- High mechanical robustness
- UL recognized, file no. E63532

Typical Applications

- Brake chopper
- Wind turbines

Remarks

Recommended $T_{jop} = -40 \dots +150^{\circ}\text{C}$



GAR

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
t _{d(on)}	V _{CC} = 900 V	T _j = 150 °C		450		ns
t _r	I _C = 1000 A	T _j = 150 °C		95		ns
E _{on}	V _{GE} = +15/-15 V	T _j = 150 °C		415		mJ
t _{d(off)}	R _{G on} = 0.7 Ω	T _j = 150 °C		620		ns
t _f	R _{G off} = 0.7 Ω	T _j = 150 °C		155		ns
E _{off}	di/dt _{on} = 9.7 kA/μs	T _j = 150 °C				
	di/dt _{off} = 5.5 kA/μs					
	dv/dt = 4300 V/μs			345		mJ
	L _s = 36 nH	T _j = 150 °C				
R _{th(j-c)}	per IGBT				0.03	K/W
R _{th(c-s)}	per IGBT (λ _{grease} =0.81 W/(m*K))			0.016		K/W
Inverse diode						
V _F = V _{EC}	I _F = 1000 A	T _j = 25 °C		1.78	2.12	V
	V _{GE} = 0 V	T _j = 150 °C		1.81	2.14	V
	chiplevel					
V _{F0}		T _j = 25 °C		1.32	1.56	V
	chiplevel	T _j = 150 °C		1.08	1.22	V
r _F		T _j = 25 °C		0.46	0.56	mΩ
	chiplevel	T _j = 150 °C		0.73	0.92	mΩ
I _{RRM}	I _F = 1000 A	T _j = 150 °C		885		A
Q _{rr}	V _{GE} = -15 V	T _j = 150 °C		355		μC
E _{rr}	di/dt _{off} = 9.2 kA/μs					
	V _R = 900 V	T _j = 150 °C		185		mJ
R _{th(j-c)}	per diode				0.042	K/W
R _{th(c-s)}	per diode (λ _{grease} =0.81 W/(m*K))			0.017		K/W
Freewheeling diode						
V _F = V _{EC}	I _F = 1000 A	T _j = 25 °C		1.78	2.12	V
	V _{GE} = 0 V	T _j = 150 °C		1.81	2.14	V
	level = chiplevel					
V _{F0}		T _j = 25 °C		1.32	1.56	V
	chiplevel	T _j = 150 °C		1.08	1.22	V
r _F		T _j = 25 °C		0.46	0.56	mΩ
	chiplevel	T _j = 150 °C		0.73	0.92	mΩ
I _{RRM}	I _F = 1000 A	T _j = 150 °C		885		A
Q _{rr}	di/dt _{off} = 9.2 kA/μs	T _j = 150 °C		355		μC
E _{rr}	V _{GE} = -15 V					
	V _R = 900 V	T _j = 150 °C		185		mJ
R _{th(j-c)}	per diode				0.042	K/W
R _{th(c-s)}	per diode (λ _{grease} =0.81 W/(m*K))			0.017		K/W
Module						
L _{CE}				10		nH
R _{CC'+EE'}	measured per switch, T _C = 25 °C			0.2		mΩ
R _{th(c-s)1}	calculated without thermal coupling (λ _{grease} =0.81 W/(m*K))			0.0041		K/W
R _{th(c-s)2}	including thermal coupling, T _s underneath module (λ _{grease} =0.81 W/(m*K))			0.007		K/W
M _s	to heat sink M5		4		6	Nm
M _t		to terminals M8	8		10	Nm
		to terminals M4	1.8		2.1	Nm
w					1250	g

SKM1000GAR17R8



SEMITRANS® 10

IGBT R8 Modules

SKM1000GAR17R8

Features*

- Symmetrical current sharing
- Low-inductive module design
- High mechanical robustness
- UL recognized, file no. E63532


Typical Applications

- Brake chopper
- Windturbines

Remarks

Recommended $T_{jop} = -40 \dots +150^{\circ}\text{C}$

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
Temperature Sensor					
R_{100}	$T_c=100^{\circ}\text{C}$ ($R_{25}=5\text{ k}\Omega$)		$493 \pm 5\%$		Ω
$B_{100/125}$	$R(T)=R_{100}\exp[B_{100/125}(1/T-1/T_{100})]$; $T[\text{K}]$		$3550 \pm 2\%$		K



GAR




Fig. 1: Output characteristics IGBT (typical); $I_C = f(V_{CE})$; $V_{GE} = 15\text{V}$; (chiplevel)




Fig. 2: Output characteristics IGBT (typical); $I_C = f(V_{CE})$; $T_j = 150^\circ\text{C}$; (chiplevel)




Fig. 3: Switching losses IGBT (typical); $E=f(I_C)$




Fig. 4: Switching losses IGBT (typical); $E=f(R_G)$




Fig. 5: Transient thermal impedance IGBT










Fig. 6: RBSOA IGBT






Fig. 13: Typ. transfer characteristic








Fig. 14: Typ. gate charge characteristic


SKM1000GAR17R8

Module label



- Dimensions in mm
- General tolerances ± 0.5 mm

SEMITRANS 10



GAR

This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.