



⚠ CRITICAL CHARACTERISTICS
 ▽ KEY CHARACTERISTICS
 ○ INSPECTION
 MUST COMPLY TO ROHS DIRECTIVE 2011/65/EU

NOTE:
 1. BACK CHANNEL COOLING: BOTTOM IN TOP OUT
 2. CABLE FEED: BOTTOM ENTRY & BOTTOM OUT
 3. PLINTH HEIGHT CAN BE OF 100, 200, & 400mm HEIGHT.

INTERNAL INTERFACE CABLES ARE HIDDEN IN THE DRAWING FOR BETTER CLARITY

INTERPRET DIM. & TOL. PER ASME Y14.5M-1994 ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES UNLESS OTHERWISE SPECIFIED ±0.10 ±0.50 ±1.0		THIRD ANGLE PROJECTION 	SCALE 0.150	SIZE A1	MATERIAL FINISH DESCRIPTION
PMW CONTROLLED DRAWING NOT VALID WITHOUT FROZEN DATE IN ID STAMP				M-CAD-PLV-D10H-IP54 CIRCUIT BREAKER-DUOT-CM	
CHANGED DESIGNED CHECKED	SABARISH LAURI MAY-22-2019 JAN-23-2019				



